

---

**pandera**

**Niels Bantilan, Nigel Markey, Jean-Francois Zinque**

**Aug 06, 2021**



# INTRODUCTION

<b>1</b>	<b>Install</b>	<b>3</b>
<b>2</b>	<b>Quick Start</b>	<b>5</b>
<b>3</b>	<b>Schema Model</b>	<b>7</b>
<b>4</b>	<b>Informative Errors</b>	<b>9</b>
<b>5</b>	<b>Contributing</b>	<b>11</b>
<b>6</b>	<b>Issues</b>	<b>13</b>
6.1	DataFrame Schemas . . . . .	13
6.1.1	Column Validation . . . . .	13
6.1.1.1	Null Values in Columns . . . . .	14
6.1.1.2	Coercing Types on Columns . . . . .	15
6.1.1.3	Required Columns . . . . .	16
6.1.1.4	Ordered Columns . . . . .	16
6.1.1.5	Stand-alone Column Validation . . . . .	16
6.1.1.6	Column Regex Pattern Matching . . . . .	17
6.1.1.7	Handling Dataframe Columns not in the Schema . . . . .	19
6.1.1.8	Validating the order of the columns . . . . .	19
6.1.2	Index Validation . . . . .	20
6.1.3	MultiIndex Validation . . . . .	21
6.1.3.1	MultiIndex Columns . . . . .	21
6.1.3.2	MultiIndex Indexes . . . . .	21
6.1.4	Get Pandas Data Types . . . . .	22
6.1.5	DataFrameSchema Transformations . . . . .	23
6.2	Series Schemas . . . . .	25
6.3	Checks . . . . .	26
6.3.1	Checking column properties . . . . .	26
6.3.2	Built-in Checks . . . . .	26
6.3.3	Vectorized vs. Element-wise Checks . . . . .	26
6.3.4	Handling Null Values . . . . .	27
6.3.5	Column Check Groups . . . . .	27
6.3.6	Wide Checks . . . . .	28
6.3.7	Raise UserWarning on Check Failure . . . . .	29
6.3.8	Registering Custom Checks . . . . .	31
6.4	Hypothesis Testing . . . . .	31
6.4.1	Overview . . . . .	31
6.4.2	Wide Hypotheses . . . . .	32
6.5	Pandera Data Types (new) . . . . .	34

6.5.1	Motivations	34
6.5.2	DataType basics	34
6.5.3	Example	34
6.5.4	Parametrized data types	36
6.6	Decorators for Pipeline Integration	37
6.6.1	Check Input	37
6.6.2	Check Output	38
6.6.3	Check IO	39
6.6.4	Decorate Functions and Coroutines	40
6.7	Schema Inference	41
6.7.1	Schema Persistence	42
6.7.1.1	Write to a Python script	42
6.7.1.2	Write to YAML	43
6.8	Schema Models	44
6.8.1	Basic Usage	45
6.8.2	Converting to DataFrameSchema	46
6.8.3	Excluded attributes	47
6.8.4	Supported dtypes	47
6.8.4.1	Dtype aliases	47
6.8.4.2	Type Vs instance	47
6.8.4.3	Parametrized dtypes	47
6.8.4.3.1	Annotated	48
6.8.4.3.2	Field	48
6.8.5	Required Columns	49
6.8.6	Schema Inheritance	49
6.8.7	Config	50
6.8.8	MultiIndex	50
6.8.9	Custom Checks	51
6.8.9.1	Column/Index checks	51
6.8.9.2	DataFrame Checks	52
6.8.9.3	Inheritance	53
6.8.10	Aliases	54
6.9	Lazy Validation	55
6.10	Data Synthesis Strategies	57
6.10.1	Basic Usage	58
6.10.2	Usage in Unit Tests	58
6.10.3	Strategies and Examples from Schema Models	59
6.10.4	Checks as Constraints	59
6.10.4.1	Check Strategy Chaining	60
6.10.4.2	In-line Custom Checks	60
6.10.5	Defining Custom Strategies	61
6.11	Extensions	61
6.11.1	Registering Custom Check Methods	61
6.11.2	Specifying a Check Strategy	62
6.11.3	Check Types	63
6.11.3.1	Element-wise Checks	63
6.11.3.2	Groupby Checks	63
6.11.4	Registered Custom Checks with the Class-based API	64
6.12	Reading Third-Party Schema (new)	66
6.12.1	Frictionless Data Schema	66
6.13	API	68
6.13.1	Core	68
6.13.1.1	Schemas	68
6.13.1.1.1	pandera.schemas.DataFrameSchema	68

6.13.1.1.1.1	pandera.schemas.DataFrameSchema.__init__	71
6.13.1.1.1.2	pandera.schemas.DataFrameSchema.add_columns	72
6.13.1.1.1.3	pandera.schemas.DataFrameSchema.coerce_dtype	73
6.13.1.1.1.4	pandera.schemas.DataFrameSchema.example	73
6.13.1.1.1.5	pandera.schemas.DataFrameSchema.from_yaml	73
6.13.1.1.1.6	pandera.schemas.DataFrameSchema.get_dtypes	74
6.13.1.1.1.7	pandera.schemas.DataFrameSchema.remove_columns	74
6.13.1.1.1.8	pandera.schemas.DataFrameSchema.rename_columns	75
6.13.1.1.1.9	pandera.schemas.DataFrameSchema.reset_index	76
6.13.1.1.1.10	pandera.schemas.DataFrameSchema.select_columns	77
6.13.1.1.1.11	pandera.schemas.DataFrameSchema.set_index	78
6.13.1.1.1.12	pandera.schemas.DataFrameSchema.strategy	79
6.13.1.1.1.13	pandera.schemas.DataFrameSchema.to_script	80
6.13.1.1.1.14	pandera.schemas.DataFrameSchema.to_yaml	80
6.13.1.1.1.15	pandera.schemas.DataFrameSchema.update_column	80
6.13.1.1.1.16	pandera.schemas.DataFrameSchema.update_columns	81
6.13.1.1.1.17	pandera.schemas.DataFrameSchema.validate	82
6.13.1.1.1.18	pandera.schemas.DataFrameSchema.__call__	83
6.13.1.1.2	pandera.schemas.SeriesSchema	83
6.13.1.1.2.1	pandera.schemas.SeriesSchema.__init__	84
6.13.1.1.2.2	pandera.schemas.SeriesSchema.validate	85
6.13.1.1.2.3	pandera.schemas.SeriesSchema.__call__	86
6.13.1.2	Schema Components	86
6.13.1.2.1	pandera.schema_components.Column	86
6.13.1.2.1.1	pandera.schema_components.Column.__init__	88
6.13.1.2.1.2	pandera.schema_components.Column.coerce_dtype	89
6.13.1.2.1.3	pandera.schema_components.Column.example	89
6.13.1.2.1.4	pandera.schema_components.Column.get_regex_columns	89
6.13.1.2.1.5	pandera.schema_components.Column.set_name	89
6.13.1.2.1.6	pandera.schema_components.Column.strategy	89
6.13.1.2.1.7	pandera.schema_components.Column.strategy_component	90
6.13.1.2.1.8	pandera.schema_components.Column.validate	90
6.13.1.2.1.9	pandera.schema_components.Column.__call__	90
6.13.1.2.2	pandera.schema_components.Index	90
6.13.1.2.2.1	pandera.schema_components.Index.example	91
6.13.1.2.2.2	pandera.schema_components.Index.strategy	92
6.13.1.2.2.3	pandera.schema_components.Index.strategy_component	92
6.13.1.2.2.4	pandera.schema_components.Index.validate	92
6.13.1.2.2.5	pandera.schema_components.Index.__call__	92
6.13.1.2.3	pandera.schema_components.MultiIndex	93
6.13.1.2.3.1	pandera.schema_components.MultiIndex.__init__	94
6.13.1.2.3.2	pandera.schema_components.MultiIndex.coerce_dtype	95
6.13.1.2.3.3	pandera.schema_components.MultiIndex.example	95
6.13.1.2.3.4	pandera.schema_components.MultiIndex.strategy	95
6.13.1.2.3.5	pandera.schema_components.MultiIndex.validate	96
6.13.1.2.3.6	pandera.schema_components.MultiIndex.__call__	96
6.13.1.3	Checks	97
6.13.1.3.1	pandera.checks.Check	97
6.13.1.3.1.1	pandera.checks.Check.eq	100
6.13.1.3.1.2	pandera.checks.Check.equal_to	100
6.13.1.3.1.3	pandera.checks.Check.ge	100
6.13.1.3.1.4	pandera.checks.Check.greater_than	101
6.13.1.3.1.5	pandera.checks.Check.greater_than_or_equal_to	101
6.13.1.3.1.6	pandera.checks.Check.gt	101

6.13.1.3.1.7	pandera.checks.Check.in_range	102
6.13.1.3.1.8	pandera.checks.Check.isin	102
6.13.1.3.1.9	pandera.checks.Check.le	102
6.13.1.3.1.10	pandera.checks.Check.less_than	103
6.13.1.3.1.11	pandera.checks.Check.less_than_or_equal_to	103
6.13.1.3.1.12	pandera.checks.Check.lt	103
6.13.1.3.1.13	pandera.checks.Check.ne	104
6.13.1.3.1.14	pandera.checks.Check.not_equal_to	104
6.13.1.3.1.15	pandera.checks.Check.notin	104
6.13.1.3.1.16	pandera.checks.Check.str_contains	105
6.13.1.3.1.17	pandera.checks.Check.str_endswith	105
6.13.1.3.1.18	pandera.checks.Check.str_length	105
6.13.1.3.1.19	pandera.checks.Check.str_matches	105
6.13.1.3.1.20	pandera.checks.Check.str_startswith	106
6.13.1.3.1.21	pandera.checks.Check.__call__	106
6.13.1.3.2	pandera.hypotheses.Hypothesis	106
6.13.1.3.2.1	pandera.hypotheses.Hypothesis.__init__	109
6.13.1.3.2.2	pandera.hypotheses.Hypothesis.one_sample_ttest	110
6.13.1.3.2.3	pandera.hypotheses.Hypothesis.two_sample_ttest	112
6.13.1.3.2.4	pandera.hypotheses.Hypothesis.__call__	113
6.13.2	Data Types	114
6.13.2.1	Library-agnostic dtypes	114
6.13.2.1.1	pandera.dtypes.DataType	115
6.13.2.1.1.1	pandera.dtypes.DataType.__init__	115
6.13.2.1.1.2	pandera.dtypes.DataType.check	115
6.13.2.1.1.3	pandera.dtypes.DataType.coerce	115
6.13.2.1.1.4	pandera.dtypes.DataType.__call__	115
6.13.2.1.2	pandera.dtypes.Bool	116
6.13.2.1.2.1	pandera.dtypes.Bool.__init__	116
6.13.2.1.2.2	pandera.dtypes.Bool.check	116
6.13.2.1.2.3	pandera.dtypes.Bool.coerce	116
6.13.2.1.2.4	pandera.dtypes.Bool.__call__	116
6.13.2.1.3	pandera.dtypes.Timestamp	117
6.13.2.1.3.1	pandera.dtypes.Timestamp.__init__	117
6.13.2.1.3.2	pandera.dtypes.Timestamp.check	117
6.13.2.1.3.3	pandera.dtypes.Timestamp.coerce	117
6.13.2.1.3.4	pandera.dtypes.Timestamp.__call__	117
6.13.2.1.4	pandera.dtypes.DateTime	118
6.13.2.1.5	pandera.dtypes.Timedelta	118
6.13.2.1.5.1	pandera.dtypes.Timedelta.__init__	118
6.13.2.1.5.2	pandera.dtypes.Timedelta.check	118
6.13.2.1.5.3	pandera.dtypes.Timedelta.coerce	118
6.13.2.1.5.4	pandera.dtypes.Timedelta.__call__	119
6.13.2.1.6	pandera.dtypes.Category	119
6.13.2.1.6.1	pandera.dtypes.Category.__init__	119
6.13.2.1.6.2	pandera.dtypes.Category.check	119
6.13.2.1.6.3	pandera.dtypes.Category.coerce	120
6.13.2.1.6.4	pandera.dtypes.Category.__call__	120
6.13.2.1.7	pandera.dtypes.Float	120
6.13.2.1.7.1	pandera.dtypes.Float.__init__	120
6.13.2.1.7.2	pandera.dtypes.Float.check	120
6.13.2.1.7.3	pandera.dtypes.Float.coerce	121
6.13.2.1.7.4	pandera.dtypes.Float.__call__	121
6.13.2.1.8	pandera.dtypes.Float16	121

6.13.2.1.8.1	pandera.dtypes.Float16.__init__	121
6.13.2.1.8.2	pandera.dtypes.Float16.check	121
6.13.2.1.8.3	pandera.dtypes.Float16.coerce	122
6.13.2.1.8.4	pandera.dtypes.Float16.__call__	122
6.13.2.1.9	pandera.dtypes.Float32	122
6.13.2.1.9.1	pandera.dtypes.Float32.__init__	122
6.13.2.1.9.2	pandera.dtypes.Float32.check	122
6.13.2.1.9.3	pandera.dtypes.Float32.coerce	123
6.13.2.1.9.4	pandera.dtypes.Float32.__call__	123
6.13.2.1.10	pandera.dtypes.Float64	123
6.13.2.1.10.1	pandera.dtypes.Float64.__init__	123
6.13.2.1.10.2	pandera.dtypes.Float64.check	123
6.13.2.1.10.3	pandera.dtypes.Float64.coerce	124
6.13.2.1.10.4	pandera.dtypes.Float64.__call__	124
6.13.2.1.11	pandera.dtypes.Float128	124
6.13.2.1.11.1	pandera.dtypes.Float128.__init__	124
6.13.2.1.11.2	pandera.dtypes.Float128.check	124
6.13.2.1.11.3	pandera.dtypes.Float128.coerce	125
6.13.2.1.11.4	pandera.dtypes.Float128.__call__	125
6.13.2.1.12	pandera.dtypes.Int	125
6.13.2.1.12.1	pandera.dtypes.Int.__init__	125
6.13.2.1.12.2	pandera.dtypes.Int.check	125
6.13.2.1.12.3	pandera.dtypes.Int.coerce	126
6.13.2.1.12.4	pandera.dtypes.Int.__call__	126
6.13.2.1.13	pandera.dtypes.Int8	126
6.13.2.1.13.1	pandera.dtypes.Int8.__init__	126
6.13.2.1.13.2	pandera.dtypes.Int8.check	126
6.13.2.1.13.3	pandera.dtypes.Int8.coerce	127
6.13.2.1.13.4	pandera.dtypes.Int8.__call__	127
6.13.2.1.14	pandera.dtypes.Int16	127
6.13.2.1.14.1	pandera.dtypes.Int16.__init__	127
6.13.2.1.14.2	pandera.dtypes.Int16.check	127
6.13.2.1.14.3	pandera.dtypes.Int16.coerce	128
6.13.2.1.14.4	pandera.dtypes.Int16.__call__	128
6.13.2.1.15	pandera.dtypes.Int32	128
6.13.2.1.15.1	pandera.dtypes.Int32.__init__	128
6.13.2.1.15.2	pandera.dtypes.Int32.check	128
6.13.2.1.15.3	pandera.dtypes.Int32.coerce	129
6.13.2.1.15.4	pandera.dtypes.Int32.__call__	129
6.13.2.1.16	pandera.dtypes.Int64	129
6.13.2.1.16.1	pandera.dtypes.Int64.__init__	129
6.13.2.1.16.2	pandera.dtypes.Int64.check	129
6.13.2.1.16.3	pandera.dtypes.Int64.coerce	130
6.13.2.1.16.4	pandera.dtypes.Int64.__call__	130
6.13.2.1.17	pandera.dtypes.UInt	130
6.13.2.1.17.1	pandera.dtypes.UInt.__init__	130
6.13.2.1.17.2	pandera.dtypes.UInt.check	130
6.13.2.1.17.3	pandera.dtypes.UInt.coerce	131
6.13.2.1.17.4	pandera.dtypes.UInt.__call__	131
6.13.2.1.18	pandera.dtypes.UInt8	131
6.13.2.1.18.1	pandera.dtypes.UInt8.__init__	131
6.13.2.1.18.2	pandera.dtypes.UInt8.check	131
6.13.2.1.18.3	pandera.dtypes.UInt8.coerce	132
6.13.2.1.18.4	pandera.dtypes.UInt8.__call__	132

6.13.2.1.19	pandera.dtypes.UInt16	132
6.13.2.1.19.1	pandera.dtypes.UInt16.__init__	132
6.13.2.1.19.2	pandera.dtypes.UInt16.check	132
6.13.2.1.19.3	pandera.dtypes.UInt16.coerce	133
6.13.2.1.19.4	pandera.dtypes.UInt16.__call__	133
6.13.2.1.20	pandera.dtypes.UInt32	133
6.13.2.1.20.1	pandera.dtypes.UInt32.__init__	133
6.13.2.1.20.2	pandera.dtypes.UInt32.check	133
6.13.2.1.20.3	pandera.dtypes.UInt32.coerce	134
6.13.2.1.20.4	pandera.dtypes.UInt32.__call__	134
6.13.2.1.21	pandera.dtypes.UInt64	134
6.13.2.1.21.1	pandera.dtypes.UInt64.__init__	134
6.13.2.1.21.2	pandera.dtypes.UInt64.check	134
6.13.2.1.21.3	pandera.dtypes.UInt64.coerce	135
6.13.2.1.21.4	pandera.dtypes.UInt64.__call__	135
6.13.2.1.22	pandera.dtypes.Complex	135
6.13.2.1.22.1	pandera.dtypes.Complex.__init__	135
6.13.2.1.22.2	pandera.dtypes.Complex.check	135
6.13.2.1.22.3	pandera.dtypes.Complex.coerce	136
6.13.2.1.22.4	pandera.dtypes.Complex.__call__	136
6.13.2.1.23	pandera.dtypes.Complex64	136
6.13.2.1.23.1	pandera.dtypes.Complex64.__init__	136
6.13.2.1.23.2	pandera.dtypes.Complex64.check	136
6.13.2.1.23.3	pandera.dtypes.Complex64.coerce	137
6.13.2.1.23.4	pandera.dtypes.Complex64.__call__	137
6.13.2.1.24	pandera.dtypes.Complex128	137
6.13.2.1.24.1	pandera.dtypes.Complex128.__init__	137
6.13.2.1.24.2	pandera.dtypes.Complex128.check	137
6.13.2.1.24.3	pandera.dtypes.Complex128.coerce	138
6.13.2.1.24.4	pandera.dtypes.Complex128.__call__	138
6.13.2.1.25	pandera.dtypes.Complex256	138
6.13.2.1.25.1	pandera.dtypes.Complex256.__init__	138
6.13.2.1.25.2	pandera.dtypes.Complex256.check	138
6.13.2.1.25.3	pandera.dtypes.Complex256.coerce	139
6.13.2.1.25.4	pandera.dtypes.Complex256.__call__	139
6.13.2.1.26	pandera.dtypes.String	139
6.13.2.1.26.1	pandera.dtypes.String.__init__	139
6.13.2.1.26.2	pandera.dtypes.String.check	139
6.13.2.1.26.3	pandera.dtypes.String.coerce	140
6.13.2.1.26.4	pandera.dtypes.String.__call__	140
6.13.2.2	Pandas-specific Dtypes	140
6.13.2.2.1	pandera.engines.pandas_engine.BOOL	140
6.13.2.2.1.1	pandera.engines.pandas_engine.BOOL.__init__	141
6.13.2.2.1.2	pandera.engines.pandas_engine.BOOL.check	141
6.13.2.2.1.3	pandera.engines.pandas_engine.BOOL.coerce	141
6.13.2.2.1.4	pandera.engines.pandas_engine.BOOL.__call__	141
6.13.2.2.2	pandera.engines.pandas_engine.INT8	141
6.13.2.2.2.1	pandera.engines.pandas_engine.INT8.__init__	142
6.13.2.2.2.2	pandera.engines.pandas_engine.INT8.check	142
6.13.2.2.2.3	pandera.engines.pandas_engine.INT8.coerce	142
6.13.2.2.2.4	pandera.engines.pandas_engine.INT8.__call__	142
6.13.2.2.3	pandera.engines.pandas_engine.INT16	142
6.13.2.2.3.1	pandera.engines.pandas_engine.INT16.__init__	143
6.13.2.2.3.2	pandera.engines.pandas_engine.INT16.check	143



6.13.2.2.3.3	pandera.engines.pandas_engine.INT16.coerce	143
6.13.2.2.3.4	pandera.engines.pandas_engine.INT16.__call__	143
6.13.2.2.4	pandera.engines.pandas_engine.INT32	143
6.13.2.2.4.1	pandera.engines.pandas_engine.INT32.__init__	144
6.13.2.2.4.2	pandera.engines.pandas_engine.INT32.check	144
6.13.2.2.4.3	pandera.engines.pandas_engine.INT32.coerce	144
6.13.2.2.4.4	pandera.engines.pandas_engine.INT32.__call__	144
6.13.2.2.5	pandera.engines.pandas_engine.INT64	144
6.13.2.2.5.1	pandera.engines.pandas_engine.INT64.__init__	145
6.13.2.2.5.2	pandera.engines.pandas_engine.INT64.check	145
6.13.2.2.5.3	pandera.engines.pandas_engine.INT64.coerce	145
6.13.2.2.5.4	pandera.engines.pandas_engine.INT64.__call__	145
6.13.2.2.6	pandera.engines.pandas_engine.UINT8	145
6.13.2.2.6.1	pandera.engines.pandas_engine.UINT8.__init__	146
6.13.2.2.6.2	pandera.engines.pandas_engine.UINT8.check	146
6.13.2.2.6.3	pandera.engines.pandas_engine.UINT8.coerce	146
6.13.2.2.6.4	pandera.engines.pandas_engine.UINT8.__call__	146
6.13.2.2.7	pandera.engines.pandas_engine.UINT16	146
6.13.2.2.7.1	pandera.engines.pandas_engine.UINT16.__init__	147
6.13.2.2.7.2	pandera.engines.pandas_engine.UINT16.check	147
6.13.2.2.7.3	pandera.engines.pandas_engine.UINT16.coerce	147
6.13.2.2.7.4	pandera.engines.pandas_engine.UINT16.__call__	147
6.13.2.2.8	pandera.engines.pandas_engine.UINT32	147
6.13.2.2.8.1	pandera.engines.pandas_engine.UINT32.__init__	148
6.13.2.2.8.2	pandera.engines.pandas_engine.UINT32.check	148
6.13.2.2.8.3	pandera.engines.pandas_engine.UINT32.coerce	148
6.13.2.2.8.4	pandera.engines.pandas_engine.UINT32.__call__	148
6.13.2.2.9	pandera.engines.pandas_engine.UINT64	148
6.13.2.2.9.1	pandera.engines.pandas_engine.UINT64.__init__	149
6.13.2.2.9.2	pandera.engines.pandas_engine.UINT64.check	149
6.13.2.2.9.3	pandera.engines.pandas_engine.UINT64.coerce	149
6.13.2.2.9.4	pandera.engines.pandas_engine.UINT64.__call__	149
6.13.2.2.10	pandera.engines.pandas_engine.STRING	149
6.13.2.2.10.1	pandera.engines.pandas_engine.STRING.__init__	150
6.13.2.2.10.2	pandera.engines.pandas_engine.STRING.check	150
6.13.2.2.10.3	pandera.engines.pandas_engine.STRING.coerce	150
6.13.2.2.10.4	pandera.engines.pandas_engine.STRING.from_parametrized_dtype	150
6.13.2.2.10.5	pandera.engines.pandas_engine.STRING.__call__	150
6.13.2.2.11	pandera.engines.numpy_engine.Object	150
6.13.2.2.11.1	pandera.engines.numpy_engine.Object.__init__	151
6.13.2.2.11.2	pandera.engines.numpy_engine.Object.check	151
6.13.2.2.11.3	pandera.engines.numpy_engine.Object.coerce	151
6.13.2.2.11.4	pandera.engines.numpy_engine.Object.__call__	151
6.13.2.3	Utility functions	151
6.13.2.3.1	pandera.dtypes.is_subdtype	152
6.13.2.3.2	pandera.dtypes.is_float	152
6.13.2.3.3	pandera.dtypes.is_int	152
6.13.2.3.4	pandera.dtypes.is_uint	152
6.13.2.3.5	pandera.dtypes.is_complex	153
6.13.2.3.6	pandera.dtypes.is_numeric	153
6.13.2.3.7	pandera.dtypes.is_bool	153
6.13.2.3.8	pandera.dtypes.is_string	153
6.13.2.3.9	pandera.dtypes.is_datetime	153
6.13.2.3.10	pandera.dtypes.is_timedelta	153

6.13.2.3.11	<code>pandera.dtypes.immutable</code>	154
6.13.2.4	Engines	154
6.13.2.4.1	<code>pandera.engines.engine.Engine</code>	154
6.13.2.4.1.1	<code>pandera.engines.engine.Engine.dtype</code>	155
6.13.2.4.1.2	<code>pandera.engines.engine.Engine.get_registered_dtypes</code>	155
6.13.2.4.1.3	<code>pandera.engines.engine.Engine.register_dtype</code>	155
6.13.2.4.1.4	<code>pandera.engines.engine.Engine.__call__</code>	156
6.13.2.4.2	<code>pandera.engines.numpy_engine.Engine</code>	156
6.13.2.4.2.1	<code>pandera.engines.numpy_engine.Engine.dtype</code>	156
6.13.2.4.3	<code>pandera.engines.pandas_engine.Engine</code>	156
6.13.2.4.3.1	<code>pandera.engines.pandas_engine.Engine.dtype</code>	156
6.13.2.4.3.2	<code>pandera.engines.pandas_engine.Engine.numpy_dtype</code>	157
6.13.2.5	PandasDtype Enum	157
6.13.2.5.1	<code>pandera.engines.pandas_engine.PandasDtype</code>	157
6.13.3	Schema Models	158
6.13.3.1	Schema Model	158
6.13.3.1.1	<code>pandera.model.SchemaModel</code>	159
6.13.3.1.1.1	<code>pandera.model.SchemaModel.example</code>	159
6.13.3.1.1.2	<code>pandera.model.SchemaModel.strategy</code>	159
6.13.3.1.1.3	<code>pandera.model.SchemaModel.to_schema</code>	160
6.13.3.1.1.4	<code>pandera.model.SchemaModel.to_yaml</code>	160
6.13.3.1.1.5	<code>pandera.model.SchemaModel.validate</code>	160
6.13.3.2	Model Components	161
6.13.3.2.1	<code>pandera.model_components.Field</code>	161
6.13.3.2.2	<code>pandera.model_components.check</code>	162
6.13.3.2.3	<code>pandera.model_components.dataframe_check</code>	162
6.13.3.3	Typing	163
6.13.3.3.1	<code>pandera.typing</code>	163
6.13.3.4	Config	164
6.13.3.4.1	<code>pandera.model.BaseConfig</code>	164
6.13.4	Decorators	165
6.13.4.1	<code>pandera.decorators.check_input</code>	165
6.13.4.2	<code>pandera.decorators.check_output</code>	166
6.13.4.3	<code>pandera.decorators.check_io</code>	167
6.13.4.4	<code>pandera.decorators.check_types</code>	168
6.13.5	Schema Inference	169
6.13.5.1	<code>pandera.schema_inference.infer_schema</code>	169
6.13.6	IO Utilities	169
6.13.6.1	<code>pandera.io.from_yaml</code>	169
6.13.6.2	<code>pandera.io.to_yaml</code>	169
6.13.6.3	<code>pandera.io.to_script</code>	170
6.13.7	Data Synthesis Strategies	170
6.13.7.1	<code>pandera.strategies</code>	170
6.13.8	Extensions	176
6.13.8.1	<code>pandera.extensions</code>	177
6.13.9	Errors	178
6.13.9.1	<code>pandera.errors.SchemaError</code>	178
6.13.9.2	<code>pandera.errors.SchemaErrors</code>	178
6.13.9.3	<code>pandera.errors.SchemaInitError</code>	178
6.13.9.4	<code>pandera.errors.SchemaDefinitionError</code>	178
6.14	Contributing	178
6.14.1	Getting Started	178
6.14.2	Contributing to the Codebase	179
6.14.2.1	Environment Setup	179

6.14.2.1.1	Option 1: <code>miniconda</code> Setup	179
6.14.2.1.2	Option 2: <code>virtualenv</code> Setup	179
6.14.2.1.3	Run Tests	179
6.14.2.1.4	Build Documentation Locally	179
6.14.2.1.5	Set up <code>pre-commit</code>	180
6.14.2.2	Making Changes	180
6.14.2.3	Run the Full Test Suite Locally	180
6.14.2.3.1	Using <code>mamba</code> (optional)	180
6.14.2.4	Project Releases	180
6.14.2.5	Contributing Documentation	181
6.14.2.6	Contributing Bugfixes	181
6.14.2.7	Contributing Enhancements	181
6.14.2.8	Making Pull Requests	181
6.14.2.8.1	Bugfixes	181
6.14.2.8.2	Documentation	181
6.14.2.8.3	Enhancements	182
6.14.2.9	Questions, Ideas, General Discussion	182
6.14.2.10	Dataframe Schema Style Guides	182
<b>7</b>	<b>How to Cite</b>	<b>185</b>
7.1	Paper	185
7.2	Software Package	185
<b>8</b>	<b>License and Credits</b>	<b>187</b>
<b>9</b>	<b>Indices and tables</b>	<b>189</b>
	<b>Python Module Index</b>	<b>191</b>
	<b>Index</b>	<b>193</b>



*A data validation library for scientists, engineers, and analysts seeking correctness.*

pandera provides a flexible and expressive API for performing data validation on tidy (long-form) and wide data to make data processing pipelines more readable and robust.

pandas data structures contain information that pandera explicitly validates at runtime. This is useful in production-critical data pipelines or reproducible research settings. With pandera, you can:

1. *Check* the types and properties of columns in a `pd.DataFrame` or values in a `pd.Series`.
2. Perform more complex statistical validation like *hypothesis testing*.
3. Seamlessly integrate with existing data analysis/processing pipelines via *function decorators*.
4. Define schema models with the *class-based API* with pydantic-style syntax and validate dataframes using the typing syntax.
5. *Synthesize data* from schema objects for property-based testing with pandas data structures.



## INSTALL

Install with *pip*:

```
pip install pandera
```

Installing optional functionality:

```
pip install pandera[hypotheses] # hypothesis checks
pip install pandera[io]         # yaml/script schema io utilities
pip install pandera[strategies] # data synthesis strategies
pip install pandera[all]        # all packages
```

Or conda:

```
conda install -c conda-forge pandera-core # core library functionality
conda install -c conda-forge pandera      # pandera with all extensions
```





## QUICK START

```
import pandas as pd
import pandera as pa

# data to validate
df = pd.DataFrame({
    "column1": [1, 4, 0, 10, 9],
    "column2": [-1.3, -1.4, -2.9, -10.1, -20.4],
    "column3": ["value_1", "value_2", "value_3", "value_2", "value_1"],
})

# define schema
schema = pa.DataFrameSchema({
    "column1": pa.Column(int, checks=pa.Check.le(10)),
    "column2": pa.Column(float, checks=pa.Check.lt(-1.2)),
    "column3": pa.Column(str, checks=[
        pa.Check.str_startswith("value_"),
        # define custom checks as functions that take a series as input and
        # outputs a boolean or boolean Series
        pa.Check(lambda s: s.str.split("_", expand=True).shape[1] == 2)
    ]),
})

validated_df = schema(df)
print(validated_df)
```

```
   column1  column2  column3
0         1    -1.3  value_1
1         4    -1.4  value_2
2         0    -2.9  value_3
3        10   -10.1  value_2
4         9   -20.4  value_1
```

You can pass the built-in python types that are supported by pandas, or strings representing the legal pandas datatypes, or pandera's `DataType`:

```
schema = pa.DataFrameSchema({
    # built-in python types
    "int_column": pa.Column(int),
    "float_column": pa.Column(float),
    "str_column": pa.Column(str),
```

(continues on next page)

(continued from previous page)

```
# pandas dtype string aliases
"int_column2": pa.Column("int64"),
"float_column2": pa.Column("float64"),
# pandas > 1.0.0 support native "string" type
"str_column2": pa.Column("str"),

# pandera DataType
"int_column3": pa.Column(pa.Int),
"float_column3": pa.Column(pa.Float),
"str_column3": pa.Column(pa.String),
})
```

For more details on data types, see *DataType*

## SCHEMA MODEL

pandera also provides an alternative API for expressing schemas inspired by [dataclasses](#) and [pydantic](#). The equivalent *SchemaModel* for the above DataFrameSchema would be:

```
from pandera.typing import Series

class Schema(pa.SchemaModel):

    column1: Series[int] = pa.Field(le=10)
    column2: Series[float] = pa.Field(lt=-1.2)
    column3: Series[str] = pa.Field(str_startswith="value_")

    @pa.check("column3")
    def column_3_check(cls, series: Series[str]) -> Series[bool]:
        """Check that column3 values have two elements after being split with '_'"""
        return series.str.split("_", expand=True).shape[1] == 2

Schema.validate(df)
```



## INFORMATIVE ERRORS

If the dataframe does not pass validation checks, `pandera` provides useful error messages. An `error` argument can also be supplied to `Check` for custom error messages.

In the case that a validation `Check` is violated:

```
import pandas as pd

from pandera import Column, DataFrameSchema, Int, Check

simple_schema = DataFrameSchema({
    "column1": Column(
        Int, Check(lambda x: 0 <= x <= 10, element_wise=True,
                    error="range checker [0, 10]"))
})

# validation rule violated
fail_check_df = pd.DataFrame({
    "column1": [-20, 5, 10, 30],
})

simple_schema(fail_check_df)
```

Traceback (most recent call last):

```
...
SchemaError: <Schema Column: 'column1' type=<class 'int'>> failed element-wise validator.
->0:
<Check <lambda>: range checker [0, 10]>
failure cases:
   index  failure_case
0      0             -20
1      3              30
```

And in the case of a mis-specified column name:

```
# column name mis-specified
wrong_column_df = pd.DataFrame({
    "foo": ["bar"] * 10,
    "baz": [1] * 10
})

simple_schema.validate(wrong_column_df)
```

```
Traceback (most recent call last):
...
pandera.SchemaError: column 'column1' not in dataframe
   foo  baz
0  bar   1
1  bar   1
2  bar   1
3  bar   1
4  bar   1
```

## CONTRIBUTING

All contributions, bug reports, bug fixes, documentation improvements, enhancements and ideas are welcome.

A detailed overview on how to contribute can be found in the [contributing guide](#) on GitHub.





Submit issues, feature requests or bugfixes on [github](#).

## 6.1 DataFrame Schemas

The `DataFrameSchema` class enables the specification of a schema that verifies the columns and index of a pandas `DataFrame` object.

The `DataFrameSchema` object consists of `Columns` and an `Index`.

```
import pandera as pa

from pandera import Column, DataFrameSchema, Check, Index

schema = DataFrameSchema(
    {
        "column1": Column(int),
        "column2": Column(float, Check(lambda s: s < -1.2)),
        # you can provide a list of validators
        "column3": Column(str, [
            Check(lambda s: s.str.startswith("value")),
            Check(lambda s: s.str.split("_", expand=True).shape[1] == 2)
        ]),
    },
    index=Index(int),
    strict=True,
    coerce=True,
)
```

### 6.1.1 Column Validation

A `Column` must specify the properties of a column in a dataframe object. It can be optionally verified for its data type, *null values* or duplicate values. The column can be *coerced* into the specified type, and the *required* parameter allows control over whether or not the column is allowed to be missing.

Similarly to pandas, the data type can be specified as:

- a string alias, as long as it is recognized by pandas.
- a python type: `int`, `float`, `double`, `bool`, `str`
- a numpy data type

- a pandas extension type: it can be an instance (e.g `pd.CategoricalDtype(["a", "b"])`) or a class (e.g `pandas.CategoricalDtype`) if it can be initialized with default values.
- a pandera `DataType`: it can also be an instance or a class.

`Column checks` allow for the DataFrame's values to be checked against a user-provided function. Check objects also support `grouping` by a different column so that the user can make assertions about subsets of the column of interest.

Column Hypotheses enable you to perform statistical hypothesis tests on a DataFrame in either wide or tidy format. See *Hypothesis Testing* for more details.

### 6.1.1.1 Null Values in Columns

By default, SeriesSchema/Column objects assume that values are not nullable. In order to accept null values, you need to explicitly specify `nullable=True`, or else you'll get an error.

```
import numpy as np
import pandas as pd
import pandera as pa

from pandera import Check, Column, DataFrameSchema

df = pd.DataFrame({"column1": [5, 1, np.nan]})

non_null_schema = DataFrameSchema({
    "column1": Column(float, Check(lambda x: x > 0))
})

non_null_schema.validate(df)
```

```
Traceback (most recent call last):
...
SchemaError: non-nullable series contains null values: {2: nan}
```

```
null_schema = DataFrameSchema({
    "column1": Column(float, Check(lambda x: x > 0), nullable=True)
})

print(null_schema.validate(df))
```

```
   column1
0      5.0
1      1.0
2      NaN
```

### 6.1.1.2 Coercing Types on Columns

If you specify `Column(dtype, ..., coerce=True)` as part of the `DataFrameSchema` definition, calling `schema.validate` will first coerce the column into the specified `dtype` before applying validation checks.

```
import pandas as pd
import pandera as pa

from pandera import Column, DataFrameSchema

df = pd.DataFrame({"column1": [1, 2, 3]})
schema = DataFrameSchema({"column1": Column(str, coerce=True)})

validated_df = schema.validate(df)
assert isinstance(validated_df.column1.iloc[0], str)
```

**Note:** Note the special case of integers columns not supporting nan values. In this case, `schema.validate` will complain if `coerce == True` and null values are allowed in the column.

```
df = pd.DataFrame({"column1": [1., 2., 3, np.nan]})
schema = DataFrameSchema({
    "column1": Column(int, coerce=True, nullable=True)
})

validated_df = schema.validate(df)
```

Traceback (most recent call last):

```
...
pandera.errors.SchemaError: Error while coercing 'column1' to type int64: Cannot convert_
↪non-finite values (NA or inf) to integer
```

The best way to handle this case is to simply specify the column as a `Float` or `Object`.

```
schema_object = DataFrameSchema({
    "column1": Column(object, coerce=True, nullable=True)
})
schema_float = DataFrameSchema({
    "column1": Column(float, coerce=True, nullable=True)
})

print(schema_object.validate(df).dtypes)
print(schema_float.validate(df).dtypes)
```

```
column1    object
dtype: object
column1    float64
dtype: object
```

If you want to coerce all of the columns specified in the `DataFrameSchema`, you can specify the `coerce` argument with `DataFrameSchema(..., coerce=True)`.

### 6.1.1.3 Required Columns

By default all columns specified in the schema are required, meaning that if a column is missing in the input DataFrame an exception will be thrown. If you want to make a column optional, specify `required=False` in the column constructor:

```
import pandas as pd
import pandera as pa

from pandera import Column, DataFrameSchema

df = pd.DataFrame({"column2": ["hello", "pandera"]})
schema = DataFrameSchema({
    "column1": Column(int, required=False),
    "column2": Column(str)
})

validated_df = schema.validate(df)
print(validated_df)
```

```
   column2
0  hello
1  pandera
```

Since `required=True` by default, missing columns would raise an error:

```
schema = DataFrameSchema({
    "column1": Column(int),
    "column2": Column(str),
})

schema.validate(df)
```

```
Traceback (most recent call last):
...
pandera.SchemaError: column 'column1' not in dataframe
   column2
0  hello
1  pandera
```

### 6.1.1.4 Ordered Columns

### 6.1.1.5 Stand-alone Column Validation

In addition to being used in the context of a `DataFrameSchema`, `Column` objects can also be used to validate columns in a dataframe on its own:

```
import pandas as pd
import pandera as pa

df = pd.DataFrame({
    "column1": [1, 2, 3],
```

(continues on next page)

(continued from previous page)

```

    "column2": ["a", "b", "c"],
})

column1_schema = pa.Column(int, name="column1")
column2_schema = pa.Column(str, name="column2")

# pass the dataframe as an argument to the Column object callable
df = column1_schema(df)
validated_df = column2_schema(df)

# or explicitly use the validate method
df = column1_schema.validate(df)
validated_df = column2_schema.validate(df)

# use the DataFrame.pipe method to validate two columns
validated_df = df.pipe(column1_schema).pipe(column2_schema)

```

For multi-column use cases, the `DataFrameSchema` is still recommended, but if you have one or a small number of columns to verify, using `Column` objects by themselves is appropriate.

### 6.1.1.6 Column Regex Pattern Matching

In the case that your dataframe has multiple columns that share common statistical properties, you might want to specify a regex pattern that matches a set of meaningfully grouped columns that have `str` names.

```

import numpy as np
import pandas as pd
import pandera as pa

categories = ["A", "B", "C"]

np.random.seed(100)

dataframe = pd.DataFrame({
    "cat_var_1": np.random.choice(categories, size=100),
    "cat_var_2": np.random.choice(categories, size=100),
    "num_var_1": np.random.uniform(0, 10, size=100),
    "num_var_2": np.random.uniform(20, 30, size=100),
})

schema = pa.DataFrameSchema({
    "num_var_+": pa.Column(
        float,
        checks=pa.Check.greater_than_or_equal_to(0),
        regex=True,
    ),
    "cat_var_+": pa.Column(
        pa.Category,
        checks=pa.Check.isin(categories),
        coerce=True,
        regex=True,
    )
})

```

(continues on next page)

(continued from previous page)

```

    ),
})

print(schema.validate(dataframe).head())

```

	cat_var_1	cat_var_2	num_var_1	num_var_2
0	A	A	6.804147	24.743304
1	A	C	3.684308	22.774633
2	A	C	5.911288	28.416588
3	C	A	4.790627	21.951250
4	C	B	4.504166	28.563142

You can also regex pattern match on `pd.MultiIndex` columns:

```

np.random.seed(100)

dataframe = pd.DataFrame({
    ("cat_var_1", "y1"): np.random.choice(categories, size=100),
    ("cat_var_2", "y2"): np.random.choice(categories, size=100),
    ("num_var_1", "x1"): np.random.uniform(0, 10, size=100),
    ("num_var_2", "x2"): np.random.uniform(0, 10, size=100),
})

schema = pa.DataFrameSchema({
    ("num_var_.+", "x.+"): pa.Column(
        float,
        checks=pa.Check.greater_than_or_equal_to(0),
        regex=True,
    ),
    ("cat_var_.+", "y.+"): pa.Column(
        pa.Category,
        checks=pa.Check.isin(categories),
        coerce=True,
        regex=True,
    ),
})

print(schema.validate(dataframe).head())

```

	cat_var_1	cat_var_2	num_var_1	num_var_2
	y1	y2	x1	x2
0	A	A	6.804147	4.743304
1	A	C	3.684308	2.774633
2	A	C	5.911288	8.416588
3	C	A	4.790627	1.951250
4	C	B	4.504166	8.563142

### 6.1.1.7 Handling Dataframe Columns not in the Schema

By default, columns that aren't specified in the schema aren't checked. If you want to check that the DataFrame *only* contains columns in the schema, specify `strict=True`:

```
import pandas as pd
import pandera as pa

from pandera import Column, DataFrameSchema

schema = DataFrameSchema(
    {"column1": Column(int)},
    strict=True)

df = pd.DataFrame({"column2": [1, 2, 3]})

schema.validate(df)
```

Traceback (most recent call last):

```
...
SchemaError: column 'column2' not in DataFrameSchema {'column1': <Schema Column: 'None'
↳ type=DataType(int64)>}
```

Alternatively, if your DataFrame contains columns that are not in the schema, and you would like these to be dropped on validation, you can specify `strict='filter'`.

```
import pandas as pd
import pandera as pa

from pandera import Column, DataFrameSchema

df = pd.DataFrame({"column1": ["drop", "me"], "column2": ["keep", "me"]})
schema = DataFrameSchema({"column2": Column(str)}, strict='filter')

validated_df = schema.validate(df)
print(validated_df)
```

```
   column2
0      keep
1        me
```

### 6.1.1.8 Validating the order of the columns

For some applications the order of the columns is important. For example:

- If you want to use [selection by position](#) instead of the more common [selection by label](#).
- Machine learning: Many ML libraries will cast a DataFrame to numpy arrays, for which order becomes crucial.

To validate the order of the DataFrame columns, specify `ordered=True`:

```
import pandas as pd
import pandera as pa
```

(continues on next page)

(continued from previous page)

```
schema = pa.DataFrameSchema(  
    columns={"a": pa.Column(int), "b": pa.Column(int)}, ordered=True  
)  
df = pd.DataFrame({"b": [1], "a": [1]})  
print(schema.validate(df))
```

```
Traceback (most recent call last):  
...  
SchemaError: column 'b' out-of-order
```

## 6.1.2 Index Validation

You can also specify an *Index* in the *DataFrameSchema*.

```
import pandas as pd  
import pandera as pa  
  
from pandera import Column, DataFrameSchema, Index, Check  
  
schema = DataFrameSchema(  
    columns={"a": Column(int)},  
    index=Index(  
        str,  
        Check(lambda x: x.str.startswith("index_"))))  
  
df = pd.DataFrame(  
    data={"a": [1, 2, 3]},  
    index=["index_1", "index_2", "index_3"])  
  
print(schema.validate(df))
```

```
      a  
index_1  1  
index_2  2  
index_3  3
```

In the case that the DataFrame index doesn't pass the Check.

```
df = pd.DataFrame(  
    data={"a": [1, 2, 3]},  
    index=["foo1", "foo2", "foo3"])  
  
schema.validate(df)
```

```
Traceback (most recent call last):  
...  
SchemaError: <Schema Index> failed element-wise validator 0:  
<lambda>  
failure cases:
```

(continues on next page)



(continued from previous page)

	index	count
failure_case		
foo1	[0]	1
foo2	[1]	1
foo3	[2]	1

### 6.1.3 MultiIndex Validation

pandera also supports multi-index column and index validation.

#### 6.1.3.1 MultiIndex Columns

Specifying multi-index columns follows the pandas syntax of specifying tuples for each level in the index hierarchy:

```
import pandas as pd
import pandera as pa

from pandera import Column, DataFrameSchema, Index

schema = DataFrameSchema({
    ("foo", "bar"): Column(int),
    ("foo", "baz"): Column(str)
})

df = pd.DataFrame({
    ("foo", "bar"): [1, 2, 3],
    ("foo", "baz"): ["a", "b", "c"],
})

print(schema.validate(df))
```

	foo	bar	baz
0	1	a	
1	2	b	
2	3	c	

#### 6.1.3.2 MultiIndex Indexes

The *MultiIndex* class allows you to define multi-index indexes by composing a list of `pandera.Index` objects.

```
import pandas as pd
import pandera as pa

from pandera import Column, DataFrameSchema, Index, MultiIndex, Check

schema = DataFrameSchema(
    columns={"column1": Column(int)},
    index=MultiIndex([
```

(continues on next page)

(continued from previous page)

```

        Index(str,
              Check(lambda s: s.isin(["foo", "bar"])),
              name="index0"),
        Index(int, name="index1"),
    ])
)

df = pd.DataFrame(
    data={"column1": [1, 2, 3]},
    index=pd.MultiIndex.from_arrays(
        ["foo", "bar", "foo"], [0, 1, 2]),
    names=["index0", "index1"]
)

print(schema.validate(df))

```

		column1
index0	index1	
foo	0	1
bar	1	2
foo	2	3

### 6.1.4 Get Pandas Data Types

Pandas provides a *dtype* parameter for casting a dataframe to a specific dtype schema. *DataFrameSchema* provides a *dtypes* property which returns a dictionary whose keys are column names and values are *DataTypes*.

Some examples of where this can be provided to pandas are:

- [https://pandas.pydata.org/pandas-docs/stable/reference/api/pandas.read\\_csv.html](https://pandas.pydata.org/pandas-docs/stable/reference/api/pandas.read_csv.html)
- <https://pandas.pydata.org/pandas-docs/stable/reference/api/pandas.DataFrame.astype.html>

```

import pandas as pd
import pandera as pa

schema = pa.DataFrameSchema(
    columns={
        "column1": pa.Column(int),
        "column2": pa.Column(pa.Category),
        "column3": pa.Column(bool)
    },
)

df = (
    pd.DataFrame.from_dict(
        {
            "a": {"column1": 1, "column2": "valueA", "column3": True},
            "b": {"column1": 1, "column2": "valueB", "column3": True},
        },
        orient="index",
    )
)

```

(continues on next page)

(continued from previous page)

```

    )
    .astype({col: str(dtype) for col, dtype in schema.dtypes.items()})
    .sort_index(axis=1)
)

print(schema.validate(df))

```

	column1	column2	column3
a	1	valueA	True
b	1	valueB	True

### 6.1.5 DataFrameSchema Transformations

Once you've defined a schema, you can then make modifications to it, both on the schema level – such as adding or removing columns and setting or resetting the index – or on the column level – such as changing the data type or checks.

This is useful for re-using schema objects in a data pipeline when additional computation has been done on a dataframe, where the column objects may have changed or perhaps where additional checks may be required.

```

import pandas as pd
import pandera as pa

data = pd.DataFrame({"col1": range(1, 6)})

schema = pa.DataFrameSchema(
    columns={"col1": pa.Column(int, pa.Check(lambda s: s >= 0))},
    strict=True)

transformed_schema = schema.add_columns({
    "col2": pa.Column(str, pa.Check(lambda s: s == "value")),
    "col3": pa.Column(float, pa.Check(lambda x: x == 0.0)),
})

# validate original data
data = schema.validate(data)

# transformation
transformed_data = data.assign(col2="value", col3=0.0)

# validate transformed data
print(transformed_schema.validate(transformed_data))

```

	col1	col2	col3
0	1	value	0.0
1	2	value	0.0
2	3	value	0.0
3	4	value	0.0
4	5	value	0.0

Similarly, if you want dropped columns to be explicitly validated in a data pipeline:

```
import pandera as pa

schema = pa.DataFrameSchema(
    columns={
        "col1": pa.Column(int, pa.Check(lambda s: s >= 0)),
        "col2": pa.Column(str, pa.Check(lambda x: x <= 0)),
        "col3": pa.Column(object, pa.Check(lambda x: x == 0)),
    },
    strict=True,
)

new_schema = schema.remove_columns(["col2", "col3"])
print(new_schema)
```

```
<Schema DataFrameSchema(
  columns={
    'col1': <Schema Column(name=col1, type=DataType(int64))>
  },
  checks=[],
  coerce=False,
  dtype=None,
  index=None,
  strict=True
  name=None,
  ordered=False
)>
```

If during the course of a data pipeline one of your columns is moved into the index, you can simply update the initial input schema using the `set_index()` method to create a schema for the pipeline output.

```
import pandera as pa

from pandera import Column, DataFrameSchema, Check, Index

schema = DataFrameSchema(
    {
        "column1": Column(int),
        "column2": Column(float)
    },
    index=Index(int, name = "column3"),
    strict=True,
    coerce=True,
)

print(schema.set_index(["column1"], append = True))
```

```
<Schema DataFrameSchema(
  columns={
    'column2': <Schema Column(name=column2, type=DataType(float64))>
  },
  checks=[],
  coerce=True,
  dtype=None,
```

(continues on next page)

(continued from previous page)

```

index=<Schema MultiIndex(
  indexes=[
    <Schema Index(name=column3, type=DataType(int64))>
    <Schema Index(name=column1, type=DataType(int64))>
  ]
  coerce=False,
  strict=False,
  name=None,
  ordered=True
)>,
strict=True
name=None,
ordered=False
)>

```

The available methods for altering the schema are: `add_columns()`, `remove_columns()`, `update_columns()`, `rename_columns()`, `set_index()`, and `reset_index()`.

## 6.2 Series Schemas

The `SeriesSchema` class allows for the validation of pandas Series objects, and are very similar to `columns` and `indexes` described in `DataFrameSchemas`.

```

import pandas as pd
import pandera as pa

# specify multiple validators
schema = pa.SeriesSchema(
    str,
    checks=[
        pa.Check(lambda s: s.str.startswith("foo")),
        pa.Check(lambda s: s.str.endswith("bar")),
        pa.Check(lambda x: len(x) > 3, element_wise=True)
    ],
    nullable=False,
    allow_duplicates=True,
    name="my_series")

validated_series = schema.validate(
    pd.Series(["foobar", "foobar", "foobar"], name="my_series"))
print(validated_series)

```

```

0    foobar
1    foobar
2    foobar
Name: my_series, dtype: object

```

## 6.3 Checks

### 6.3.1 Checking column properties

*Check* objects accept a function as a required argument, which is expected to take a `pa.Series` input and output a boolean or a Series of boolean values. For the check to pass, all of the elements in the boolean series must evaluate to True, for example:

```
import pandera as pa

check_lt_10 = pa.Check(lambda s: s <= 10)

schema = pa.DataFrameSchema({"column1": pa.Column(int, check_lt_10)})
schema.validate(pd.DataFrame({"column1": range(10)}))
```

Multiple checks can be applied to a column:

```
schema = pa.DataFrameSchema({
    "column2": pa.Column(str, [
        pa.Check(lambda s: s.str.startswith("value")),
        pa.Check(lambda s: s.str.split("_", expand=True).shape[1] == 2)
    ]),
})
```

### 6.3.2 Built-in Checks

For common validation tasks, built-in checks are available in pandera.

```
import pandera as pa
from pandera import Column, Check, DataFrameSchema

schema = DataFrameSchema({
    "small_values": Column(float, Check.less_than(100)),
    "one_to_three": Column(int, Check.isin([1, 2, 3])),
    "phone_number": Column(str, Check.str_matches(r'^[a-z0-9-]+$')),
})
```

See the *Check* API reference for a complete list of built-in checks.

### 6.3.3 Vectorized vs. Element-wise Checks

By default, *Check* objects operate on `pd.Series` objects. If you want to make atomic checks for each element in the Column, then you can provide the `element_wise=True` keyword argument:

```
import pandas as pd
import pandera as pa

schema = pa.DataFrameSchema({
    "a": pa.Column(
        int,
        checks=[
```

(continues on next page)

(continued from previous page)

```

    # a vectorized check that returns a bool
    pa.Check(lambda s: s.mean() > 5, element_wise=False),

    # a vectorized check that returns a boolean series
    pa.Check(lambda s: s > 0, element_wise=False),

    # an element-wise check that returns a bool
    pa.Check(lambda x: x > 0, element_wise=True),
]
),
})
df = pd.DataFrame({"a": [4, 4, 5, 6, 6, 7, 8, 9]})
schema.validate(df)

```

`element_wise == False` by default so that you can take advantage of the speed gains provided by the `pd.Series` API by writing vectorized checks.

### 6.3.4 Handling Null Values

By default, `pandera` drops null values before passing the objects to validate into the check function. For `Series` objects null elements are dropped (this also applies to columns), and for `DataFrame` objects, rows with any null value are dropped.

If you want to check the properties of a pandas data structure while preserving null values, specify `Check(..., ignore_na=False)` when defining a check.

Note that this is different from the `nullable` argument in `Column` objects, which simply checks for null values in a column.

### 6.3.5 Column Check Groups

`Column` checks support grouping by a different column so that you can make assertions about subsets of the column of interest. This changes the function signature of the `Check` function so that its input is a dict where keys are the group names and values are subsets of the series being validated.

Specifying `groupby` as a column name, list of column names, or callable changes the expected signature of the `Check` function argument to:

```
Callable[Dict[Any, pd.Series] -> Union[bool, pd.Series]]
```

where the dict keys are the discrete keys in the `groupby` columns.

In the example below we define a `DataFrameSchema` with column checks for `height_in_feet` using a single column, multiple columns, and a more complex `groupby` function that creates a new column `age_less_than_15` on the fly.

```

import pandas as pd
import pandera as pa

schema = pa.DataFrameSchema({
    "height_in_feet": pa.Column(
        float, [
            # groupby as a single column
            pa.Check(

```

(continues on next page)

```

        lambda g: g[False].mean() > 6,
        groupby="age_less_than_20"),

    # define multiple groupby columns
    pa.Check(
        lambda g: g[True, "F"].sum() == 9.1,
        groupby=["age_less_than_20", "sex"]),

    # groupby as a callable with signature:
    # (DataFrame) -> DataFrameGroupBy
    pa.Check(
        lambda g: g[False, "M"].median() == 6.75,
        groupby=lambda df: (
            df.assign(age_less_than_15=lambda d: d["age"] < 15)
                .groupby(["age_less_than_15", "sex"])),
    ),
    "age": pa.Column(int, pa.Check(lambda s: s > 0)),
    "age_less_than_20": pa.Column(bool),
    "sex": pa.Column(str, pa.Check(lambda s: s.isin(["M", "F"])))
})

df = (
    pd.DataFrame({
        "height_in_feet": [6.5, 7, 6.1, 5.1, 4],
        "age": [25, 30, 21, 18, 13],
        "sex": ["M", "M", "F", "F", "F"]
    })
    .assign(age_less_than_20=lambda x: x["age"] < 20)
)

schema.validate(df)

```

### 6.3.6 Wide Checks

pandera is primarily designed to operate on long-form data (commonly known as [tidy data](#)), where each row is an observation and each column is an attribute associated with an observation.

However, pandera also supports checks on wide-form data to operate across columns in a DataFrame. For example, if you want to make assertions about `height` across two groups, the tidy dataset and schema might look like this:

```

import pandas as pd
import pandera as pa

df = pd.DataFrame({
    "height": [5.6, 6.4, 4.0, 7.1],
    "group": ["A", "B", "A", "B"],
})

schema = pa.DataFrameSchema({
    "height": pa.Column(

```

(continues on next page)



(continued from previous page)

```

        float,
        pa.Check(lambda g: g["A"].mean() < g["B"].mean(), groupby="group")
    ),
    "group": pa.Column(str)
})

schema.validate(df)

```

Whereas the equivalent wide-form schema would look like this:

```

df = pd.DataFrame({
    "height_A": [5.6, 4.0],
    "height_B": [6.4, 7.1],
})

schema = pa.DataFrameSchema(
    columns={
        "height_A": pa.Column(float),
        "height_B": pa.Column(float),
    },
    # define checks at the DataFrameSchema-level
    checks=pa.Check(
        lambda df: df["height_A"].mean() < df["height_B"].mean()
    )
)

schema.validate(df)

```

You can see that when checks are supplied to the `DataFrameSchema` `checks` key-word argument, the check function should expect a pandas `DataFrame` and should return a `bool`, a `Series` of booleans, or a `DataFrame` of boolean values.

### 6.3.7 Raise `UserWarning` on Check Failure

In some cases, you might want to raise a `UserWarning` and continue execution of your program. The `Check` and `Hypothesis` classes and their built-in methods support the keyword argument `raise_warning`, which is `False` by default. If set to `True`, the check will raise a `UserWarning` instead of raising a `SchemaError` exception.

---

**Note:** Use this feature carefully! If the check is for informational purposes and not critical for data integrity then use `raise_warning=True`. However, if the assumptions expressed in a `Check` are necessary conditions to considering your data valid, do not set this option to `true`.

---

One scenario where you'd want to do this would be in a data pipeline that does some preprocessing, checks for normality in certain columns, and writes the resulting dataset to a table. In this case, you want to see if your normality assumptions are not fulfilled by certain columns, but you still want the resulting table for further analysis.

```

import warnings

import numpy as np
import pandas as pd

```

(continues on next page)

```
import pandera as pa

from scipy.stats import normaltest

np.random.seed(1000)

df = pd.DataFrame({
    "var1": np.random.normal(loc=0, scale=1, size=1000),
    "var2": np.random.uniform(low=0, high=10, size=1000),
})

normal_check = pa.Hypothesis(
    test=normaltest,
    samples="normal_variable",
    # null hypotheses: sample comes from a normal distribution. The
    # relationship function checks if we cannot reject the null hypothesis,
    # i.e. the p-value is greater or equal to alpha.
    relationship=lambda stat, pvalue, alpha=0.05: pvalue >= alpha,
    error="normality test",
    raise_warning=True,
)

schema = pa.DataFrameSchema(
    columns={
        "var1": pa.Column(checks=normal_check),
        "var2": pa.Column(checks=normal_check),
    }
)

# catch and print warnings
with warnings.catch_warnings(record=True) as caught_warnings:
    warnings.simplefilter("always")
    validated_df = schema(df)
    for warning in caught_warnings:
        print(warning.message)
```

```
<Schema Column(name=var2, type=None)> failed series or dataframe validator 0:
<Check _hypothesis_check: normality test>
```

### 6.3.8 Registering Custom Checks

pandera now offers an interface to register custom checks functions so that they're available in the `Check` namespace. See *the extensions* document for more information.

## 6.4 Hypothesis Testing

pandera enables you to perform statistical hypothesis tests on your data.

**Note:** The hypothesis feature requires a pandera installation with `hypotheses` dependency set. See the *installation* instructions for more details.

### 6.4.1 Overview

The `Hypothesis` class defines built in methods, which can be called as in this example of a two-sample t-test:

```
import pandas as pd
import pandera as pa

from pandera import Column, DataFrameSchema, Check, Hypothesis

from scipy import stats

df = (
    pd.DataFrame({
        "height_in_feet": [6.5, 7, 6.1, 5.1, 4],
        "sex": ["M", "M", "F", "F", "F"]
    })
)

schema = DataFrameSchema({
    "height_in_feet": Column(
        float, [
            Hypothesis.two_sample_ttest(
                sample1="M",
                sample2="F",
                groupby="sex",
                relationship="greater_than",
                alpha=0.05,
                equal_var=True),
        ]),
    "sex": Column(str)
})

schema.validate(df)
```

```
Traceback (most recent call last):
```

```
...
```

```
pandera.SchemaError: <Schema Column: 'height_in_feet' type=float64> failed series_
```

```
validator 0: hypothesis_check: failed two sample ttest between 'M' and 'F'
```

(continues on next page)

You can also define custom hypotheses by passing in functions to the `test` and `relationship` arguments.

The `test` function takes as input one or multiple array-like objects and should return a `stat`, which is the test statistic, and `pvalue` for assessing statistical significance. It also takes key-word arguments supplied by the `test_kwargs` dict when initializing a `Hypothesis` object.

The `relationship` function should take all of the outputs of `test` as positional arguments, in addition to key-word arguments supplied by the `relationship_kwargs` dict.

Here's an implementation of the two-sample t-test that uses the `scipy` implementation:

```
def two_sample_ttest(array1, array2):
    # the "height_in_feet" series is first grouped by "sex" and then
    # passed into the custom `test` function as two separate arrays in the
    # order specified in the `samples` argument.
    return stats.ttest_ind(array1, array2)

def null_relationship(stat, pvalue, alpha=0.01):
    return pvalue / 2 >= alpha

schema = DataFrameSchema({
    "height_in_feet": Column(
        float, [
            Hypothesis(
                test=two_sample_ttest,
                samples=["M", "F"],
                groupby="sex",
                relationship=null_relationship,
                relationship_kwargs={"alpha": 0.05}
            )
        ],
    ),
    "sex": Column(str, checks=Check.isin(["M", "F"]))
})

schema.validate(df)
```

## 6.4.2 Wide Hypotheses

pandera is primarily designed to operate on long-form data (commonly known as `tidy data`), where each row is an observation and columns are attributes associated with the observation.

However, pandera also supports hypothesis testing on wide-form data to operate across columns in a `DataFrame`.

For example, if you want to make assertions about `height` across two groups, the tidy dataset and schema might look like this:

```
import pandas as pd
import pandera as pa

from pandera import Check, DataFrameSchema, Column, Hypothesis
```

(continues on next page)

(continued from previous page)

```
df = pd.DataFrame({
    "height": [5.6, 7.5, 4.0, 7.9],
    "group": ["A", "B", "A", "B"],
})

schema = DataFrameSchema({
    "height": Column(
        float, Hypothesis.two_sample_ttest(
            "A", "B",
            groupby="group",
            relationship="less_than",
            alpha=0.05
        )
    ),
    "group": Column(str, Check(lambda s: s.isin(["A", "B"])))
})

schema.validate(df)
```

The equivalent wide-form schema would look like this:

```
import pandas as pd
import pandera as pa

from pandera import DataFrameSchema, Column, Hypothesis

df = pd.DataFrame({
    "height_A": [5.6, 4.0],
    "height_B": [7.5, 7.9],
})

schema = DataFrameSchema(
    columns={
        "height_A": Column(Float),
        "height_B": Column(Float),
    },
    # define checks at the DataFrameSchema-level
    checks=Hypothesis.two_sample_ttest(
        "height_A", "height_B",
        relationship="less_than",
        alpha=0.05
    )
)

schema.validate(df)
```

## 6.5 Pandera Data Types (new)

*new in 0.7.0*

### 6.5.1 Motivations

Pandera defines its own interface for data types in order to abstract the specifics of dataframe-like data structures in the python ecosystem, such as Apache Spark, Apache Arrow and xarray.

---

**Note:** In the following section Pandera `Data Type` refers to a `pandera.dtypes.DataType` object whereas `native data type` refers to data types used by third-party libraries that Pandera supports (e.g. pandas).

---

Most of the time, it is transparent to end users since pandera columns and indexes accept native data types. However, it is possible to extend the pandera interface by:

- modifying the **data type check** performed during schema validation.
- modifying the behavior of the **coerce** argument for `DataFrameSchema`.
- adding your **own custom data types**.

### 6.5.2 DataType basics

All pandera data types inherit from `pandera.dtypes.DataType` and must be hashable.

A data type implements three key methods:

- `pandera.dtypes.DataType.check()` which validates that data types are equivalent.
- `pandera.dtypes.DataType.coerce()` which coerces a data container (e.g. `pandas.Series`) to the data type.
- The dunder method `__str__()` which should output the native alias. For example `str(pandera.Float64) == "float64"`

For pandera's validation methods to be aware of a data type, it has to be registered with the targeted engine via `pandera.engines.Engine.register_dtype()`. An engine is in charge of mapping a pandera `DataType` with a native data type counterpart belonging to a third-party library. The mapping can be queried with `pandera.engines.Engine.dtype()`.

As of pandera 0.7.0, only the pandas `Engine` is supported.

### 6.5.3 Example

Let's extend `pandas.BooleanDtype` coercion to handle the string literals "True" and "False".

```
import pandas as pd
import pandera as pa
from pandera import dtypes
from pandera.engines import pandas_engine

@pandas_engine.Engine.register_dtype # step 1
@dtypes.immutable # step 2
```

(continues on next page)

(continued from previous page)

```

class LiteralBool(pandas_engine.BOOL): # step 3
    def coerce(self, series: pd.Series) -> pd.Series:
        """Coerce a pandas.Series to date types."""
        if pd.api.types.is_string_dtype(series):
            series = series.replace({"True": 1, "False": 0})
        return series.astype("boolean")

data = pd.Series(["True", "False"], name="literal_bools")

# step 4
print(
    pa.SeriesSchema(LiteralBool(), coerce=True, name="literal_bools")
    .validate(data)
    .dtype
)

```

```
boolean
```

The example above performs the following steps:

1. Register the data type with the pandas engine.
2. `pandera.dtypes.immutable()` creates an immutable (and hashable) `dataclass()`.
3. Inherit `pandera.engines.pandas_engine.BOOL`, which is the pandera representation of `pandas.BooleanDtype`. This is not mandatory but it makes our life easier by having already implemented all the required methods.
4. Check that our new data type can coerce the string literals.

So far we did not override the default behavior:

```

import pandera as pa

pa.SeriesSchema("boolean", coerce=True).validate(data)

```

Traceback (most recent call last):

```

...
pandera.errors.SchemaError: Error while coercing 'literal_bools' to type boolean: Need
↪to pass bool-like values

```

To completely replace the default `BOOL`, we need to supply all the equivalent representations to `register_dtype()`. Behind the scenes, when `pa.SeriesSchema("boolean")` is called the corresponding pandera data type is looked up using `pandera.engines.engine.Engine.dtype()`.

```

print(f"before: {pandas_engine.Engine.dtype('boolean').__class__}")

@pandas_engine.Engine.register_dtype(
    equivalents=["boolean", pd.BooleanDtype, pd.BooleanDtype()],
)
@dtypes.immutable
class LiteralBool(pandas_engine.BOOL):

```

(continues on next page)

(continued from previous page)

```

def coerce(self, series: pd.Series) -> pd.Series:
    """Coerce a pandas.Series to date types."""
    if pd.api.types.is_string_dtype(series):
        series = series.replace({"True": 1, "False": 0})
    return series.astype("boolean")

print(f"after: {pandas_engine.Engine.dtype('boolean').__class__}")

for dtype in ["boolean", pd.BooleanDtype, pd.BooleanDtype()]:
    pa.SeriesSchema(dtype, coerce=True).validate(data)

```

```

before: <class 'pandera.engines.pandas_engine.BOOL'>
after: <class 'LiteralBool'>

```

**Note:** For convenience, we specified both `pd.BooleanDtype` and `pd.BooleanDtype()` as equivalents. That gives us more flexibility in what pandera schemas can recognize (see last for-loop above).

## 6.5.4 Parametrized data types

Some data types can be parametrized. One common example is `pandas.CategoricalDtype`.

The `equivalents` argument of `register_dtype()` does not handle this situation but will automatically register a `classmethod()` with signature `from_parametrized_dtype(cls, equivalent:...)` if the decorated `DataType` defines it. The `equivalent` argument must be type-annotated because it is leveraged to dispatch the input of `dtype` to the appropriate `from_parametrized_dtype` class method.

For example, here is a snippet from `pandera.engines.pandas_engine.Category`:

```

import pandas as pd
from pandera import dtypes

@classmethod
def from_parametrized_dtype(
    cls, cat: Union[dtypes.Category, pd.CategoricalDtype]
):
    """Convert a categorical to
    a Pandera :class:`pandera.dtypes.pandas_engine.Category`."""
    return cls(categories=cat.categories, ordered=cat.ordered) # type: ignore

```

**Note:** The dispatch mechanism relies on `functools.singledispatch()`. Unlike the built-in implementation, `typing.Union` is recognized.



## 6.6 Decorators for Pipeline Integration

If you have an existing data pipeline that uses pandas data structures, you can use the `check_input()` and `check_output()` decorators to easily check function arguments or returned variables from existing functions.

### 6.6.1 Check Input

Validates input pandas DataFrame/Series before entering the wrapped function.

```
import pandas as pd
import pandera as pa

from pandera import DataFrameSchema, Column, Check, check_input

df = pd.DataFrame({
    "column1": [1, 4, 0, 10, 9],
    "column2": [-1.3, -1.4, -2.9, -10.1, -20.4],
})

in_schema = DataFrameSchema({
    "column1": Column(int,
                      Check(lambda x: 0 <= x <= 10, element_wise=True)),
    "column2": Column(float, Check(lambda x: x < -1.2)),
})

# by default, check_input assumes that the first argument is
# dataframe/series.
@check_input(in_schema)
def preprocessor(dataframe):
    dataframe["column3"] = dataframe["column1"] + dataframe["column2"]
    return dataframe

preprocessed_df = preprocessor(df)
print(preprocessed_df)
```

	column1	column2	column3
0	1	-1.3	-0.3
1	4	-1.4	2.6
2	0	-2.9	-2.9
3	10	-10.1	-0.1
4	9	-20.4	-11.4

You can also provide the argument name as a string

```
@check_input(in_schema, "dataframe")
def preprocessor(dataframe):
    ...
```

Or an integer representing the index in the positional arguments.

```
@check_input(in_schema, 1)
def preprocessor(foo, dataframe):
    ...
```

## 6.6.2 Check Output

The same as `check_input`, but this decorator checks the output DataFrame/Series of the decorated function.

```
import pandas as pd
import pandera as pa

from pandera import DataFrameSchema, Column, Check, check_output

preprocessed_df = pd.DataFrame({
    "column1": [1, 4, 0, 10, 9],
})

# assert that all elements in "column1" are zero
out_schema = DataFrameSchema({
    "column1": Column(int, Check(lambda x: x == 0))
})

# by default assumes that the pandas DataFrame/Schema is the only output
@check_output(out_schema)
def zero_column_1(df):
    df["column1"] = 0
    return df

# you can also specify in the index of the argument if the output is list-like
@check_output(out_schema, 1)
def zero_column_1_arg(df):
    df["column1"] = 0
    return "foobar", df

# or the key containing the data structure to verify if the output is dict-like
@check_output(out_schema, "out_df")
def zero_column_1_dict(df):
    df["column1"] = 0
    return {"out_df": df, "out_str": "foobar"}

# for more complex outputs, you can specify a function
@check_output(out_schema, lambda x: x[1]["out_df"])
def zero_column_1_custom(df):
    df["column1"] = 0
    return ("foobar", {"out_df": df})
```

(continues on next page)

(continued from previous page)

```

zero_column_1(preprocessed_df)
zero_column_1_arg(preprocessed_df)
zero_column_1_dict(preprocessed_df)
zero_column_1_custom(preprocessed_df)

```

### 6.6.3 Check IO

For convenience, you can also use the `check_io()` decorator where you can specify input and output schemas more concisely:

```

import pandas as pd
import pandera as pa

from pandera import DataFrameSchema, Column, Check, check_input

df = pd.DataFrame({
    "column1": [1, 4, 0, 10, 9],
    "column2": [-1.3, -1.4, -2.9, -10.1, -20.4],
})

in_schema = DataFrameSchema({
    "column1": Column(int),
    "column2": Column(float),
})

out_schema = in_schema.add_columns({"column3": Column(float)})

@pa.check_io(df1=in_schema, df2=in_schema, out=out_schema)
def preprocessor(df1, df2):
    return (df1 + df2).assign(column3=lambda x: x.column1 + x.column2)

preprocessed_df = preprocessor(df, df)
print(preprocessed_df)

```

	column1	column2	column3
0	2	-2.6	-0.6
1	8	-2.8	5.2
2	0	-5.8	-5.8
3	20	-20.2	-0.2
4	18	-40.8	-22.8

## 6.6.4 Decorate Functions and Coroutines

All pandera decorators work on synchronous as well as asynchronous code, on both bound and unbound functions/coroutines. For example, one can use the same decorators on:

- sync/async functions
- sync/async methods
- sync/async class methods
- sync/async static methods

All decorators work on sync/async regular/class/static methods of metaclasses as well.

```
import pandera as pa
from pandera.typing import DataFrame, Series

class Schema(pa.SchemaModel):
    col1: Series[int]

    class Config:
        strict = True

@pa.check_types
async def coroutine(df: DataFrame[Schema]) -> DataFrame[Schema]:
    return df

@pa.check_types
async def function(df: DataFrame[Schema]) -> DataFrame[Schema]:
    return df

class SomeClass:
    @pa.check_output(Schema.to_schema())
    async def regular_coroutine(self, df) -> DataFrame[Schema]:
        return df

    @classmethod
    @pa.check_input(Schema.to_schema(), "df")
    async def class_coroutine(cls, df):
        return Schema.validate(df)

    @staticmethod
    @pa.check_io(df=Schema.to_schema(), out=Schema.to_schema())
    def static_method(df):
        return df
```

## 6.7 Schema Inference

*New in version 0.4.0*

With simple use cases, writing a schema definition manually is pretty straight-forward with pandera. However, it can get tedious to do this with dataframes that have many columns of various data types.

To help you handle these cases, the `infer_schema()` function enables you to quickly infer a draft schema from a pandas dataframe or series. Below is a simple example:

```
import pandas as pd
import pandera as pa

from pandera import Check, Column, DataFrameSchema

df = pd.DataFrame({
    "column1": [5, 10, 20],
    "column2": ["a", "b", "c"],
    "column3": pd.to_datetime(["2010", "2011", "2012"]),
})
schema = pa.infer_schema(df)
print(schema)
```

```
<Schema DataFrameSchema(
  columns={
    'column1': <Schema Column(name=column1, type=DataType(int64))>
    'column2': <Schema Column(name=column2, type=DataType(object))>
    'column3': <Schema Column(name=column3, type=DataType(datetime64[ns]))>
  },
  checks=[],
  coerce=True,
  dtype=None,
  index=<Schema Index(name=None, type=DataType(int64))>,
  strict=False
  name=None,
  ordered=False
)>
```

These inferred schemas are **rough drafts** that shouldn't be used for validation without modification. You can modify the inferred schema to obtain the schema definition that you're satisfied with.

For `DataFrameSchema` objects, the following methods create modified copies of the schema:

- `add_columns()`
- `remove_columns()`
- `update_column()`

For `SeriesSchema` objects:

- `set_checks()`

The section below describes two workflows for persisting and modifying an inferred schema.

## 6.7.1 Schema Persistence

The schema persistence feature requires a pandera installation with the `io` extension. See the *installation* instructions for more details.

There are two ways of persisting schemas, inferred or otherwise.

### 6.7.1.1 Write to a Python script

You can also write your schema to a python script with `to_script()`:

```
# supply a file-like object, Path, or str to write to a file. If not  
# specified, to_script will output the code as a string.  
schema_script = schema.to_script()  
print(schema_script)
```

```
from pandas import Timestamp  
from pandera import DataFrameSchema, Column, Check, Index, MultiIndex  
  
schema = DataFrameSchema(  
    columns={  
        "column1": Column(  
            dtype=pandera.engines.numpy_engine.Int64,  
            checks=[  
                Check.greater_than_or_equal_to(min_value=5.0),  
                Check.less_than_or_equal_to(max_value=20.0),  
            ],  
            nullable=False,  
            allow_duplicates=True,  
            coerce=False,  
            required=True,  
            regex=False,  
        ),  
        "column2": Column(  
            dtype=pandera.engines.numpy_engine.Object,  
            checks=None,  
            nullable=False,  
            allow_duplicates=True,  
            coerce=False,  
            required=True,  
            regex=False,  
        ),  
        "column3": Column(  
            dtype=pandera.engines.pandas_engine.DateTime,  
            checks=[  
                Check.greater_than_or_equal_to(  
                    min_value=Timestamp("2010-01-01 00:00:00")  
                ),  
                Check.less_than_or_equal_to(  
                    max_value=Timestamp("2012-01-01 00:00:00")  
                ),  
            ],  
            nullable=False,
```

(continues on next page)

(continued from previous page)

```

        allow_duplicates=True,
        coerce=False,
        required=True,
        regex=False,
    ),
},
index=Index(
    dtype=pandera.engines.numpy_engine.Int64,
    checks=[
        Check.greater_than_or_equal_to(min_value=0.0),
        Check.less_than_or_equal_to(max_value=2.0),
    ],
    nullable=False,
    coerce=False,
    name=None,
),
coerce=True,
strict=False,
name=None,
)

```

As a python script, you can iterate on an inferred schema and use it to validate data once you are satisfied with your schema definition.

### 6.7.1.2 Write to YAML

You can also write the schema object to a yaml file with `to_yaml()`, and you can then read it into memory with `from_yaml()`. The `to_yaml()` and `from_yaml()` is a convenience method for this functionality.

```

# supply a file-like object, Path, or str to write to a file. If not
# specified, to_yaml will output a yaml string.
yaml_schema = schema.to_yaml()
print(yaml_schema.replace(f"{{pa.__version__}}", "{{PANDERA_VERSION}}"))

```

```

schema_type: dataframe
version: {PANDERA_VERSION}
columns:
  column1:
    dtype: int64
    nullable: false
    checks:
      greater_than_or_equal_to: 5.0
      less_than_or_equal_to: 20.0
    allow_duplicates: true
    coerce: false
    required: true
    regex: false
  column2:
    dtype: object
    nullable: false
    checks: null

```

(continues on next page)

```
allow_duplicates: true
coerce: false
required: true
regex: false
column3:
  dtype: datetime64[ns]
  nullable: false
  checks:
    greater_than_or_equal_to: '2010-01-01 00:00:00'
    less_than_or_equal_to: '2012-01-01 00:00:00'
  allow_duplicates: true
  coerce: false
  required: true
  regex: false
checks: null
index:
- dtype: int64
  nullable: false
  checks:
    greater_than_or_equal_to: 0.0
    less_than_or_equal_to: 2.0
  name: null
  coerce: false
coerce: true
strict: false
```

You can edit this yaml file by specifying column names under the `column` key. The respective values map onto key-word arguments in the `Column` class.

---

**Note:** Currently, only built-in `Check` methods are supported under the `checks` key.

---

## 6.8 Schema Models

*new in 0.5.0*

pandera provides a class-based API that's heavily inspired by `pydantic`. In contrast to the *object-based API*, you can define schema models in much the same way you'd define `pydantic` models.

*Schema Models* are annotated with the `pandera.typing` module using the standard `typing` syntax. Models can be explicitly converted to a `DataFrameSchema` or used to validate a `DataFrame` directly.

---

**Note:** Due to current limitations in the pandas library (see discussion [here](#)), `pandera` annotations are only used for **run-time** validation and **cannot** be leveraged by static-type checkers like `mypy`. See the discussion [here](#) for more details.

---



## 6.8.1 Basic Usage

```
import pandas as pd
import pandera as pa
from pandera.typing import Index, DataFrame, Series

class InputSchema(pa.SchemaModel):
    year: Series[int] = pa.Field(gt=2000, coerce=True)
    month: Series[int] = pa.Field(ge=1, le=12, coerce=True)
    day: Series[int] = pa.Field(ge=0, le=365, coerce=True)

class OutputSchema(InputSchema):
    revenue: Series[float]

@pa.check_types
def transform(df: DataFrame[InputSchema]) -> DataFrame[OutputSchema]:
    return df.assign(revenue=100.0)

df = pd.DataFrame({
    "year": ["2001", "2002", "2003"],
    "month": ["3", "6", "12"],
    "day": ["200", "156", "365"],
})

transform(df)

invalid_df = pd.DataFrame({
    "year": ["2001", "2002", "1999"],
    "month": ["3", "6", "12"],
    "day": ["200", "156", "365"],
})

transform(invalid_df)
```

```
Traceback (most recent call last):
...
pandera.errors.SchemaError: <Schema Column: 'year' type=DataType(int64)> failed element-
↪wise validator 0:
<Check greater_than: greater_than(2000)>
failure cases:
   index  failure_case
0      2           1999
```

As you can see in the example above, you can define a schema by sub-classing `SchemaModel` and defining column/index fields as class attributes. The `check_types()` decorator is required to perform validation of the dataframe at run-time.

Note that `Field`s apply to both `Column` and `Index` objects, exposing the built-in Checks via key-word arguments.

(New in 0.6.2) When you access a class attribute defined on the schema, it will return the name of the column used in the validated `pd.DataFrame`. In the example above, this will simply be the string “year”.

```
print(f"Column name for 'year' is {InputSchema.year}\n")
print(df.loc[:, [InputSchema.year, "day"]])
```

```
Column name for 'year' is year
```

```
   year  day
0  2001  200
1  2002  156
2  2003  365
```

## 6.8.2 Converting to DataFrameSchema

You can easily convert a *SchemaModel* class into a *DataFrameSchema*:

```
print(InputSchema.to_schema())
```

```
<Schema DataFrameSchema(
  columns={
    'year': <Schema Column(name=year, type=DataType(int64))>
    'month': <Schema Column(name=month, type=DataType(int64))>
    'day': <Schema Column(name=day, type=DataType(int64))>
  },
  checks=[],
  coerce=False,
  dtype=None,
  index=None,
  strict=False
  name=None,
  ordered=False
)>
```

Or use the *validate()* method to validate dataframes:

```
print(InputSchema.validate(df))
```

```
   year  month  day
0  2001     3  200
1  2002     6  156
2  2003    12  365
```

### 6.8.3 Excluded attributes

Class variables which begin with an underscore will be automatically excluded from the model. *Config* is also a reserved name. However, *aliases* can be used to circumvent these limitations.

### 6.8.4 Supported dtypes

Any dtypes supported by pandera can be used as type parameters for `Series` and `Index`. There are, however, a couple of gotchas.

#### 6.8.4.1 Dtype aliases

`pandera.typing` aliases will be deprecated in a future version, please use `DataType` subclasses instead.

```
import pandera as pa
from pandera.typing import Series, String

class Schema(pa.SchemaModel):
    a: Series[String]
```

#### 6.8.4.2 Type Vs instance

You must give a **type**, not an **instance**.

✓ Good:

```
import pandas as pd

class Schema(pa.SchemaModel):
    a: Series[pd.StringDtype]
```

Bad:

```
class Schema(pa.SchemaModel):
    a: Series[pd.StringDtype()]
```

Traceback (most recent call last):

```
...
TypeError: Parameters to generic types must be types. Got StringDtype.
```

#### 6.8.4.3 Parametrized dtypes

Pandas supports a couple of parametrized dtypes. As of pandas 1.2.0:

Kind of Data	Data Type	Parameters
tz-aware datetime	DatetimeTZDtype	unit, tz
Categorical	CategoricalDtype	categories, ordered
period	PeriodDtype	freq
sparse	SparseDtype	dtype, fill_value
intervals	IntervalDtype	subtype

### 6.8.4.3.1 Annotated

Parameters can be given via `typing.Annotated`. It requires python > 3.9 or `typing_extensions`, which is already a requirement of Pandera. Unfortunately `typing.Annotated` has not been backported to python 3.6.

✓ Good:

```
try:
    from typing import Annotated # python 3.9+
except ImportError:
    from typing_extensions import Annotated

class Schema(pa.SchemaModel):
    col: Series[Annotated[pd.DatetimeTZDtype, "ns", "est"]]
```

Furthermore, you must pass all parameters in the order defined in the dtype's constructor (see [table](#)).

Bad:

```
class Schema(pa.SchemaModel):
    col: Series[Annotated[pd.DatetimeTZDtype, "utc"]]

Schema.to_schema()
```

```
Traceback (most recent call last):
...
TypeError: Annotation 'DatetimeTZDtype' requires all positional arguments ['unit', 'tz'].
```

### 6.8.4.3.2 Field

✓ Good:

```
class SchemaFieldDatetimeTZDtype(pa.SchemaModel):
    col: Series[pd.DatetimeTZDtype] = pa.Field(dtype_kwargs={"unit": "ns", "tz": "EST"})
```

You cannot use both `typing.Annotated` and `dtype_kwargs`.

Bad:

```
class SchemaFieldDatetimeTZDtype(pa.SchemaModel):
    col: Series[Annotated[pd.DatetimeTZDtype, "ns", "est"]] = pa.Field(dtype_kwargs={
    ↪ "unit": "ns", "tz": "EST"})

Schema.to_schema()
```

```
Traceback (most recent call last):
...
TypeError: Cannot specify redundant 'dtype_kwargs' for pandera.typing.Series[typing_
↪ extensions.Annotated[pandas.core.dtypes.dtypes.DatetimeTZDtype, 'ns', 'est']].
Usage Tip: Drop 'typing.Annotated'.
```

## 6.8.5 Required Columns

By default all columns specified in the schema are *required*, meaning that if a column is missing in the input DataFrame an exception will be thrown. If you want to make a column optional, annotate it with `typing.Optional`.

```
from typing import Optional

import pandas as pd
import pandera as pa
from pandera.typing import Series

class Schema(pa.SchemaModel):
    a: Series[str]
    b: Optional[Series[int]]

df = pd.DataFrame({"a": ["2001", "2002", "2003"]})
Schema.validate(df)
```

## 6.8.6 Schema Inheritance

You can also use inheritance to build schemas on top of a base schema.

```
class BaseSchema(pa.SchemaModel):
    year: Series[str]

class FinalSchema(BaseSchema):
    year: Series[int] = pa.Field(ge=2000, coerce=True) # overwrite the base type
    passengers: Series[int]
    idx: Index[int] = pa.Field(ge=0)

df = pd.DataFrame({
    "year": ["2000", "2001", "2002"],
})

@pa.check_types
def transform(df: DataFrame[BaseSchema]) -> DataFrame[FinalSchema]:
    return (
        df.assign(passengers=[61000, 50000, 45000])
        .set_index(pd.Index([1, 2, 3]))
        .astype({"year": int})
    )

print(transform(df))
```

	year	passengers
1	2000	61000
2	2001	50000
3	2002	45000

## 6.8.7 Config

Schema-wide options can be controlled via the `Config` class on the `SchemaModel` subclass. The full set of options can be found in the `BaseConfig` class.

```
class Schema(pa.SchemaModel):

    year: Series[int] = pa.Field(gt=2000, coerce=True)
    month: Series[int] = pa.Field(ge=1, le=12, coerce=True)
    day: Series[int] = pa.Field(ge=0, le=365, coerce=True)

    class Config:
        name = "BaseSchema"
        strict = True
        coerce = True
        foo = "bar" # Interpreted as dataframe check
```

It is not required for the `Config` to subclass `BaseConfig` but it **must** be named `'Config'`.

See *Registered Custom Checks with the Class-based API* for details on using registered dataframe checks.

## 6.8.8 MultiIndex

The *MultiIndex* capabilities are also supported with the class-based API:

```
import pandera as pa
from pandera.typing import Index, Series

class MultiIndexSchema(pa.SchemaModel):

    year: Index[int] = pa.Field(gt=2000, coerce=True)
    month: Index[int] = pa.Field(ge=1, le=12, coerce=True)
    passengers: Series[int]

    class Config:
        # provide multi index options in the config
        multiindex_name = "time"
        multiindex_strict = True
        multiindex_coerce = True

index = MultiIndexSchema.to_schema().index
print(index)
```

```
<Schema MultiIndex(
  indexes=[
    <Schema Index(name=year, type=DataType(int64))>
    <Schema Index(name=month, type=DataType(int64))>
  ]
  coerce=True,
  strict=True,
  name=time,
  ordered=True
)>
```

```
from pprint import pprint

pprint({name: col.checks for name, col in index.columns.items()})
```

```
{'month': [<Check greater_than_or_equal_to: greater_than_or_equal_to(1)>,
           <Check less_than_or_equal_to: less_than_or_equal_to(12)>],
 'year': [<Check greater_than: greater_than(2000)>]}
```

Multiple Index annotations are automatically converted into a *MultiIndex*. MultiIndex options are given in the *Config*.

## 6.8.9 Custom Checks

Unlike the object-based API, custom checks can be specified as class methods.

### 6.8.9.1 Column/Index checks

```
import pandera as pa
from pandera.typing import Index, Series

class CustomCheckSchema(pa.SchemaModel):

    a: Series[int] = pa.Field(gt=0, coerce=True)
    abc: Series[int]
    idx: Index[str]

    @pa.check("a", name="foobar")
    def custom_check(cls, a: Series[int]) -> Series[bool]:
        return a < 100

    @pa.check("^a", regex=True, name="foobar")
    def custom_check_regex(cls, a: Series[int]) -> Series[bool]:
        return a > 0

    @pa.check("idx")
    def check_idx(cls, idx: Index[int]) -> Series[bool]:
        return idx.str.contains("dog")
```

#### Note:

- You can supply the key-word arguments of the *Check* class initializer to get the flexibility of *groupby checks*
- Similarly to pydantic, `classmethod()` decorator is added behind the scenes if omitted.
- You still may need to add the `@classmethod` decorator *after* the `check()` decorator if your static-type checker or linter complains.
- Since checks are class methods, the first argument value they receive is a *SchemaModel* subclass, not an instance of a model.

```

from typing import Dict

class GroupbyCheckSchema(pa.SchemaModel):

    value: Series[int] = pa.Field(gt=0, coerce=True)
    group: Series[str] = pa.Field(isin=["A", "B"])

    @pa.check("value", groupby="group", regex=True, name="check_means")
    def check_groupby(cls, grouped_value: Dict[str, Series[int]]) -> bool:
        return grouped_value["A"].mean() < grouped_value["B"].mean()

df = pd.DataFrame({
    "value": [100, 110, 120, 10, 11, 12],
    "group": list("AAABBB"),
})

print(GroupbyCheckSchema.validate(df))

```

```

Traceback (most recent call last):
...
pandera.errors.SchemaError: <Schema Column: 'value' type=DataType(int64)> failed series_
->validator 1:
<Check check_means>

```

### 6.8.9.2 DataFrame Checks

You can also define dataframe-level checks, similar to the *object-based API*, using the `dataframe_check()` decorator:

```

import pandas as pd
import pandera as pa
from pandera.typing import Index, Series

class DataFrameCheckSchema(pa.SchemaModel):

    col1: Series[int] = pa.Field(gt=0, coerce=True)
    col2: Series[float] = pa.Field(gt=0, coerce=True)
    col3: Series[float] = pa.Field(lt=0, coerce=True)

    @pa.dataframe_check
    def product_is_negative(cls, df: pd.DataFrame) -> Series[bool]:
        return df["col1"] * df["col2"] * df["col3"] < 0

df = pd.DataFrame({
    "col1": [1, 2, 3],
    "col2": [5, 6, 7],
    "col3": [-1, -2, -3],
})

DataFrameCheckSchema.validate(df)

```



### 6.8.9.3 Inheritance

The custom checks are inherited and therefore can be overwritten by the subclass.

```
import pandas as pd
import pandera as pa
from pandera.typing import Index, Series

class Parent(pa.SchemaModel):

    a: Series[int] = pa.Field(coerce=True)

    @pa.check("a", name="foobar")
    def check_a(cls, a: Series[int]) -> Series[bool]:
        return a < 100

class Child(Parent):

    a: Series[int] = pa.Field(coerce=False)

    @pa.check("a", name="foobar")
    def check_a(cls, a: Series[int]) -> Series[bool]:
        return a > 100

is_a_coerce = Child.to_schema().columns["a"].coerce
print(f"coerce: {is_a_coerce}")
```

```
coerce: False
```

```
df = pd.DataFrame({"a": [1, 2, 3]})
print(Child.validate(df))
```

```
Traceback (most recent call last):
...
pandera.errors.SchemaError: <Schema Column: 'a' type=DataType(int64)> failed element-
wise validator 0:
<Check foobar>
failure cases:
   index  failure_case
0      0             1
1      1             2
2      2             3
```

## 6.8.10 Aliases

*SchemaModel* supports columns which are not valid python variable names via the argument *alias* of *Field*.

Checks must reference the aliased names.

```
import pandera as pa
import pandas as pd

class Schema(pa.SchemaModel):
    col_2020: pa.typing.Series[int] = pa.Field(alias=2020)
    idx: pa.typing.Index[int] = pa.Field(alias="_idx", check_name=True)

    @pa.check(2020)
    def int_column_lt_100(cls, series):
        return series < 100

df = pd.DataFrame({2020: [99]}, index=[0])
df.index.name = "_idx"

print(Schema.validate(df))
```

```
      2020
_idx
0      99
```

(New in 0.6.2) The *alias* is respected when using the class attribute to get the underlying *pd.DataFrame* column name or index level name.

```
print(Schema.col_2020)
```

```
2020
```

Very similar to the example above, you can also use the variable name directly within the class scope, and it will respect the alias.

**Note:** To access a variable from the class scope, you need to make it a class attribute, and therefore assign it a default *Field*.

```
import pandera as pa
import pandas as pd

class Schema(pa.SchemaModel):
    a: pa.typing.Series[int] = pa.Field()
    col_2020: pa.typing.Series[int] = pa.Field(alias=2020)

    @pa.check(col_2020)
    def int_column_lt_100(cls, series):
        return series < 100

    @pa.check(a)
```

(continues on next page)

(continued from previous page)

```
def int_column_gt_100(cls, series):
    return series > 100

df = pd.DataFrame({2020: [99], "a": [101]})
print(Schema.validate(df))
```

```
   2020    a
0     99  101
```

## 6.9 Lazy Validation

*New in version 0.4.0*

By default, when you call the `validate` method on schema or schema component objects, a `SchemaError` is raised as soon as one of the assumptions specified in the schema is falsified. For example, for a `DataFrameSchema` object, the following situations will raise an exception:

- a column specified in the schema is not present in the dataframe.
- if `strict=True`, a column in the dataframe is not specified in the schema.
- the `data` type does not match.
- if `coerce=True`, the dataframe column cannot be coerced into the specified `data` type.
- the `Check` specified in one of the columns returns `False` or a boolean series containing at least one `False` value.

For example:

```
import pandas as pd
import pandera as pa

from pandera import Check, Column, DataFrameSchema

df = pd.DataFrame({"column": ["a", "b", "c"]})

schema = pa.DataFrameSchema({"column": Column(int)})
schema.validate(df)
```

```
Traceback (most recent call last):
...
SchemaError: expected series 'column' to have type int64, got object
```

For more complex cases, it is useful to see all of the errors raised during the `validate` call so that you can debug the causes of errors on different columns and checks. The `lazy` keyword argument in the `validate` method of all schemas and schema components gives you the option of doing just this:

```
import pandas as pd
import pandera as pa

from pandera import Check, Column, DataFrameSchema
```

(continues on next page)

```

schema = pa.DataFrameSchema(
    columns={
        "int_column": Column(int),
        "float_column": Column(float, Check.greater_than(0)),
        "str_column": Column(str, Check.equal_to("a")),
        "date_column": Column(pa.DateTime),
    },
    strict=True
)

df = pd.DataFrame({
    "int_column": ["a", "b", "c"],
    "float_column": [0, 1, 2],
    "str_column": ["a", "b", "d"],
    "unknown_column": None,
})

schema.validate(df, lazy=True)

```

Traceback (most recent call last):

```

...
pandera.errors.SchemaErrors: A total of 5 schema errors were found.

```

Error Counts

```

-----
- column_not_in_schema: 1
- column_not_in_dataframe: 1
- schema_component_check: 3

```

Schema Error Summary

```

-----

```

schema_context	column	check	failure_cases	n_failure_cases
DataFrameSchema	<NA>	column_in_dataframe	[date_column]	1
		column_in_schema	[unknown_column]	1
Column	float_column	dtype('float64')	[int64]	1
	int_column	dtype('int64')	[object]	1
	str_column	equal_to(a)	[b, d]	2

Usage Tip

```

-----
Directly inspect all errors by catching the exception:

```

```

...
try:
    schema.validate(dataframe, lazy=True)
except SchemaErrors as err:
    err.failure_cases # dataframe of schema errors
    err.data # invalid dataframe
...

```

As you can see from the output above, a `SchemaErrors` exception is raised with a summary of the error counts and failure cases caught by the schema. You can also see from the **Usage Tip** that you can catch these errors and inspect the failure cases in a more granular form:

```
try:
    schema.validate(df, lazy=True)
except pa.errors.SchemaErrors as err:
    print("Schema errors and failure cases:")
    print(err.failure_cases)
    print("\nDataFrame object that failed validation:")
    print(err.data)
```

```
Schema errors and failure cases:
  schema_context      column      check check_number \
0 DataFrameSchema      None  column_in_schema      None
1 DataFrameSchema      None  column_in_dataframe      None
2      Column  int_column      dtype('int64')      None
3      Column  float_column  dtype('float64')      None
4      Column  float_column  greater_than(0)          0
5      Column   str_column      equal_to(a)          0
6      Column   str_column      equal_to(a)          0

  failure_case index
0 unknown_column  None
1   date_column  None
2      object     None
3      int64     None
4          0      0
5          b      1
6          d      2

DataFrame object that failed validation:
  int_column  float_column  str_column  unknown_column
0          a            0          a            None
1          b            1          b            None
2          c            2          d            None
```

## 6.10 Data Synthesis Strategies

*new in 0.6.0*

pandera provides a utility for generating synthetic data purely from pandera schema or schema component objects. Under the hood, the schema metadata is collected to create a data-generating strategy using `hypothesis`, which is a property-based testing library.

## 6.10.1 Basic Usage

Once you've defined a schema, it's easy to generate examples:

```
import pandera as pa

schema = pa.DataFrameSchema(
    {
        "column1": pa.Column(int, pa.Check.eq(10)),
        "column2": pa.Column(float, pa.Check.eq(0.25)),
        "column3": pa.Column(str, pa.Check.eq("foo")),
    }
)
print(schema.example(size=3))
```

	column1	column2	column3
0	10	0.25	foo
1	10	0.25	foo
2	10	0.25	foo

Note that here we've constrained the specific values in each column using *Check* s in order to make the data generation process deterministic for documentation purposes.

## 6.10.2 Usage in Unit Tests

The `example` method is available for all schemas and schema components, and is primarily meant to be used interactively. It *could* be used in a script to generate test cases, but *hypothesis* recommends against doing this and instead using the `strategy` method to create a *hypothesis* strategy that can be used in *pytest* unit tests.

```
import hypothesis

def processing_fn(df):
    return df.assign(column4=df.column1 * df.column2)

@hypothesis.given(schema.strategy(size=5))
def test_processing_fn(dataframe):
    result = processing_fn(dataframe)
    assert "column4" in result
```

The above example is trivial, but you get the idea! Schema objects can create a `strategy` that can then be collected by a *pytest* runner. We could also run the tests explicitly ourselves, or run it as a `unittest.TestCase`. For more information on testing with *hypothesis*, see the [hypothesis quick start guide](#).

A more practical example involves using *schema transformations*. We can modify the function above to make sure that `processing_fn` actually outputs the correct result:

```
out_schema = schema.add_columns({"column4": pa.Column(float)})

@pa.check_output(out_schema)
def processing_fn(df):
    return df.assign(column4=df.column1 * df.column2)

@hypothesis.given(schema.strategy(size=5))
```

(continues on next page)

(continued from previous page)

```
def test_processing_fn(dataframe):
    processing_fn(dataframe)
```

Now the `test_processing_fn` simply becomes an execution test, raising a `SchemaError` if `processing_fn` doesn't add `column4` to the dataframe.

### 6.10.3 Strategies and Examples from Schema Models

You can also use the *class-based API* to generate examples. Here's the equivalent schema model for the above examples:

```
from pandera.typing import Series, DataFrame

class InSchema(pa.SchemaModel):
    column1: Series[int] = pa.Field(eq=10)
    column2: Series[float] = pa.Field(eq=0.25)
    column3: Series[str] = pa.Field(eq="foo")

class OutSchema(InSchema):
    column4: Series[float]

@pa.check_types
def processing_fn(df: DataFrame[InSchema]) -> DataFrame[OutSchema]:
    return df.assign(column4=df.column1 * df.column2)

@hypothesis.given(InSchema.strategy(size=5))
def test_processing_fn(dataframe):
    processing_fn(dataframe)
```

### 6.10.4 Checks as Constraints

As you may have noticed in the first example, *Check*s further constrain the data synthesized from a strategy. Without checks, the `example` method would simply generate any value of the specified type. You can specify multiple checks on a column and pandera should be able to generate valid data under those constraints.

```
schema_multiple_checks = pa.DataFrameSchema({
    "column1": pa.Column(
        float, checks=[
            pa.Check.gt(0),
            pa.Check.lt(1e10),
            pa.Check.notin([-100, -10, 0]),
        ]
    )
})

for _ in range(100):
    # generate 10 rows of the dataframe
    sample_data = schema_multiple_checks.example(size=10)

    # validate the sampled data
    schema_multiple_checks(sample_data)
```

One caveat here is that it's up to you to define a set of checks that are jointly satisfiable. If not, an `Unsatisfiable` exception will be raised:

```
schema_multiple_checks = pa.DataFrameSchema({
    "column1": pa.Column(
        float, checks=[
            # nonsensical constraints
            pa.Check.gt(0),
            pa.Check.lt(-10),
        ]
    )
})

schema_multiple_checks.example(size=10)
```

```
Traceback (most recent call last):
...
Unsatisfiable: Unable to satisfy assumptions of hypothesis example_generating_inner_
↪function.
```

### 6.10.4.1 Check Strategy Chaining

If you specify multiple checks for a particular column, this is what happens under the hood:

- The first check in the list is the *base strategy*, which `hypothesis` uses to generate data.
- All subsequent checks filter the values generated by the previous strategy such that it fulfills the constraints of current check.

To optimize efficiency of the data-generation procedure, make sure to specify the most restrictive constraint of a column as the *base strategy* and build other constraints on top of it.

### 6.10.4.2 In-line Custom Checks

One of the strengths of `pandera` is its flexibility with regard to defining custom checks on the fly:

```
schema_inline_check = pa.DataFrameSchema({
    "col": pa.Column(str, pa.Check(lambda s: s.isin({"foo", "bar"})))
})
```

One of the disadvantages of this is that the fallback strategy is to simply apply the check to the generated data, which can be highly inefficient. In this case, `hypothesis` will generate strings and try to find examples of strings that are in the set `{"foo", "bar"}`, which will be very slow and most likely raise an `Unsatisfiable` exception. To get around this limitation, you can register custom checks and define strategies that correspond to them.



## 6.10.5 Defining Custom Strategies

All built-in *Check*s are associated with a data synthesis strategy. You can define your own data synthesis strategies by using the *extensions API* to register a custom check function with a corresponding strategy.

## 6.11 Extensions

*new in 0.6.0*

### 6.11.1 Registering Custom Check Methods

One of the strengths of pandera is its flexibility in enabling you to defining in-line custom checks on the fly:

```
import pandera as pa

# checks elements in a column/dataframe
element_wise_check = pa.Check(lambda x: x < 0, element_wise=True)

# applies the check function to a dataframe/series
vectorized_check = pa.Check(lambda series_or_df: series_or_df < 0)
```

However, there are two main disadvantages of schemas with inline custom checks:

1. they are not serializable with the *IO interface*.
2. you can't use them to *synthesize data* because the checks are not associated with a *hypothesis* strategy.

pandera now offers a way to register custom checks so that they're available in the *Check* class as a check method. Here let's define a custom method that checks whether a pandas object contains elements that lie within two values.

```
import pandera as pa
import pandera.extensions as extensions
import pandas as pd

@extensions.register_check_method(statistics=["min_value", "max_value"])
def is_between(pandas_obj, *, min_value, max_value):
    return (min_value <= pandas_obj) & (pandas_obj <= max_value)

schema = pa.DataFrameSchema({
    "col": pa.Column(int, pa.Check.is_between(min_value=1, max_value=10))
})

data = pd.DataFrame({"col": [1, 5, 10]})
print(schema(data))
```

```
   col
0    1
1    5
2   10
```

As you can see, a custom check's first argument is a pandas series or dataframe by default (more on that later), followed by keyword-only arguments, specified with the *\** syntax.

The `register_check_method()` requires you to explicitly name the check statistics via the keyword argument, which are essentially the constraints placed by the check on the pandas data structure.

### 6.11.2 Specifying a Check Strategy

To specify a check strategy with your custom check, you'll need to install the `strategies extension`. First let's look at a trivially simple example, where the check verifies whether a column is equal to a certain value:

```
def custom_equals(pandas_obj, *, value):
    return pandas_obj == value
```

The corresponding strategy for this check would be:

```
from typing import Optional
import hypothesis
import pandera.strategies as st

def equals_strategy(
    pandera_dtype: pa.DataType,
    strategy: Optional[st.SearchStrategy] = None,
    *,
    value,
):
    if strategy is None:
        return st.pandas_dtype_strategy(
            pandera_dtype, strategy=hypothesis.strategies.just(value),
        )
    return strategy.filter(lambda x: x == value)
```

As you may notice, the pandera strategy interface has two arguments followed by keyword-only arguments that match the check function keyword-only check statistics. The `pandera_dtype` positional argument is useful for ensuring the correct data type. In the above example, we're using the `pandas_dtype_strategy()` strategy to make sure the generated value is of the correct data type.

The optional `strategy` argument allows us to use the check strategy as a *base strategy* or a *chained strategy*. There's a detail that we're responsible for implementing in the strategy function body: we need to handle two cases to account for *strategy chaining*:

1. when the strategy function is being used as a *base strategy*, i.e. when `strategy` is `None`
2. when the strategy function is being chained from a previously-defined strategy, i.e. when `strategy` is not `None`.

Finally, to register the custom check with the strategy, use the `register_check_method()` decorator:

```
@extensions.register_check_method(
    statistics=["value"], strategy=equals_strategy
)
def custom_equals(pandas_obj, *, value):
    return pandas_obj == value
```

Let's unpack what's going in here. The `custom_equals` function only has a single statistic, which is the `value` argument, which we've also specified in `register_check_method()`. This means that the associated check strategy must match its keyword-only arguments.

Going back to our `is_between` function example, here's what the strategy would look like:

```

def in_between_strategy(
    pandera_dtype: pa.DataType,
    strategy: Optional[st.SearchStrategy] = None,
    *,
    min_value,
    max_value
):
    if strategy is None:
        return st.pandas_dtype_strategy(
            pandera_dtype,
            min_value=min_value,
            max_value=max_value,
            exclude_min=False,
            exclude_max=False,
        )
    return strategy.filter(lambda x: min_value <= x <= max_value)

@extensions.register_check_method(
    statistics=["min_value", "max_value"],
    strategy=in_between_strategy,
)
def is_between_with_strat(pandas_obj, *, min_value, max_value):
    return (min_value <= pandas_obj) & (pandas_obj <= max_value)

```

### 6.11.3 Check Types

The extensions module also supports registering *element-wise* and *groupby* checks.

#### 6.11.3.1 Element-wise Checks

```

@extensions.register_check_method(
    statistics=["val"],
    check_type="element_wise",
)
def element_wise_equal_check(element, *, val):
    return element == val

```

Note that the first argument of `element_wise_equal_check` is a single element in the column or dataframe.

#### 6.11.3.2 Groupby Checks

In this groupby check, we're verifying that the values of one column for `group_a` are, on average, greater than those of `group_b`:

```

from typing import Dict

@extensions.register_check_method(
    statistics=["group_a", "group_b"],
    check_type="groupby",
)

```

(continues on next page)

(continued from previous page)

```

def groupby_check(dict_groups: Dict[str, pd.Series], *, group_a, group_b):
    return dict_groups[group_a].mean() > dict_groups[group_b].mean()

data = pd.DataFrame({
    "values": [20, 10, 1, 15],
    "groups": list("xyxy"),
})

schema = pa.DataFrameSchema({
    "values": pa.Column(
        int,
        pa.Check.groupby_check(group_a="x", group_b="y", groupby="groups"),
    ),
    "groups": pa.Column(str),
})

print(schema(data))

```

	values	groups
0	20	x
1	10	x
2	1	y
3	15	y

#### 6.11.4 Registered Custom Checks with the Class-based API

Since registered checks are part of the `Check` namespace, you can also use custom checks with the *class-based API*:

```

from pandera.typing import Series

class Schema(pa.SchemaModel):
    col1: Series[str] = pa.Field(custom_equals="value")
    col2: Series[int] = pa.Field(is_between={"min_value": 0, "max_value": 10})

data = pd.DataFrame({
    "col1": ["value"] * 5,
    "col2": range(5)
})

print(Schema.validate(data))

```

	col1	col2
0	value	0
1	value	1
2	value	2
3	value	3
4	value	4

DataFrame checks can be attached by using the `Config` class. Any field names that do not conflict with existing fields of `BaseConfig` and do not start with an underscore (`_`) are interpreted as the name of registered checks. If the value is a tuple or dict, it is interpreted as the positional or keyword arguments of the check, and as the first argument otherwise.

For example, to register zero, one, and two statistic dataframe checks one could do the following:

```
import pandera as pa
import pandera.extensions as extensions
import numpy as np
import pandas as pd

@extensions.register_check_method()
def is_small(df):
    return sum(df.shape) < 1000

@extensions.register_check_method(statistics=["fraction"])
def total_missing_fraction_less_than(df, *, fraction: float):
    return (1 - df.count().sum().item() / sum(df.shape)) < fraction

@extensions.register_check_method(statistics=["col_a", "col_b"])
def col_mean_a_greater_than_b(df, *, col_a: str, col_b: str):
    return df[col_a].mean() > df[col_b].mean()

from pandera.typing import Series

class Schema(pa.SchemaModel):
    col1: Series[float] = pa.Field(nullable=True, ignore_na=False)
    col2: Series[float] = pa.Field(nullable=True, ignore_na=False)

    class Config:
        is_small = ()
        total_missing_fraction_less_than = 0.6
        col_mean_a_greater_than_b = {"col_a": "col2", "col_b": "col1"}

data = pd.DataFrame({
    "col1": [float('nan')] * 3 + [0.5, 0.3, 0.1],
    "col2": np.arange(6.),
})

print(Schema.validate(data))
```

```
   col1  col2
0  NaN    0.0
1  NaN    1.0
2  NaN    2.0
3  0.5    3.0
4  0.3    4.0
5  0.1    5.0
```

## 6.12 Reading Third-Party Schema (new)

*new in 0.7.0*

Pandera now accepts schema from other data validation frameworks. This requires a pandera installation with the `io` extension; please see the *installation* instructions for more details.

### 6.12.1 Frictionless Data Schema

---

**Note:** Please see the [Frictionless schema](#) documentation for more information on this standard.

---

`pandera.io.from_frictionless_schema(schema)`

Create a `DataFrameSchema` from either a frictionless json/yaml schema file saved on disk, or from a frictionless schema already loaded into memory.

Each field from the frictionless schema will be converted to a pandera column specification using `FrictionlessFieldParser` to map field characteristics to pandera column specifications.

**Parameters** `schema` (`Union[str, Path, Dict, Schema]`) – the frictionless schema object (or a string/Path to the location on disk of a schema specification) to parse.

**Return type** `DataFrameSchema`

**Returns** dataframe schema with frictionless field specs converted to pandera column checks and constraints for use as normal.

#### Example

Here, we're defining a very basic frictionless schema in memory before parsing it and then querying the resulting `DataFrameSchema` object as per any other Pandera schema:

```
>>> from pandera.io import from_frictionless_schema
>>>
>>> FRICTIONLESS_SCHEMA = {
...     "fields": [
...         {
...             "name": "column_1",
...             "type": "integer",
...             "constraints": {"minimum": 10, "maximum": 99}
...         },
...         {
...             "name": "column_2",
...             "type": "string",
...             "constraints": {"maxLength": 10, "pattern": "\\S+"}
...         },
...     ],
...     "primaryKey": "column_1"
... }
>>> schema = from_frictionless_schema(FRICTIONLESS_SCHEMA)
>>> schema.columns["column_1"].checks
[<Check in_range: in_range(10, 99)>]
>>> schema.columns["column_1"].required
True
>>> schema.columns["column_1"].allow_duplicates
```

(continues on next page)

(continued from previous page)

```
False
>>> schema.columns["column_2"].checks
[<Check str_length: str_length(None, 10)>, <Check str_matches: str_matches(re.
↪ compile('^\\S+$'))>]
```

under the hood, this uses the *FrictionlessFieldParser* class to parse each frictionless field (column):

```
class pandera.io.FrictionlessFieldParser(field, primary_keys)
```

Parses frictionless data schema field specifications so we can convert them to an equivalent Pandera *Column* schema.

For this implementation, we are using field names, constraints and types but leaving other frictionless parameters out (e.g. foreign keys, type formats, titles, descriptions).

#### Parameters

- **field** – a field object from a frictionless schema.
- **primary\_keys** – the primary keys from a frictionless schema. These are used to ensure primary key fields are treated properly - no duplicates, no missing values etc.

**property allow\_duplicates:** `bool`

Determine whether this field can contain duplicate values.

If a field is a primary key, this will return `False`.

**Return type** `bool`

**property checks:** `Optional[Dict]`

Convert a set of frictionless schema field constraints into checks.

This parses the standard set of frictionless constraints which can be found [here](#) and maps them into the equivalent pandera checks.

**Return type** `Optional[Dict]`

**Returns** a dictionary of pandera *Check* objects which capture the standard constraint logic of a frictionless schema field.

**property coerce:** `bool`

Determine whether values within this field should be coerced.

This currently returns `True` for all fields within a frictionless schema.

**Return type** `bool`

**property dtype:** `str`

Determine what type of field this is, so we can feed that into *DataType*. If no type is specified in the frictionless schema, we default to string values.

**Return type** `str`

**Returns** the pandas-compatible representation of this field type as a string.

**property nullable:** `bool`

Determine whether this field can contain missing values.

If a field is a primary key, this will return `False`.

**Return type** `bool`

**property regex:** `bool`

Determine whether this field name should be used for regex matches.

This currently returns `False` for all fields within a frictionless schema.

**Return type** `bool`

**property required:** `bool`

Determine whether this field must exist within the data.

This currently returns `True` for all fields within a frictionless schema.

**Return type** `bool`

**to\_pandera\_column()**

Export this field to a column spec dictionary.

**Return type** `Dict`

## 6.13 API

<i>Core</i>	The core objects for defining pandera schemas
<i>Data Types</i>	Data types for type checking and coercion.
<i>Schema Models</i>	Alternative class-based API for defining pandera schemas.
<i>Decorators</i>	Decorators for integrating pandera schemas with python functions.
<i>Schema Inference</i>	Bootstrap schemas from real data
<i>IO Utilities</i>	Utility functions for reading/writing schemas
<i>Data Synthesis Strategies</i>	Module of functions for generating data from schemas.
<i>Extensions</i>	Utility functions for extending pandera functionality
<i>Errors</i>	Pandera-specific exceptions

### 6.13.1 Core

#### 6.13.1.1 Schemas

<code>pandera.schemas.DataFrameSchema</code>	A light-weight pandas DataFrame validator.
<code>pandera.schemas.SeriesSchema</code>	Series validator.

##### 6.13.1.1.1 `pandera.schemas.DataFrameSchema`

```
class pandera.schemas.DataFrameSchema(columns=None, checks=None, index=None, dtype=None,
transformer=None, coerce=False, strict=False, name=None,
ordered=False, pandas_dtype=None)
```

A light-weight pandas DataFrame validator.

Initialize DataFrameSchema validator.

#### Parameters

- **columns** (*mapping of column names and column schema component.*) – a dict where keys are column names and values are Column objects specifying the datatypes and properties of a particular column.
- **checks** (`Union[Check, Hypothesis, List[Union[Check, Hypothesis]], None]`) – dataframe-wide checks.



- **index** – specify the datatypes and properties of the index.
- **dtype** (`Union[str, type, DataType, ExtensionDtype, dtype, None]`) – datatype of the dataframe. This overrides the data types specified in any of the columns. If a string is specified, then assumes one of the valid pandas string values: <http://pandas.pydata.org/pandas-docs/stable/basics.html#dtypes>.
- **transformer** (`Optional[Callable]`) – a callable with signature: `pandas.DataFrame -> pandas.DataFrame`. If specified, calling `validate` will verify properties of the columns and return the transformed dataframe object.
- **coerce** (`bool`) – whether or not to coerce all of the columns on validation. This has no effect on columns where `pandas_dtype=None`
- **strict** (`Union[bool, str]`) – ensure that all and only the columns defined in the schema are present in the dataframe. If set to ‘filter’, only the columns in the schema will be passed to the validated dataframe. If set to filter and columns defined in the schema are not present in the dataframe, will throw an error.
- **name** (`Optional[str]`) – name of the schema.
- **ordered** (`bool`) – whether or not to validate the columns order.
- **pandas\_dtype** (`Union[str, type, DataType, ExtensionDtype, dtype, None]`) – alias of `dtype` for backwards compatibility.

**Warning:** This option will be deprecated in 0.8.0

### Raises

- `SchemaInitError` – if impossible to build schema from parameters
- `SchemaInitError` – if `dtype` and `pandas_dtype` are both supplied.

### Examples

```
>>> import pandera as pa
>>>
>>> schema = pa.DataFrameSchema({
...     "str_column": pa.Column(str),
...     "float_column": pa.Column(float),
...     "int_column": pa.Column(int),
...     "date_column": pa.Column(pa.DateTime),
... })
```

Use the pandas API to define checks, which takes a function with the signature: `pd.Series -> Union[bool, pd.Series]` where the output series contains boolean values.

```
>>> schema_withchecks = pa.DataFrameSchema({
...     "probability": pa.Column(
...         float, pa.Check(lambda s: (s >= 0) & (s <= 1))),
...
...     # check that the "category" column contains a few discrete
...     # values, and the majority of the entries are dogs.
...     "category": pa.Column(
...         str, [
...             pa.Check(lambda s: s.isin(["dog", "cat", "duck"])),
```

(continues on next page)

```

...     pa.Check(lambda s: (s == "dog").mean() > 0.5),
...     ],
... })

```

See [here](#) for more usage details.

## Attributes

<code>coerce</code>	Whether to coerce series to specified type.
<code>dtype</code>	Get the dtype property.
<code>dtypes</code>	A dict where the keys are column names and values are <i>DataType</i> s for the column.
<code>ordered</code>	Whether or not to validate the columns order.

## Methods

<code>__init__</code>	Initialize DataFrameSchema validator.
<code>add_columns</code>	Create a copy of the <i>DataFrameSchema</i> with extra columns.
<code>coerce_dtype</code>	Coerce dataframe to the type specified in dtype.
<code>example</code>	Generate an example of a particular size.
<code>from_yaml</code>	Create DataFrameSchema from yaml file.
<code>get_dtypes</code>	Same as the dtype property, but expands columns where <code>regex == True</code> based on the supplied dataframe.
<code>remove_columns</code>	Removes columns from a <i>DataFrameSchema</i> and returns a new copy.
<code>rename_columns</code>	Rename columns using a dictionary of key-value pairs.
<code>reset_index</code>	A method for resetting the Index of a <i>DataFrameSchema</i>
<code>select_columns</code>	Select subset of columns in the schema.
<code>set_index</code>	A method for setting the Index of a <i>DataFrameSchema</i> , via an existing Column or list of columns.
<code>strategy</code>	Create a hypothesis strategy for generating a DataFrame.
<code>to_script</code>	Create DataFrameSchema from yaml file.
<code>to_yaml</code>	Write DataFrameSchema to yaml file.
<code>update_column</code>	Create copy of a <i>DataFrameSchema</i> with updated column properties.
<code>update_columns</code>	Create copy of a <i>DataFrameSchema</i> with updated column properties.
<code>validate</code>	Check if all columns in a dataframe have a column in the Schema.
<code>__call__</code>	Alias for <i>DataFrameSchema.validate()</i> method.

### 6.13.1.1.1.1 pandera.schemas.DataFrameSchema.\_\_init\_\_

`DataFrameSchema.__init__` (*columns=None, checks=None, index=None, dtype=None, transformer=None, coerce=False, strict=False, name=None, ordered=False, pandas\_dtype=None*)

Initialize DataFrameSchema validator.

#### Parameters

- **columns** (*mapping of column names and column schema component.*) – a dict where keys are column names and values are Column objects specifying the datatypes and properties of a particular column.
- **checks** (`Union[Check, Hypothesis, List[Union[Check, Hypothesis]], None]`) – dataframe-wide checks.
- **index** – specify the datatypes and properties of the index.
- **dtype** (`Union[str, type, DataType, ExtensionDtype, dtype, None]`) – datatype of the dataframe. This overrides the data types specified in any of the columns. If a string is specified, then assumes one of the valid pandas string values: <http://pandas.pydata.org/pandas-docs/stable/basics.html#dtypes>.
- **transformer** (`Optional[Callable]`) – a callable with signature: `pandas.DataFrame -> pandas.DataFrame`. If specified, calling `validate` will verify properties of the columns and return the transformed dataframe object.
- **coerce** (`bool`) – whether or not to coerce all of the columns on validation. This has no effect on columns where `pandas_dtype=None`
- **strict** (`Union[bool, str]`) – ensure that all and only the columns defined in the schema are present in the dataframe. If set to 'filter', only the columns in the schema will be passed to the validated dataframe. If set to filter and columns defined in the schema are not present in the dataframe, will throw an error.
- **name** (`Optional[str]`) – name of the schema.
- **ordered** (`bool`) – whether or not to validate the columns order.
- **pandas\_dtype** (`Union[str, type, DataType, ExtensionDtype, dtype, None]`) – alias of `dtype` for backwards compatibility.

**Warning:** This option will be deprecated in 0.8.0

#### Raises

- `SchemaInitError` – if impossible to build schema from parameters
- `SchemaInitError` – if `dtype` and `pandas_dtype` are both supplied.

#### Examples

```
>>> import pandera as pa
>>>
>>> schema = pa.DataFrameSchema({
...     "str_column": pa.Column(str),
...     "float_column": pa.Column(float),
...     "int_column": pa.Column(int),
```

(continues on next page)

(continued from previous page)

```
...     "date_column": pa.Column(pa.DateTime),
... })
```

Use the pandas API to define checks, which takes a function with the signature: `pd.Series -> Union[bool, pd.Series]` where the output series contains boolean values.

```
>>> schema_withchecks = pa.DataFrameSchema({
...     "probability": pa.Column(
...         float, pa.Check(lambda s: (s >= 0) & (s <= 1))),
...     # check that the "category" column contains a few discrete
...     # values, and the majority of the entries are dogs.
...     "category": pa.Column(
...         str, [
...             pa.Check(lambda s: s.isin(["dog", "cat", "duck"])),
...             pa.Check(lambda s: (s == "dog").mean() > 0.5),
...         ]),
... })
```

See [here](#) for more usage details.

#### 6.13.1.1.1.2 pandera.schemas.DataFrameSchema.add\_columns

`DataFrameSchema.add_columns(extra_schema_cols)`

Create a copy of the `DataFrameSchema` with extra columns.

**Parameters** `extra_schema_cols` (`DataFrameSchema`) – Additional columns of the format

**Return type** `DataFrameSchema`

**Returns** a new `DataFrameSchema` with the `extra_schema_cols` added.

#### Example

To add columns to the schema, pass a dictionary with column name and `Column` instance key-value pairs.

```
>>> import pandera as pa
>>>
>>> example_schema = pa.DataFrameSchema(
...     {
...         "category": pa.Column(str),
...         "probability": pa.Column(float),
...     }
... )
>>> print(
...     example_schema.add_columns({"even_number": pa.Column(pa.Bool)})
... )
<Schema DataFrameSchema(
  columns={
    'category': <Schema Column(name=category, type=DataType(str))>
    'probability': <Schema Column(name=probability, type=DataType(float64))>
    'even_number': <Schema Column(name=even_number, type=DataType(bool))>
  },
  checks=[],
```

(continues on next page)

(continued from previous page)

```
coerce=False,  
dtype=None,  
index=None,  
strict=False  
name=None,  
ordered=False  
)>
```

**See also:**

`remove_columns()`

### 6.13.1.1.1.3 `pandera.schemas.DataFrameSchema.coerce_dtype`

`DataFrameSchema.coerce_dtype(obj)`

Coerce dataframe to the type specified in dtype.

**Parameters** `obj` (`DataFrame`) – dataframe to coerce.

**Return type** `DataFrame`

**Returns** dataframe with coerced dtypes

### 6.13.1.1.1.4 `pandera.schemas.DataFrameSchema.example`

`DataFrameSchema.example(size=None, n_regex_columns=1)`

Generate an example of a particular size.

**Parameters** `size` (`Optional[int]`) – number of elements in the generated DataFrame.

**Return type** `DataFrame`

**Returns** pandas DataFrame object.

### 6.13.1.1.1.5 `pandera.schemas.DataFrameSchema.from_yaml`

**classmethod** `DataFrameSchema.from_yaml(yaml_schema)`

Create DataFrameSchema from yaml file.

**Parameters** `yaml_schema` – str, Path to yaml schema, or serialized yaml string.

**Return type** `DataFrameSchema`

**Returns** dataframe schema.

### 6.13.1.1.1.6 `pandera.schemas.DataFrameSchema.get_dtypes`

`DataFrameSchema.get_dtypes(dataframe)`

Same as the `dtype` property, but expands columns where `regex == True` based on the supplied dataframe.

**Return type** `Dict[str, str]`

**Returns** dictionary of columns and their associated dtypes.

### 6.13.1.1.1.7 `pandera.schemas.DataFrameSchema.remove_columns`

`DataFrameSchema.remove_columns(cols_to_remove)`

Removes columns from a `DataFrameSchema` and returns a new copy.

**Parameters** `cols_to_remove (List)` – Columns to be removed from the `DataFrameSchema`

**Return type** `DataFrameSchema`

**Returns** a new `DataFrameSchema` without the `cols_to_remove`

**Raises** `SchemaInitError`: if column not in schema.

**Example**

To remove a column or set of columns from a schema, pass a list of columns to be removed:

```
>>> import pandera as pa
>>>
>>> example_schema = pa.DataFrameSchema(
...     {
...         "category" : pa.Column(str),
...         "probability": pa.Column(float)
...     }
... )
>>>
>>> print(example_schema.remove_columns(["category"]))
<Schema DataFrameSchema(
  columns={
    'probability': <Schema Column(name=probability, type=DataType(float64))>
  },
  checks=[],
  coerce=False,
  dtype=None,
  index=None,
  strict=False
  name=None,
  ordered=False
)>
```

**See also:**

`add_columns()`

### 6.13.1.1.1.8 pandera.schemas.DataFrameSchema.rename\_columns

`DataFrameSchema.rename_columns(rename_dict)`

Rename columns using a dictionary of key-value pairs.

**Parameters** `rename_dict` (`Dict[str, str]`) – dictionary of ‘old\_name’: ‘new\_name’ key-value pairs.

**Return type** `DataFrameSchema`

**Returns** `DataFrameSchema` (copy of original)

**Raises** `SchemaInitError` if column not in the schema.

#### Example

To rename a column or set of columns, pass a dictionary of old column names and new column names, similar to the pandas `DataFrame` method.

```
>>> import pandera as pa
>>>
>>> example_schema = pa.DataFrameSchema({
...     "category" : pa.Column(str),
...     "probability": pa.Column(float)
... })
>>>
>>> print(
...     example_schema.rename_columns({
...         "category": "categories",
...         "probability": "probabilities"
...     })
... )
<Schema DataFrameSchema(
  columns={
    'categories': <Schema Column(name=categories, type=DataType(str))>
    'probabilities': <Schema Column(name=probabilities,
↪ type=DataType(float64))>
  },
  checks=[],
  coerce=False,
  dtype=None,
  index=None,
  strict=False
  name=None,
  ordered=False
)>
```

#### See also:

[update\\_column\(\)](#)

### 6.13.1.1.1.9 pandera.schemas.DataFrameSchema.reset\_index

`DataFrameSchema.reset_index(level=None, drop=False)`

A method for resetting the Index of a *DataFrameSchema*

#### Parameters

- **level** (`Optional[List[str]]`) – list of labels
- **drop** (`bool`) – bool, default True

**Return type** *DataFrameSchema*

**Returns** a new *DataFrameSchema* with specified column(s) in the index.

**Raises** *SchemaInitError* if no index set in schema.

#### Examples

Similar to the pandas `reset_index` method on a pandas `DataFrame`, this method can be used to to fully or partially reset indices of a schema.

To remove the entire index from the schema, just call the `reset_index` method with default parameters.

```
>>> import pandera as pa
>>>
>>> example_schema = pa.DataFrameSchema(
...     {"probability" : pa.Column(float)},
...     index = pa.Index(name="unique_id", dtype=int)
... )
>>>
>>> print(example_schema.reset_index())
<Schema DataFrameSchema(
  columns={
    'probability': <Schema Column(name=probability, type=DataType(float64))>
    'unique_id': <Schema Column(name=unique_id, type=DataType(int64))>
  },
  checks=[],
  coerce=False,
  dtype=None,
  index=None,
  strict=False,
  name=None,
  ordered=False
)>
```

This reclassifies an index (or indices) as a column (or columns).

Similarly, to partially alter the index, pass the name of the column you would like to be removed to the `level` parameter, and you may also decide whether to drop the levels with the `drop` parameter.

```
>>> example_schema = pa.DataFrameSchema({
...     "category" : pa.Column(str)},
...     index = pa.MultiIndex([
...         pa.Index(name="unique_id1", dtype=int),
...         pa.Index(name="unique_id2", dtype=str)
...     ])
... )
```

(continues on next page)



(continued from previous page)

```

... )
>>> print(example_schema.reset_index(level = ["unique_id1"]))
<Schema DataFrameSchema(
  columns={
    'category': <Schema Column(name=category, type=DataType(str))>
    'unique_id1': <Schema Column(name=unique_id1, type=DataType(int64))>
  },
  checks=[],
  coerce=False,
  dtype=None,
  index=<Schema Index(name=unique_id2, type=DataType(str))>,
  strict=False
  name=None,
  ordered=False
)>

```

**See also:**`set_index()`**6.13.1.1.10 pandera.schemas.DataFrameSchema.select\_columns**`DataFrameSchema.select_columns(columns)`

Select subset of columns in the schema.

*New in version 0.4.5***Parameters** `columns` (`List[Any]`) – list of column names to select.**Return type** `DataFrameSchema`**Returns** `DataFrameSchema` (copy of original) with only the selected columns.**Raises** `SchemaInitError` if column not in the schema.**Example**

To subset a schema by column, and return a new schema:

```

>>> import pandera as pa
>>>
>>> example_schema = pa.DataFrameSchema({
...     "category" : pa.Column(str),
...     "probability": pa.Column(float)
... })
>>>
>>> print(example_schema.select_columns(['category']))
<Schema DataFrameSchema(
  columns={
    'category': <Schema Column(name=category, type=DataType(str))>
  },
  checks=[],
  coerce=False,
  dtype=None,
  index=None,

```

(continues on next page)

```

strict=False
name=None,
ordered=False
)>

```

---

**Note:** If an index is present in the schema, it will also be included in the new schema.

---

### 6.13.1.1.1.11 `pandera.schemas.DataFrameSchema.set_index`

`DataFrameSchema.set_index(keys, drop=True, append=False)`

A method for setting the Index of a `DataFrameSchema`, via an existing Column or list of columns.

#### Parameters

- **keys** (`List[str]`) – list of labels
- **drop** (`bool`) – bool, default True
- **append** (`bool`) – bool, default False

**Return type** `DataFrameSchema`

**Returns** a new `DataFrameSchema` with specified column(s) in the index.

**Raises** `SchemaInitError` if column not in the schema.

#### Examples

Just as you would set the index in a pandas `DataFrame` from an existing column, you can set an index within the schema from an existing column in the schema.

```

>>> import pandera as pa
>>>
>>> example_schema = pa.DataFrameSchema({
...     "category" : pa.Column(str),
...     "probability": pa.Column(float)})
>>>
>>> print(example_schema.set_index(['category']))
<Schema DataFrameSchema(
  columns={
    'probability': <Schema Column(name=probability, type=DataType(float64))>
  },
  checks=[],
  coerce=False,
  dtype=None,
  index=<Schema Index(name=category, type=DataType(str))>,
  strict=False
  name=None,
  ordered=False
)>

```

If you have an existing index in your schema, and you would like to append a new column as an index to it (yielding a `Multiindex`), just use `set_index` as you would in pandas.

```

>>> example_schema = pa.DataFrameSchema(
...     {
...         "column1": pa.Column(str),
...         "column2": pa.Column(int)
...     },
...     index=pa.Index(name = "column3", dtype = int)
... )
>>>
>>> print(example_schema.set_index(["column2"], append = True))
<Schema DataFrameSchema(
  columns={
    'column1': <Schema Column(name=column1, type=DataType(str))>
  },
  checks=[],
  coerce=False,
  dtype=None,
  index=<Schema MultiIndex(
    indexes=[
      <Schema Index(name=column3, type=DataType(int64))>
      <Schema Index(name=column2, type=DataType(int64))>
    ]
    coerce=False,
    strict=False,
    name=None,
    ordered=True
  )>,
  strict=False,
  name=None,
  ordered=False
)>

```

**See also:**

`reset_index()`

#### 6.13.1.1.12 pandera.schemas.DataFrameSchema.strategy

`DataFrameSchema.strategy(*, size=None, n_regex_columns=1)`

Create a hypothesis strategy for generating a DataFrame.

##### Parameters

- **size** (`Optional[int]`) – number of elements to generate
- **n\_regex\_columns** (`int`) – number of regex columns to generate.

**Returns** a strategy that generates pandas DataFrame objects.

### 6.13.1.1.1.13 `pandera.schemas.DataFrameSchema.to_script`

`DataFrameSchema.to_script(fp=None)`

Create `DataFrameSchema` from yaml file.

**Parameters** `path` – str, Path to write script

**Return type** `DataFrameSchema`

**Returns** dataframe schema.

### 6.13.1.1.1.14 `pandera.schemas.DataFrameSchema.to_yaml`

`DataFrameSchema.to_yaml(stream=None)`

Write `DataFrameSchema` to yaml file.

**Parameters** `stream` (`Optional[PathLike]`) – file stream to write to. If None, dumps to string.

**Returns** yaml string if stream is None, otherwise returns None.

### 6.13.1.1.1.15 `pandera.schemas.DataFrameSchema.update_column`

`DataFrameSchema.update_column(column_name, **kwargs)`

Create copy of a `DataFrameSchema` with updated column properties.

**Parameters**

- `column_name` (`str`) –
- `kwargs` – key-word arguments supplied to `Column`

**Return type** `DataFrameSchema`

**Returns** a new `DataFrameSchema` with updated column

**Raises** `SchemaInitError`: if column not in schema or you try to change the name.

**Example**

Calling `schema.1` returns the `DataFrameSchema` with the updated column.

```
>>> import pandera as pa
>>>
>>> example_schema = pa.DataFrameSchema({
...     "category" : pa.Column(str),
...     "probability": pa.Column(float)
... })
>>> print(
...     example_schema.update_column(
...         'category', dtype=pa.Category
...     )
... )
<Schema DataFrameSchema(
  columns={
    'category': <Schema Column(name=category, type=DataType(category))>
    'probability': <Schema Column(name=probability, type=DataType(float64))>
  },
```

(continues on next page)

(continued from previous page)

```

checks=[],
coerce=False,
dtype=None,
index=None,
strict=False
name=None,
ordered=False
)>

```

**See also:**

`rename_columns()`

**6.13.1.1.16 pandera.schemas.DataFrameSchema.update\_columns**

`DataFrameSchema.update_columns(update_dict)`

Create copy of a *DataFrameSchema* with updated column properties.

**Parameters** `update_dict` (`Dict[str, Dict[str, Any]]`) –

**Return type** *DataFrameSchema*

**Returns** a new *DataFrameSchema* with updated columns

**Raises** *SchemaInitError*: if column not in schema or you try to change the name.

**Example**

Calling `schema.update_columns` returns the *DataFrameSchema* with the updated columns.

```

>>> import pandera as pa
>>>
>>> example_schema = pa.DataFrameSchema({
...     "category" : pa.Column(str),
...     "probability": pa.Column(float)
... })
>>>
>>> print(
...     example_schema.update_columns(
...         {"category": {"dtype": pa.Category}}
...     )
... )
<Schema DataFrameSchema(
  columns={
    'category': <Schema Column(name=category, type=DataType(category))>
    'probability': <Schema Column(name=probability, type=DataType(float64))>
  },
  checks=[],
  coerce=False,
  dtype=None,
  index=None,
  strict=False
  name=None,
  ordered=False
)>

```

---

**Note:** This is the successor to the `update_column` method, which will be deprecated.

---

### 6.13.1.1.1.17 `pandera.schemas.DataFrameSchema.validate`

`DataFrameSchema.validate`(*check\_obj*, *head=None*, *tail=None*, *sample=None*, *random\_state=None*, *lazy=False*, *inplace=False*)

Check if all columns in a dataframe have a column in the Schema.

#### Parameters

- **check\_obj** (*pd.DataFrame*) – the dataframe to be validated.
- **head** (*Optional[int]*) – validate the first *n* rows. Rows overlapping with *tail* or *sample* are de-duplicated.
- **tail** (*Optional[int]*) – validate the last *n* rows. Rows overlapping with *head* or *sample* are de-duplicated.
- **sample** (*Optional[int]*) – validate a random sample of *n* rows. Rows overlapping with *head* or *tail* are de-duplicated.
- **random\_state** (*Optional[int]*) – random seed for the *sample* argument.
- **lazy** (*bool*) – if True, lazily evaluates dataframe against all validation checks and raises a `SchemaErrors`. Otherwise, raise `SchemaError` as soon as one occurs.
- **inplace** (*bool*) – if True, applies coercion to the object of validation, otherwise creates a copy of the data.

**Return type** `DataFrame`

**Returns** validated `DataFrame`

**Raises** `SchemaError` – when `DataFrame` violates built-in or custom checks.

#### Example

Calling `schema.validate` returns the dataframe.

```
>>> import pandas as pd
>>> import pandera as pa
>>>
>>> df = pd.DataFrame({
...     "probability": [0.1, 0.4, 0.52, 0.23, 0.8, 0.76],
...     "category": ["dog", "dog", "cat", "duck", "dog", "dog"]
... })
>>>
>>> schema_withchecks = pa.DataFrameSchema({
...     "probability": pa.Column(
...         float, pa.Check(lambda s: (s >= 0) & (s <= 1))),
...     # check that the "category" column contains a few discrete
...     # values, and the majority of the entries are dogs.
...     "category": pa.Column(
...         str, [
...             pa.Check(lambda s: s.isin(["dog", "cat", "duck"])),
...             pa.Check(lambda s: (s == "dog").mean() > 0.5),
...         ]
...     )
... })
```

(continues on next page)

(continued from previous page)

```

...     ]),
... })
>>>
>>> schema_withchecks.validate(df)[["probability", "category"]]
  probability category
0          0.10     dog
1          0.40     dog
2          0.52     cat
3          0.23    duck
4          0.80     dog
5          0.76     dog

```

#### 6.13.1.1.18 pandera.schemas.DataFrameSchema.\_\_call\_\_

`DataFrameSchema.__call__(dataframe, head=None, tail=None, sample=None, random_state=None, lazy=False, inplace=False)`

Alias for `DataFrameSchema.validate()` method.

##### Parameters

- **dataframe** (`pd.DataFrame`) – the dataframe to be validated.
- **head** (`int`) – validate the first n rows. Rows overlapping with `tail` or `sample` are de-duplicated.
- **tail** (`int`) – validate the last n rows. Rows overlapping with `head` or `sample` are de-duplicated.
- **sample** (`Optional[int]`) – validate a random sample of n rows. Rows overlapping with `head` or `tail` are de-duplicated.
- **random\_state** (`Optional[int]`) – random seed for the `sample` argument.
- **lazy** (`bool`) – if True, lazily evaluates dataframe against all validation checks and raises a `SchemaErrors`. Otherwise, raise `SchemaError` as soon as one occurs.
- **inplace** (`bool`) – if True, applies coercion to the object of validation, otherwise creates a copy of the data.

#### 6.13.1.1.2 pandera.schemas.SeriesSchema

`class pandera.schemas.SeriesSchema(dtype=None, checks=None, index=None, nullable=False, allow_duplicates=True, coerce=False, name=None, pandas_dtype=None)`

Series validator.

Initialize series schema base object.

##### Parameters

- **dtype** (`Union[str, type, DataType, ExtensionDtype, dtype, None]`) – datatype of the column. If a string is specified, then assumes one of the valid pandas string values: <http://pandas.pydata.org/pandas-docs/stable/basics.html#dtypes>
- **checks** (`Union[Check, Hypothesis, List[Union[Check, Hypothesis]], None]`) – If `element_wise` is True, then callable signature should be:

Callable[*Any*, *bool*] where the *Any* input is a scalar element in the column. Otherwise, the input is assumed to be a `pandas.Series` object.

- **index** – specify the datatypes and properties of the index.
- **nullable** (*bool*) – Whether or not column can contain null values.
- **allow\_duplicates** (*bool*) – Whether or not column can contain duplicate values.
- **coerce** (*bool*) – If True, when `schema.validate` is called the column will be coerced into the specified dtype. This has no effect on columns where `pandas_dtype=None`.
- **name** (*Optional[str]*) – series name.
- **pandas\_dtype** (*Union[str, type, DataType, ExtensionDtype, dtype, None]*) – alias of dtype for backwards compatibility.

**Warning:** This option will be deprecated in 0.8.0

## Attributes

<code>allow_duplicates</code>	Whether to allow duplicate values.
<code>checks</code>	Return list of checks or hypotheses.
<code>coerce</code>	Whether to coerce series to specified type.
<code>dtype</code>	Get the pandas dtype
<code>name</code>	Get SeriesSchema name.
<code>nullable</code>	Whether the series is nullable.

## Methods

<code>__init__</code>	Initialize series schema base object.
<code>validate</code>	Validate a Series object.
<code>__call__</code>	Alias for <code>SeriesSchema.validate()</code> method.

### 6.13.1.1.2.1 pandera.schemas.SeriesSchema.\_\_init\_\_

`SeriesSchema.__init__(dtype=None, checks=None, index=None, nullable=False, allow_duplicates=True, coerce=False, name=None, pandas_dtype=None)`

Initialize series schema base object.

#### Parameters

- **dtype** (*Union[str, type, DataType, ExtensionDtype, dtype, None]*) – datatype of the column. If a string is specified, then assumes one of the valid pandas string values: <http://pandas.pydata.org/pandas-docs/stable/basics.html#dtypes>
- **checks** (*Union[Check, Hypothesis, List[Union[Check, Hypothesis]], None]*) – If `element_wise` is True, then callable signature should be:

Callable[*Any*, *bool*] where the *Any* input is a scalar element in the column. Otherwise, the input is assumed to be a `pandas.Series` object.

- **index** – specify the datatypes and properties of the index.



- **nullable** (*bool*) – Whether or not column can contain null values.
- **allow\_duplicates** (*bool*) – Whether or not column can contain duplicate values.
- **coerce** (*bool*) – If True, when `schema.validate` is called the column will be coerced into the specified dtype. This has no effect on columns where `pandas_dtype=None`.
- **name** (*Optional[str]*) – series name.
- **pandas\_dtype** (*Union[str, type, DataType, ExtensionDtype, dtype, None]*) – alias of dtype for backwards compatibility.

**Warning:** This option will be deprecated in 0.8.0

### 6.13.1.1.2.2 `pandera.schemas.SeriesSchema.validate`

`SeriesSchema.validate`(*check\_obj, head=None, tail=None, sample=None, random\_state=None, lazy=False, inplace=False*)

Validate a Series object.

#### Parameters

- **check\_obj** (*Series*) – One-dimensional ndarray with axis labels (including time series).
- **head** (*Optional[int]*) – validate the first n rows. Rows overlapping with *tail* or *sample* are de-duplicated.
- **tail** (*Optional[int]*) – validate the last n rows. Rows overlapping with *head* or *sample* are de-duplicated.
- **sample** (*Optional[int]*) – validate a random sample of n rows. Rows overlapping with *head* or *tail* are de-duplicated.
- **random\_state** (*Optional[int]*) – random seed for the *sample* argument.
- **lazy** (*bool*) – if True, lazily evaluates dataframe against all validation checks and raises a `SchemaErrors`. Otherwise, raise `SchemaError` as soon as one occurs.
- **inplace** (*bool*) – if True, applies coercion to the object of validation, otherwise creates a copy of the data.

**Return type** `Series`

**Returns** validated `Series`.

**Raises** `SchemaError` – when `DataFrame` violates built-in or custom checks.

#### Example

```
>>> import pandas as pd
>>> import pandera as pa
>>>
>>> series_schema = pa.SeriesSchema(
...     float, [
...         pa.Check(lambda s: s > 0),
...         pa.Check(lambda s: s < 1000),
...         pa.Check(lambda s: s.mean() > 300),
...     ])
>>> series = pd.Series([1, 100, 800, 900, 999], dtype=float)
```

(continues on next page)

(continued from previous page)

```
>>> print(series_schema.validate(series))
0      1.0
1     100.0
2     800.0
3     900.0
4     999.0
dtype: float64
```

### 6.13.1.1.2.3 pandera.schemas.SeriesSchema.\_\_call\_\_

`SeriesSchema.__call__(check_obj, head=None, tail=None, sample=None, random_state=None, lazy=False, inplace=False)`

Alias for `SeriesSchema.validate()` method.

**Return type** Series

### 6.13.1.2 Schema Components

<code>pandera.schema_components.Column</code>	Validate types and properties of DataFrame columns.
<code>pandera.schema_components.Index</code>	Validate types and properties of a DataFrame Index.
<code>pandera.schema_components.MultiIndex</code>	Validate types and properties of a DataFrame MultiIndex.

#### 6.13.1.2.1 pandera.schema\_components.Column

**class** `pandera.schema_components.Column`(*dtype=None, checks=None, nullable=False, allow\_duplicates=True, coerce=False, required=True, name=None, regex=False, pandas\_dtype=None*)

Validate types and properties of DataFrame columns.

Create column validator object.

#### Parameters

- **dtype** (`Union[str, type, DataType, ExtensionDtype, dtype, None]`) – datatype of the column. A `PandasDtype` for type-checking dataframe. If a string is specified, then assumes one of the valid pandas string values: <http://pandas.pydata.org/pandas-docs/stable/basics.html#dtypes>
- **checks** (`Union[Check, Hypothesis, List[Union[Check, Hypothesis]], None]`) – checks to verify validity of the column
- **nullable** (`bool`) – Whether or not column can contain null values.
- **allow\_duplicates** (`bool`) – Whether or not column can contain duplicate values.
- **coerce** (`bool`) – If True, when `schema.validate` is called the column will be coerced into the specified dtype. This has no effect on columns where `pandas_dtype=None`.
- **required** (`bool`) – Whether or not column is allowed to be missing
- **name** (`Union[str, Tuple[str, ...], None]`) – column name in dataframe to validate.

- **regex** (*bool*) – whether the `name` attribute should be treated as a regex pattern to apply to multiple columns in a dataframe.
- **pandas\_dtype** (*Union[str, type, DataType, ExtensionDtype, dtype, None]*) – alias of `dtype` for backwards compatibility.

**Warning:** This option will be deprecated in 0.8.0

Raises *SchemaInitError* – if impossible to build schema from parameters

#### Example

```
>>> import pandas as pd
>>> import pandera as pa
>>>
>>>
>>> schema = pa.DataFrameSchema({
...     "column": pa.Column(str)
... })
>>>
>>> schema.validate(pd.DataFrame({"column": ["foo", "bar"]}))
   column
0     foo
1     bar
```

See [here](#) for more usage details.

#### Attributes

<code>allow_duplicates</code>	Whether to allow duplicate values.
<code>checks</code>	Return list of checks or hypotheses.
<code>coerce</code>	Whether to coerce series to specified type.
<code>dtype</code>	Get the pandas dtype
<code>name</code>	Get SeriesSchema name.
<code>nullable</code>	Whether the series is nullable.
<code>properties</code>	Get column properties.
<code>regex</code>	True if name attribute should be treated as a regex pattern.

#### Methods

<code>__init__</code>	Create column validator object.
<code>coerce_dtype</code>	Coerce dtype of a column, handling duplicate column names.
<code>example</code>	Generate an example of a particular size.
<code>get_regex_columns</code>	Get matching column names based on regex column name pattern.
<code>set_name</code>	Used to set or modify the name of a column object.

continues on next page

Table 8 – continued from previous page

<code>strategy</code>	Create a hypothesis strategy for generating a Column.
<code>strategy_component</code>	Generate column data object for use by DataFrame strategy.
<code>validate</code>	Validate a Column in a DataFrame object.
<code>__call__</code>	Alias for <code>validate</code> method.

#### 6.13.1.2.1.1 `pandera.schema_components.Column.__init__`

`Column.__init__` (*dtype=None, checks=None, nullable=False, allow\_duplicates=True, coerce=False, required=True, name=None, regex=False, pandas\_dtype=None*)

Create column validator object.

##### Parameters

- **dtype** (`Union[str, type, DataType, ExtensionDtype, dtype, None]`) – datatype of the column. A `PandasDtype` for type-checking dataframe. If a string is specified, then assumes one of the valid pandas string values: <http://pandas.pydata.org/pandas-docs/stable/basics.html#dtypes>
- **checks** (`Union[Check, Hypothesis, List[Union[Check, Hypothesis]], None]`) – checks to verify validity of the column
- **nullable** (`bool`) – Whether or not column can contain null values.
- **allow\_duplicates** (`bool`) – Whether or not column can contain duplicate values.
- **coerce** (`bool`) – If True, when `schema.validate` is called the column will be coerced into the specified dtype. This has no effect on columns where `pandas_dtype=None`.
- **required** (`bool`) – Whether or not column is allowed to be missing
- **name** (`Union[str, Tuple[str, ...], None]`) – column name in dataframe to validate.
- **regex** (`bool`) – whether the name attribute should be treated as a regex pattern to apply to multiple columns in a dataframe.
- **pandas\_dtype** (`Union[str, type, DataType, ExtensionDtype, dtype, None]`) – alias of `dtype` for backwards compatibility.

**Warning:** This option will be deprecated in 0.8.0

Raises `SchemaInitError` – if impossible to build schema from parameters

##### Example

```
>>> import pandas as pd
>>> import pandera as pa
>>>
>>>
>>> schema = pa.DataFrameSchema({
...     "column": pa.Column(str)
... })
>>>
>>> schema.validate(pd.DataFrame({"column": ["foo", "bar"]}))
```

(continues on next page)

(continued from previous page)

```

column
0    foo
1    bar

```

See [here](#) for more usage details.

#### 6.13.1.2.1.2 `pandera.schema_components.Column.coerce_dtype`

`Column.coerce_dtype(obj)`

Coerce dtype of a column, handling duplicate column names.

#### 6.13.1.2.1.3 `pandera.schema_components.Column.example`

`Column.example(size=None)`

Generate an example of a particular size.

**Parameters** `size` – number of elements in the generated Index.

**Return type** DataFrame

**Returns** pandas DataFrame object.

#### 6.13.1.2.1.4 `pandera.schema_components.Column.get_regex_columns`

`Column.get_regex_columns(columns)`

Get matching column names based on regex column name pattern.

**Parameters** `columns` (`Union[Index, MultiIndex]`) – columns to regex pattern match

**Return type** `Union[Index, MultiIndex]`

**Returns** matchin columns

#### 6.13.1.2.1.5 `pandera.schema_components.Column.set_name`

`Column.set_name(name)`

Used to set or modify the name of a column object.

**Parameters** `name` (`str`) – the name of the column object

#### 6.13.1.2.1.6 `pandera.schema_components.Column.strategy`

`Column.strategy(*, size=None)`

Create a hypothesis strategy for generating a Column.

**Parameters** `size` – number of elements to generate

**Returns** a dataframe strategy for a single column.

### 6.13.1.2.1.7 `pandera.schema_components.Column.strategy_component`

`Column.strategy_component()`

Generate column data object for use by DataFrame strategy.

### 6.13.1.2.1.8 `pandera.schema_components.Column.validate`

`Column.validate(check_obj, head=None, tail=None, sample=None, random_state=None, lazy=False, inplace=False)`

Validate a Column in a DataFrame object.

#### Parameters

- **check\_obj** (DataFrame) – pandas DataFrame to validate.
- **head** (Optional[int]) – validate the first n rows. Rows overlapping with *tail* or *sample* are de-duplicated.
- **tail** (Optional[int]) – validate the last n rows. Rows overlapping with *head* or *sample* are de-duplicated.
- **sample** (Optional[int]) – validate a random sample of n rows. Rows overlapping with *head* or *tail* are de-duplicated.
- **random\_state** (Optional[int]) – random seed for the *sample* argument.
- **lazy** (bool) – if True, lazily evaluates dataframe against all validation checks and raises a `SchemaErrors`. Otherwise, raise `SchemaError` as soon as one occurs.
- **inplace** (bool) – if True, applies coercion to the object of validation, otherwise creates a copy of the data.

**Return type** DataFrame

**Returns** validated DataFrame.

### 6.13.1.2.1.9 `pandera.schema_components.Column.__call__`

`Column.__call__(check_obj, head=None, tail=None, sample=None, random_state=None, lazy=False, inplace=False)`

Alias for `validate` method.

**Return type** Union[DataFrame, Series]

### 6.13.1.2.2 `pandera.schema_components.Index`

`class pandera.schema_components.Index(dtype=None, checks=None, nullable=False, allow_duplicates=True, coerce=False, name=None, pandas_dtype=None)`

Validate types and properties of a DataFrame Index.

Initialize series schema base object.

#### Parameters

- **dtype** (Union[str, type, DataType, ExtensionDtype, dtype, None]) – datatype of the column. If a string is specified, then assumes one of the valid pandas string values: <http://pandas.pydata.org/pandas-docs/stable/basics.html#dtypes>

- **checks** (`Union[Check, Hypothesis, List[Union[Check, Hypothesis]], None]`) – If `element_wise` is `True`, then callable signature should be:  
`Callable[Any, bool]` where the `Any` input is a scalar element in the column. Otherwise, the input is assumed to be a `pandas.Series` object.
- **nullable** (`bool`) – Whether or not column can contain null values.
- **allow\_duplicates** (`bool`) – Whether or not column can contain duplicate values.
- **coerce** (`bool`) – If `True`, when `schema.validate` is called the column will be coerced into the specified dtype. This has no effect on columns where `dtype=None`.
- **name** (`Optional[Any]`) – column name in dataframe to validate.
- **pandas\_dtype** (`Union[str, type, DataType, ExtensionDtype, dtype, None]`) – alias of dtype for backwards compatibility.

**Warning:** This option will be deprecated in 0.8.0

### Attributes

<code>allow_duplicates</code>	Whether to allow duplicate values.
<code>checks</code>	Return list of checks or hypotheses.
<code>coerce</code>	Whether to coerce series to specified type.
<code>dtype</code>	Get the pandas dtype
<code>name</code>	Get SeriesSchema name.
<code>names</code>	Get index names in the Index schema component.
<code>nullable</code>	Whether the series is nullable.

### Methods

<code>example</code>	Generate an example of a particular size.
<code>strategy</code>	Create a hypothesis strategy for generating an Index.
<code>strategy_component</code>	Generate column data object for use by MultiIndex strategy.
<code>validate</code>	Validate DataFrameSchema or SeriesSchema Index.
<code>__call__</code>	Alias for <code>validate</code> method.

#### 6.13.1.2.2.1 pandera.schema\_components.Index.example

`Index.example(size=None)`

Generate an example of a particular size.

**Parameters** `size` (`Optional[int]`) – number of elements in the generated Index.

**Return type** Index

**Returns** pandas Index object.

#### 6.13.1.2.2.2 pandera.schema\_components.Index.strategy

`Index.strategy(*, size=None)`

Create a hypothesis strategy for generating an Index.

**Parameters** `size` (`Optional[int]`) – number of elements to generate.

**Returns** index strategy.

#### 6.13.1.2.2.3 pandera.schema\_components.Index.strategy\_component

`Index.strategy_component()`

Generate column data object for use by MultiIndex strategy.

#### 6.13.1.2.2.4 pandera.schema\_components.Index.validate

`Index.validate(check_obj, head=None, tail=None, sample=None, random_state=None, lazy=False, inplace=False)`

Validate DataFrameSchema or SeriesSchema Index.

**Check\_obj** pandas DataFrame of Series containing index to validate.

**Parameters**

- **head** (`Optional[int]`) – validate the first n rows. Rows overlapping with *tail* or *sample* are de-duplicated.
- **tail** (`Optional[int]`) – validate the last n rows. Rows overlapping with *head* or *sample* are de-duplicated.
- **sample** (`Optional[int]`) – validate a random sample of n rows. Rows overlapping with *head* or *tail* are de-duplicated.
- **random\_state** (`Optional[int]`) – random seed for the *sample* argument.
- **lazy** (`bool`) – if True, lazily evaluates dataframe against all validation checks and raises a `SchemaErrors`. Otherwise, raise `SchemaError` as soon as one occurs.
- **inplace** (`bool`) – if True, applies coercion to the object of validation, otherwise creates a copy of the data.

**Return type** `Union[DataFrame, Series]`

**Returns** validated DataFrame or Series.

#### 6.13.1.2.2.5 pandera.schema\_components.Index.\_\_call\_\_

`Index.__call__(check_obj, head=None, tail=None, sample=None, random_state=None, lazy=False, inplace=False)`

Alias for `validate` method.

**Return type** `Union[DataFrame, Series]`



### 6.13.1.2.3 pandera.schema\_components.MultiIndex

**class** pandera.schema\_components.**MultiIndex**(*indexes*, *coerce=False*, *strict=False*, *name=None*, *ordered=True*)

Validate types and properties of a DataFrame MultiIndex.

This class inherits from *DataFrameSchema* to leverage its validation logic.

Create MultiIndex validator.

#### Parameters

- **indexes** (*List[Index]*) – list of Index validators for each level of the MultiIndex index.
- **coerce** (*bool*) – Whether or not to coerce the MultiIndex to the specified dtypes before validation
- **strict** (*bool*) – whether or not to accept columns in the MultiIndex that aren't defined in the *indexes* argument.
- **name** (*Optional[str]*) – name of schema component
- **ordered** (*bool*) – whether or not to validate the indexes order.

#### Example

```
>>> import pandas as pd
>>> import pandera as pa
>>>
>>> schema = pa.DataFrameSchema(
...     columns={"column": pa.Column(int)},
...     index=pa.MultiIndex([
...         pa.Index(str,
...             pa.Check(lambda s: s.isin(["foo", "bar"]))),
...         pa.Index(int, name="index1"),
...     ])
... )
>>>
>>> df = pd.DataFrame(
...     data={"column": [1, 2, 3]},
...     index=pd.MultiIndex.from_arrays(
...         [
...             ["foo", "bar", "foo"], [0, 1, 2]
...         ],
...         names=["index0", "index1"],
...     )
... )
>>>
>>> schema.validate(df)
           column
index0 index1
foo      0      1
bar      1      2
foo      2      3
```

See [here](#) for more usage details.

## Attributes

<code>coerce</code>	Whether or not to coerce data types.
<code>dtype</code>	Get the dtype property.
<code>dtypes</code>	A dict where the keys are column names and values are <i>DataTypes</i> for the column.
<code>names</code>	Get index names in the MultiIndex schema component.
<code>ordered</code>	Whether or not to validate the columns order.

## Methods

<code>__init__</code>	Create MultiIndex validator.
<code>coerce_dtype</code>	Coerce type of a pd.Series by type specified in dtype.
<code>example</code>	Generate an example of a particular size.
<code>strategy</code>	Create a hypothesis strategy for generating a DataFrame.
<code>validate</code>	Validate DataFrame or Series MultiIndex.
<code>__call__</code>	Alias for DataFrameSchema.validate() method.

### 6.13.1.2.3.1 pandera.schema\_components.MultiIndex.\_\_init\_\_

`MultiIndex.__init__(indexes, coerce=False, strict=False, name=None, ordered=True)`  
Create MultiIndex validator.

#### Parameters

- **indexes** (`List[Index]`) – list of Index validators for each level of the MultiIndex index.
- **coerce** (`bool`) – Whether or not to coerce the MultiIndex to the specified dtypes before validation
- **strict** (`bool`) – whether or not to accept columns in the MultiIndex that aren't defined in the indexes argument.
- **name** (`Optional[str]`) – name of schema component
- **ordered** (`bool`) – whether or not to validate the indexes order.

#### Example

```
>>> import pandas as pd
>>> import pandera as pa
>>>
>>>
>>> schema = pa.DataFrameSchema(
...     columns={"column": pa.Column(int)},
...     index=pa.MultiIndex([
...         pa.Index(str,
...             pa.Check(lambda s: s.isin(["foo", "bar"])),
...             name="index0"),
...         pa.Index(int, name="index1"),
...     ])

```

(continues on next page)

(continued from previous page)

```

... )
>>>
>>> df = pd.DataFrame(
...     data={"column": [1, 2, 3]},
...     index=pd.MultiIndex.from_arrays(
...         ["foo", "bar", "foo"], [0, 1, 2]),
...     names=["index0", "index1"],
... )
... )
>>>
>>> schema.validate(df)
           column
index0 index1
foo     0         1
bar     1         2
foo     2         3

```

See [here](#) for more usage details.

#### 6.13.1.2.3.2 `pandera.schema_components.MultiIndex.coerce_dtype`

`MultiIndex.coerce_dtype(obj)`

Coerce type of a `pd.Series` by type specified in `dtype`.

**Parameters** `obj` (`MultiIndex`) – multi-index to coerce.

**Return type** `MultiIndex`

**Returns** `MultiIndex` with coerced data type

#### 6.13.1.2.3.3 `pandera.schema_components.MultiIndex.example`

`MultiIndex.example(size=None)`

Generate an example of a particular size.

**Parameters** `size` – number of elements in the generated `DataFrame`.

**Return type** `MultiIndex`

**Returns** pandas `DataFrame` object.

#### 6.13.1.2.3.4 `pandera.schema_components.MultiIndex.strategy`

`MultiIndex.strategy(*, size=None)`

Create a hypothesis strategy for generating a `DataFrame`.

**Parameters**

- `size` – number of elements to generate
- `n_regex_columns` – number of regex columns to generate.

**Returns** a strategy that generates pandas `DataFrame` objects.

### 6.13.1.2.3.5 pandera.schema\_components.MultiIndex.validate

`MultiIndex.validate`(*check\_obj*, *head=None*, *tail=None*, *sample=None*, *random\_state=None*, *lazy=False*, *inplace=False*)

Validate DataFrame or Series MultiIndex.

#### Parameters

- **check\_obj** (`Union[DataFrame, Series]`) – pandas DataFrame of Series to validate.
- **head** (`Optional[int]`) – validate the first n rows. Rows overlapping with *tail* or *sample* are de-duplicated.
- **tail** (`Optional[int]`) – validate the last n rows. Rows overlapping with *head* or *sample* are de-duplicated.
- **sample** (`Optional[int]`) – validate a random sample of n rows. Rows overlapping with *head* or *tail* are de-duplicated.
- **random\_state** (`Optional[int]`) – random seed for the *sample* argument.
- **lazy** (`bool`) – if True, lazily evaluates dataframe against all validation checks and raises a `SchemaErrors`. Otherwise, raise `SchemaError` as soon as one occurs.
- **inplace** (`bool`) – if True, applies coercion to the object of validation, otherwise creates a copy of the data.

**Return type** `Union[DataFrame, Series]`

**Returns** validated DataFrame or Series.

### 6.13.1.2.3.6 pandera.schema\_components.MultiIndex.\_\_call\_\_

`MultiIndex.__call__`(*dataframe*, *head=None*, *tail=None*, *sample=None*, *random\_state=None*, *lazy=False*, *inplace=False*)

Alias for `DataFrameSchema.validate()` method.

#### Parameters

- **dataframe** (`pd.DataFrame`) – the dataframe to be validated.
- **head** (`int`) – validate the first n rows. Rows overlapping with *tail* or *sample* are de-duplicated.
- **tail** (`int`) – validate the last n rows. Rows overlapping with *head* or *sample* are de-duplicated.
- **sample** (`Optional[int]`) – validate a random sample of n rows. Rows overlapping with *head* or *tail* are de-duplicated.
- **random\_state** (`Optional[int]`) – random seed for the *sample* argument.
- **lazy** (`bool`) – if True, lazily evaluates dataframe against all validation checks and raises a `SchemaErrors`. Otherwise, raise `SchemaError` as soon as one occurs.
- **inplace** (`bool`) – if True, applies coercion to the object of validation, otherwise creates a copy of the data.

### 6.13.1.3 Checks

<code>pandera.checks.Check</code>	Check a pandas Series or DataFrame for certain properties.
<code>pandera.hypotheses.Hypothesis</code>	Special type of Check that defines hypothesis tests on data.

#### 6.13.1.3.1 `pandera.checks.Check`

```
class pandera.checks.Check(check_fn, groups=None, groupby=None, ignore_na=True, element_wise=False,
                             name=None, error=None, raise_warning=False, n_failure_cases=10,
                             **check_kwargs)
```

Check a pandas Series or DataFrame for certain properties.

Apply a validation function to each element, Series, or DataFrame.

##### Parameters

- **check\_fn** (`Union[Callable[[Series], Union[Series, bool]], Callable[[DataFrame], Union[DataFrame, Series, bool]]]`) – A function to check pandas data structure. For Column or SeriesSchema checks, if `element_wise` is `True`, this function should have the signature: `Callable[[pd.Series], Union[pd.Series, bool]]`, where the output series is a boolean vector.

If `element_wise` is `False`, this function should have the signature: `Callable[[Any], bool]`, where `Any` is an element in the column.

For `DataFrameSchema` checks, if `element_wise=True`, `fn` should have the signature: `Callable[[pd.DataFrame], Union[pd.DataFrame, pd.Series, bool]]`, where the output dataframe or series contains booleans.

If `element_wise` is `True`, `fn` is applied to each row in the dataframe with the signature `Callable[[pd.Series], bool]` where the series input is a row in the dataframe.

- **groups** (`Union[str, List[str], None]`) – The dict input to the `fn` callable will be constrained to the groups specified by `groups`.
- **groupby** (`Union[str, List[str], Callable, None]`) – If a string or list of strings is provided, these columns are used to group the Column series. If a callable is passed, the expected signature is: `Callable[[pd.DataFrame], pd.core.groupby.DataFrameGroupBy]`

The the case of `Column` checks, this function has access to the entire dataframe, but `Column.name` is selected from this `DataFrameGroupBy` object so that a `SeriesGroupBy` object is passed into `check_fn`.

Specifying the `groupby` argument changes the `check_fn` signature to:

```
Callable[[Dict[Union[str, Tuple[str]], pd.Series]], Union[bool, pd.Series]] # noqa
```

where the input is a dictionary mapping keys to subsets of the column/dataframe.

- **ignore\_na** (`bool`) – If `True`, null values will be ignored when determining if a check passed or failed. For dataframes, ignores rows with any null value. *New in version 0.4.0*
- **element\_wise** (`bool`) – Whether or not to apply validator in an element-wise fashion. If `bool`, assumes that all checks should be applied to the column element-wise. If list, should be the same number of elements as checks.

- **name** (Optional[str]) – optional name for the check.
- **error** (Optional[str]) – custom error message if series fails validation check.
- **raise\_warning** (bool) – if True, raise a UserWarning and do not throw exception instead of raising a SchemaError for a specific check. This option should be used carefully in cases where a failing check is informational and shouldn't stop execution of the program.
- **n\_failure\_cases** (Optional[int]) – report the first n unique failure cases. If None, report all failure cases.
- **check\_kwargs** – key-word arguments to pass into check\_fn

### Example

```

>>> import pandas as pd
>>> import pandera as pa
>>>
>>>
>>> # column checks are vectorized by default
>>> check_positive = pa.Check(lambda s: s > 0)
>>>
>>> # define an element-wise check
>>> check_even = pa.Check(lambda x: x % 2 == 0, element_wise=True)
>>>
>>> # specify assertions across categorical variables using `groupby`,
>>> # for example, make sure the mean measure for group "A" is always
>>> # larger than the mean measure for group "B"
>>> check_by_group = pa.Check(
...     lambda measures: measures["A"].mean() > measures["B"].mean(),
...     groupby=["group"],
... )
>>>
>>> # define a wide DataFrame-level check
>>> check_dataframe = pa.Check(
...     lambda df: df["measure_1"] > df["measure_2"])
>>>
>>> measure_checks = [check_positive, check_even, check_by_group]
>>>
>>> schema = pa.DataFrameSchema(
...     columns={
...         "measure_1": pa.Column(int, checks=measure_checks),
...         "measure_2": pa.Column(int, checks=measure_checks),
...         "group": pa.Column(str),
...     },
...     checks=check_dataframe
... )
>>>
>>> df = pd.DataFrame({
...     "measure_1": [10, 12, 14, 16],
...     "measure_2": [2, 4, 6, 8],
...     "group": ["B", "B", "A", "A"]
... })
>>>
>>> schema.validate(df)[["measure_1", "measure_2", "group"]]
measure_1 measure_2 group

```

(continues on next page)

(continued from previous page)

0	10	2	B
1	12	4	B
2	14	6	A
3	16	8	A

See [here](#) for more usage details.

### Attributes

<code>statistics</code>	Get check statistics.
<code>REGISTERED_CUSTOM_CHECKS</code>	

### Methods

<code>eq</code>	Ensure all elements of a series equal a certain value.
<code>equal_to</code>	Ensure all elements of a series equal a certain value.
<code>ge</code>	Ensure all values are greater or equal a certain value.
<code>greater_than</code>	Ensure values of a series are strictly greater than a minimum value.
<code>greater_than_or_equal_to</code>	Ensure all values are greater or equal a certain value.
<code>gt</code>	Ensure values of a series are strictly greater than a minimum value.
<code>in_range</code>	Ensure all values of a series are within an interval.
<code>isin</code>	Ensure only allowed values occur within a series.
<code>le</code>	Ensure values are less than or equal to a maximum value.
<code>less_than</code>	Ensure values of a series are strictly below a maximum value.
<code>less_than_or_equal_to</code>	Ensure values are less than or equal to a maximum value.
<code>lt</code>	Ensure values of a series are strictly below a maximum value.
<code>ne</code>	Ensure no elements of a series equals a certain value.
<code>not_equal_to</code>	Ensure no elements of a series equals a certain value.
<code>notin</code>	Ensure some defined values don't occur within a series.
<code>str_contains</code>	Ensure that a pattern can be found within each row.
<code>str_endswith</code>	Ensure that all values end with a certain string.
<code>str_length</code>	Ensure that the length of strings is within a specified range.
<code>str_matches</code>	Ensure that string values match a regular expression.
<code>str_startswith</code>	Ensure that all values start with a certain string.
<code>__call__</code>	Validate pandas DataFrame or Series.

#### 6.13.1.3.1.1 `pandera.checks.Check.eq`

**classmethod** `Check.eq(cls, value, **kwargs)`

Ensure all elements of a series equal a certain value.

*New in version 0.4.5* Alias: `eq`

**Parameters**

- **value** – All elements of a given `pandas.Series` must have this value
- **kwargs** – key-word arguments passed into the `Check` initializer.

**Return type** `Check`

**Returns** `Check` object

#### 6.13.1.3.1.2 `pandera.checks.Check.equal_to`

**classmethod** `Check.equal_to(cls, value, **kwargs)`

Ensure all elements of a series equal a certain value.

*New in version 0.4.5* Alias: `eq`

**Parameters**

- **value** – All elements of a given `pandas.Series` must have this value
- **kwargs** – key-word arguments passed into the `Check` initializer.

**Return type** `Check`

**Returns** `Check` object

#### 6.13.1.3.1.3 `pandera.checks.Check.ge`

**classmethod** `Check.ge(cls, min_value, **kwargs)`

Ensure all values are greater or equal a certain value.

*New in version 0.4.5* Alias: `ge`

**Parameters**

- **min\_value** – Allowed minimum value for values of a series. Must be a type comparable to the dtype of the `pandas.Series` to be validated.
- **kwargs** – key-word arguments passed into the `Check` initializer.

**Return type** `Check`

**Returns** `Check` object



#### 6.13.1.3.1.4 `pandera.checks.Check.greater_than`

**classmethod** `Check.greater_than(cls, min_value, **kwargs)`

Ensure values of a series are strictly greater than a minimum value.

*New in version 0.4.5* Alias: `gt`

##### Parameters

- **min\_value** – Lower bound to be exceeded. Must be a type comparable to the dtype of the `pandas.Series` to be validated (e.g. a numerical type for float or int and a datetime for datetime).
- **kwargs** – key-word arguments passed into the `Check` initializer.

**Return type** `Check`

**Returns** `Check` object

#### 6.13.1.3.1.5 `pandera.checks.Check.greater_than_or_equal_to`

**classmethod** `Check.greater_than_or_equal_to(cls, min_value, **kwargs)`

Ensure all values are greater or equal a certain value.

*New in version 0.4.5* Alias: `ge`

##### Parameters

- **min\_value** – Allowed minimum value for values of a series. Must be a type comparable to the dtype of the `pandas.Series` to be validated.
- **kwargs** – key-word arguments passed into the `Check` initializer.

**Return type** `Check`

**Returns** `Check` object

#### 6.13.1.3.1.6 `pandera.checks.Check.gt`

**classmethod** `Check.gt(cls, min_value, **kwargs)`

Ensure values of a series are strictly greater than a minimum value.

*New in version 0.4.5* Alias: `gt`

##### Parameters

- **min\_value** – Lower bound to be exceeded. Must be a type comparable to the dtype of the `pandas.Series` to be validated (e.g. a numerical type for float or int and a datetime for datetime).
- **kwargs** – key-word arguments passed into the `Check` initializer.

**Return type** `Check`

**Returns** `Check` object

#### 6.13.1.3.1.7 pandera.checks.Check.in\_range

**classmethod** `Check.in_range(cls, min_value, max_value, include_min=True, include_max=True, **kwargs)`

Ensure all values of a series are within an interval.

##### Parameters

- **min\_value** – Left / lower endpoint of the interval.
- **max\_value** – Right / upper endpoint of the interval. Must not be smaller than `min_value`.
- **include\_min** – Defines whether `min_value` is also an allowed value (the default) or whether all values must be strictly greater than `min_value`.
- **include\_max** – Defines whether `min_value` is also an allowed value (the default) or whether all values must be strictly smaller than `max_value`.
- **kwargs** – key-word arguments passed into the `Check` initializer.

Both endpoints must be a type comparable to the dtype of the `pandas.Series` to be validated.

**Return type** `Check`

**Returns** `Check` object

#### 6.13.1.3.1.8 pandera.checks.Check.isin

**classmethod** `Check.isin(cls, allowed_values, **kwargs)`

Ensure only allowed values occur within a series.

##### Parameters

- **allowed\_values** (`Iterable`) – The set of allowed values. May be any iterable.
- **kwargs** – key-word arguments passed into the `Check` initializer.

**Return type** `Check`

**Returns** `Check` object

---

**Note:** It is checked whether all elements of a `pandas.Series` are part of the set of elements of allowed values. If allowed values is a string, the set of elements consists of all distinct characters of the string. Thus only single characters which occur in `allowed_values` at least once can meet this condition. If you want to check for substrings use `Check.str_is_substring()`.

---

#### 6.13.1.3.1.9 pandera.checks.Check.le

**classmethod** `Check.le(cls, max_value, **kwargs)`

Ensure values are less than or equal to a maximum value.

*New in version 0.4.5* Alias: `le`

##### Parameters

- **max\_value** – Upper bound not to be exceeded. Must be a type comparable to the dtype of the `pandas.Series` to be validated.
- **kwargs** – key-word arguments passed into the `Check` initializer.

**Return type** *Check*

**Returns** *Check* object

#### 6.13.1.3.1.10 `pandera.checks.Check.less_than`

**classmethod** `Check.less_than(cls, max_value, **kwargs)`

Ensure values of a series are strictly below a maximum value.

*New in version 0.4.5* Alias: `lt`

##### Parameters

- **max\_value** – All elements of a series must be strictly smaller than this. Must be a type comparable to the dtype of the `pandas.Series` to be validated.
- **kwargs** – key-word arguments passed into the *Check* initializer.

**Return type** *Check*

**Returns** *Check* object

#### 6.13.1.3.1.11 `pandera.checks.Check.less_than_or_equal_to`

**classmethod** `Check.less_than_or_equal_to(cls, max_value, **kwargs)`

Ensure values are less than or equal to a maximum value.

*New in version 0.4.5* Alias: `le`

##### Parameters

- **max\_value** – Upper bound not to be exceeded. Must be a type comparable to the dtype of the `pandas.Series` to be validated.
- **kwargs** – key-word arguments passed into the *Check* initializer.

**Return type** *Check*

**Returns** *Check* object

#### 6.13.1.3.1.12 `pandera.checks.Check.lt`

**classmethod** `Check.lt(cls, max_value, **kwargs)`

Ensure values of a series are strictly below a maximum value.

*New in version 0.4.5* Alias: `lt`

##### Parameters

- **max\_value** – All elements of a series must be strictly smaller than this. Must be a type comparable to the dtype of the `pandas.Series` to be validated.
- **kwargs** – key-word arguments passed into the *Check* initializer.

**Return type** *Check*

**Returns** *Check* object

#### 6.13.1.3.1.13 `pandera.checks.Check.ne`

**classmethod** `Check.ne(cls, value, **kwargs)`

Ensure no elements of a series equals a certain value.

*New in version 0.4.5* Alias: `ne`

**Parameters**

- **value** – This value must not occur in the checked `pandas.Series`.
- **kwargs** – key-word arguments passed into the `Check` initializer.

**Return type** `Check`

**Returns** `Check` object

#### 6.13.1.3.1.14 `pandera.checks.Check.not_equal_to`

**classmethod** `Check.not_equal_to(cls, value, **kwargs)`

Ensure no elements of a series equals a certain value.

*New in version 0.4.5* Alias: `ne`

**Parameters**

- **value** – This value must not occur in the checked `pandas.Series`.
- **kwargs** – key-word arguments passed into the `Check` initializer.

**Return type** `Check`

**Returns** `Check` object

#### 6.13.1.3.1.15 `pandera.checks.Check.notin`

**classmethod** `Check.notin(cls, forbidden_values, **kwargs)`

Ensure some defined values don't occur within a series.

**Parameters**

- **forbidden\_values** (`Iterable`) – The set of values which should not occur. May be any iterable.
- **raise\_warning** – if True, check raises `UserWarning` instead of `SchemaError` on validation.

**Return type** `Check`

**Returns** `Check` object

---

**Note:** Like `Check.isin()` this check operates on single characters if it is applied on strings. A string as `paraforbidden_values`meter `forbidden_values` is understood as set of prohibited characters. Any string of length > 1 can't be in it by design.

---

#### 6.13.1.3.1.16 pandera.checks.Check.str\_contains

**classmethod** `Check.str_contains(cls, pattern, **kwargs)`

Ensure that a pattern can be found within each row.

**Parameters**

- **pattern** (`str`) – Regular expression pattern to use for searching
- **kwargs** – key-word arguments passed into the *Check* initializer.

**Return type** *Check*

**Returns** *Check* object

The behaviour is as of `pandas.Series.str.contains()`.

#### 6.13.1.3.1.17 pandera.checks.Check.str\_endswith

**classmethod** `Check.str_endswith(cls, string, **kwargs)`

Ensure that all values end with a certain string.

**Parameters**

- **string** (`str`) – String all values should end with
- **kwargs** – key-word arguments passed into the *Check* initializer.

**Return type** *Check*

**Returns** *Check* object

#### 6.13.1.3.1.18 pandera.checks.Check.str\_length

**classmethod** `Check.str_length(cls, min_value=None, max_value=None, **kwargs)`

Ensure that the length of strings is within a specified range.

**Parameters**

- **min\_value** (`Optional[int]`) – Minimum length of strings (default: no minimum)
- **max\_value** (`Optional[int]`) – Maximum length of strings (default: no maximum)
- **kwargs** – key-word arguments passed into the *Check* initializer.

**Return type** *Check*

**Returns** *Check* object

#### 6.13.1.3.1.19 pandera.checks.Check.str\_matches

**classmethod** `Check.str_matches(cls, pattern, **kwargs)`

Ensure that string values match a regular expression.

**Parameters**

- **pattern** (`str`) – Regular expression pattern to use for matching
- **kwargs** – key-word arguments passed into the *Check* initializer.

**Return type** *Check*

Returns *Check* object

The behaviour is as of `pandas.Series.str.match()`.

#### 6.13.1.3.1.20 `pandera.checks.Check.str_startswith`

**classmethod** `Check.str_startswith(cls, string, **kwargs)`

Ensure that all values start with a certain string.

**Parameters**

- **string** (`str`) – String all values should start with
- **kwargs** – key-word arguments passed into the *Check* initializer.

**Return type** *Check*

Returns *Check* object

#### 6.13.1.3.1.21 `pandera.checks.Check.__call__`

`Check.__call__(df_or_series, column=None)`

Validate pandas DataFrame or Series.

**Parameters**

- **df\_or\_series** (`Union[DataFrame, Series]`) – pandas DataFrame or Series to validate.
- **column** (`Optional[str]`) – for dataframe checks, apply the check function to this column.

**Return type** `CheckResult`

**Returns**

`CheckResult` tuple containing:

`check_output`: boolean scalar, `Series` or `DataFrame` indicating which elements passed the check.

`check_passed`: boolean scalar that indicating whether the check passed overall.

`checked_object`: the checked object itself. Depending on the options provided to the `Check`, this will be a pandas `Series`, `DataFrame`, or if the `groupby` option is specified, a `Dict[str, Series]` or `Dict[str, DataFrame]` where the keys are distinct groups.

`failure_cases`: subset of the `check_object` that failed.

#### 6.13.1.3.2 `pandera.hypotheses.Hypothesis`

**class** `pandera.hypotheses.Hypothesis(test, samples=None, groupby=None, relationship='equal', test_kwargs=None, relationship_kwargs=None, name=None, error=None, raise_warning=False)`

Special type of `Check` that defines hypothesis tests on data.

Perform a hypothesis test on a `Series` or `DataFrame`.

**Parameters**

- **test** (`Callable`) – The hypothesis test function. It should take one or more arrays as positional arguments and return a test statistic and a p-value. The arrays passed into the test function are determined by the `samples` argument.

- **samples** (`Union[str, List[str], None]`) – for *Column* or *SeriesSchema* hypotheses, this refers to the group keys in the *groupby* column(s) used to group the *Series* into a dict of *Series*. The *samples* column(s) are passed into the *test* function as positional arguments.

For *DataFrame*-level hypotheses, *samples* refers to a column or multiple columns to pass into the *test* function. The *samples* column(s) are passed into the *test* function as positional arguments.

- **groupby** (`Union[str, List[str], Callable, None]`) – If a string or list of strings is provided, then these columns are used to group the Column Series by *groupby*. If a callable is passed, the expected signature is `DataFrame -> DataFrameGroupby`. The function has access to the entire dataframe, but the `Column.name` is selected from this `DataFrameGroupby` object so that a `SeriesGroupBy` object is passed into the *hypothesis\_check* function.

Specifying this argument changes the *fn* signature to: `dict[str|tuple[str], Series] -> bool|pd.Series[bool]`

Where specific groups can be obtained from the input dict.

- **relationship** (`Union[str, Callable]`) – Represents what relationship conditions are imposed on the hypothesis test. A function or lambda function can be supplied.

Available built-in relationships are: “greater\_than”, “less\_than”, “not\_equal” or “equal”, where “equal” is the null hypothesis.

If callable, the input function signature should have the signature `(stat: float, pvalue: float, **kwargs)` where *stat* is the hypothesis test statistic, *pvalue* assesses statistical significance, and *\*\*kwargs* are other arguments supplied via the *\*\*relationship\_kwargs* argument.

Default is “equal” for the null hypothesis.

- **test\_kwargs** (`dict`) – Keyword arguments to be supplied to the test.
- **relationship\_kwargs** (`dict`) – Keyword arguments to be supplied to the relationship function. e.g. *alpha* could be used to specify a threshold in a t-test.
- **name** (`Optional[str]`) – optional name of hypothesis test
- **error** (`Optional[str]`) – error message to show
- **raise\_warning** (`bool`) – if True, raise a `UserWarning` and do not throw exception instead of raising a `SchemaError` for a specific check. This option should be used carefully in cases where a failing check is informational and shouldn’t stop execution of the program.

### Examples

Define a two-sample hypothesis test using `scipy`.

```
>>> import pandas as pd
>>> import pandera as pa
>>>
>>> from scipy import stats
>>>
>>> schema = pa.DataFrameSchema({
...     "height_in_feet": pa.Column(float, [
...         pa.Hypothesis(
...             test=stats.ttest_ind,
...             samples=["A", "B"],
...             groupby="group",
...             # assert that the mean height of group "A" is greater
```

(continues on next page)

```

...         # than that of group "B"
...         relationship=lambda stat, pvalue, alpha=0.1: (
...             stat > 0 and pvalue / 2 < alpha
...         ),
...         # set alpha criterion to 5%
...         relationship_kwargs={"alpha": 0.05}
...     )
... ],
... "group": pa.Column(str),
... })
>>> df = (
...     pd.DataFrame({
...         "height_in_feet": [8.1, 7, 5.2, 5.1, 4],
...         "group": ["A", "A", "B", "B", "B"]
...     })
... )
>>> schema.validate(df)[["height_in_feet", "group"]]
  height_in_feet group
0              8.1    A
1              7.0    A
2              5.2    B
3              5.1    B
4              4.0    B

```

See [here](#) for more usage details.

## Attributes

RELATIONSHIPS	Relationships available for built-in hypothesis tests.
is_one_sample_test	Return True if hypothesis is a one-sample test.
statistics	Get check statistics.
REGISTERED_CUSTOM_CHECKS	

## Methods

<code>__init__</code>	Perform a hypothesis test on a Series or DataFrame.
<code>one_sample_ttest</code>	Calculate a t-test for the mean of one sample.
<code>two_sample_ttest</code>	Calculate a t-test for the means of two samples.
<code>__call__</code>	Validate pandas DataFrame or Series.



### 6.13.1.3.2.1 pandera.hypotheses.Hypothesis.\_\_init\_\_

`Hypothesis.__init__(test, samples=None, groupby=None, relationship='equal', test_kwargs=None, relationship_kwargs=None, name=None, error=None, raise_warning=False)`

Perform a hypothesis test on a Series or DataFrame.

#### Parameters

- **test** (`Callable`) – The hypothesis test function. It should take one or more arrays as positional arguments and return a test statistic and a p-value. The arrays passed into the test function are determined by the `samples` argument.
- **samples** (`Union[str, List[str], None]`) – for `Column` or `SeriesSchema` hypotheses, this refers to the group keys in the `groupby` column(s) used to group the `Series` into a dict of `Series`. The `samples` column(s) are passed into the `test` function as positional arguments.

For `DataFrame`-level hypotheses, `samples` refers to a column or multiple columns to pass into the `test` function. The `samples` column(s) are passed into the `test` function as positional arguments.

- **groupby** (`Union[str, List[str], Callable, None]`) – If a string or list of strings is provided, then these columns are used to group the Column Series by `groupby`. If a callable is passed, the expected signature is `DataFrame -> DataFrameGroupby`. The function has access to the entire dataframe, but the `Column.name` is selected from this `DataFrameGroupby` object so that a `SeriesGroupBy` object is passed into the `hypothesis_check` function.

Specifying this argument changes the `fn` signature to: `dict[str|tuple[str], Series] -> bool|pd.Series[bool]`

Where specific groups can be obtained from the input dict.

- **relationship** (`Union[str, Callable]`) – Represents what relationship conditions are imposed on the hypothesis test. A function or lambda function can be supplied.

Available built-in relationships are: “greater\_than”, “less\_than”, “not\_equal” or “equal”, where “equal” is the null hypothesis.

If callable, the input function signature should have the signature `(stat: float, pvalue: float, **kwargs)` where `stat` is the hypothesis test statistic, `pvalue` assesses statistical significance, and `**kwargs` are other arguments supplied via the `**relationship_kwargs` argument.

Default is “equal” for the null hypothesis.

- **test\_kwargs** (`dict`) – Keyword arguments to be supplied to the test.
- **relationship\_kwargs** (`dict`) – Keyword arguments to be supplied to the relationship function. e.g. `alpha` could be used to specify a threshold in a t-test.
- **name** (`Optional[str]`) – optional name of hypothesis test
- **error** (`Optional[str]`) – error message to show
- **raise\_warning** (`bool`) – if True, raise a `UserWarning` and do not throw exception instead of raising a `SchemaError` for a specific check. This option should be used carefully in cases where a failing check is informational and shouldn’t stop execution of the program.

#### Examples

Define a two-sample hypothesis test using `scipy`.

```

>>> import pandas as pd
>>> import pandera as pa
>>>
>>> from scipy import stats
>>>
>>> schema = pa.DataFrameSchema({
...     "height_in_feet": pa.Column(float, [
...         pa.Hypothesis(
...             test=stats.ttest_ind,
...             samples=["A", "B"],
...             groupby="group",
...             # assert that the mean height of group "A" is greater
...             # than that of group "B"
...             relationship=lambda stat, pvalue, alpha=0.1: (
...                 stat > 0 and pvalue / 2 < alpha
...             ),
...             # set alpha criterion to 5%
...             relationship_kwargs={"alpha": 0.05}
...         )
...     ]),
...     "group": pa.Column(str),
... })
>>> df = (
...     pd.DataFrame({
...         "height_in_feet": [8.1, 7, 5.2, 5.1, 4],
...         "group": ["A", "A", "B", "B", "B"]
...     })
... )
>>> schema.validate(df)[["height_in_feet", "group"]]
  height_in_feet group
0             8.1    A
1             7.0    A
2             5.2    B
3             5.1    B
4             4.0    B

```

See [here](#) for more usage details.

### 6.13.1.3.2.2 pandera.hypotheses.Hypothesis.one\_sample\_ttest

**classmethod** `Hypothesis.one_sample_ttest` (*popmean*, *sample=None*, *groupby=None*, *relationship='equal'*, *alpha=0.01*, *raise\_warning=False*)

Calculate a t-test for the mean of one sample.

#### Parameters

- **sample** (`Optional[str]`) – The sample group to test. For *Column* and *SeriesSchema* hypotheses, this refers to the *groupby* level that is used to subset the *Column* being checked. For *DataFrameSchema* hypotheses, refers to column in the *DataFrame*.
- **groupby** (`Union[str, List[str], Callable, None]`) – If a string or list of strings is provided, then these columns are used to group the *Column Series* by *groupby*. If a callable is passed, the expected signature is `DataFrame -> DataFrameGroupby`. The function has access to the entire dataframe, but the `Column.name` is selected from this `DataFrameGroupby`

object so that a `SeriesGroupBy` object is passed into *fn*.

Specifying this argument changes the *fn* signature to: `dict[str|tuple[str], Series] -> bool|pd.Series[bool]`

Where specific groups can be obtained from the input dict.

- **popmean** (`float`) – population mean to compare *sample* to.
- **relationship** (`str`) – Represents what relationship conditions are imposed on the hypothesis test. Available relationships are: “greater\_than”, “less\_than”, “not\_equal” and “equal”. For example, *group1 greater\_than group2* specifies an alternative hypothesis that the mean of group1 is greater than group 2 relative to a null hypothesis that they are equal.
- **alpha** (`float`) – (Default value = 0.01) The significance level; the probability of rejecting the null hypothesis when it is true. For example, a significance level of 0.01 indicates a 1% risk of concluding that a difference exists when there is no actual difference.
- **raise\_warning** – if True, check raises `UserWarning` instead of `SchemaError` on validation.

### Example

If you want to compare one sample with a pre-defined mean:

```
>>> import pandas as pd
>>> import pandera as pa
>>>
>>>
>>> schema = pa.DataFrameSchema({
...     "height_in_feet": pa.Column(
...         float, [
...             pa.Hypothesis.one_sample_ttest(
...                 popmean=5,
...                 relationship="greater_than",
...                 alpha=0.1),
...         ]),
... })
>>> df = (
...     pd.DataFrame({
...         "height_in_feet": [8.1, 7, 6.5, 6.7, 5.1],
...     })
... )
>>> schema.validate(df)
height_in_feet
0            8.1
1            7.0
2            6.5
3            6.7
4            5.1
```

### 6.13.1.3.2.3 pandera.hypotheses.Hypothesis.two\_sample\_ttest

**classmethod** `Hypothesis.two_sample_ttest`(*sample1*, *sample2*, *groupby=None*, *relationship='equal'*, *alpha=0.01*, *equal\_var=True*, *nan\_policy='propagate'*, *raise\_warning=False*)

Calculate a t-test for the means of two samples.

Perform a two-sided test for the null hypothesis that 2 independent samples have identical average (expected) values. This test assumes that the populations have identical variances by default.

#### Parameters

- **sample1** (`str`) – The first sample group to test. For `Column` and `SeriesSchema` hypotheses, refers to the level in the `groupby` column. For `DataFrameSchema` hypotheses, refers to column in the `DataFrame`.
- **sample2** (`str`) – The second sample group to test. For `Column` and `SeriesSchema` hypotheses, refers to the level in the `groupby` column. For `DataFrameSchema` hypotheses, refers to column in the `DataFrame`.
- **groupby** (`Union[str, List[str], Callable, None]`) – If a string or list of strings is provided, then these columns are used to group the Column Series by `groupby`. If a callable is passed, the expected signature is `DataFrame -> DataFrameGroupby`. The function has access to the entire dataframe, but the `Column.name` is selected from this `DataFrameGroupby` object so that a `SeriesGroupBy` object is passed into `fn`.

Specifying this argument changes the `fn` signature to: `dict[str|tuple[str], Series] -> bool|pd.Series[bool]`

Where specific groups can be obtained from the input dict.

- **relationship** (`str`) – Represents what relationship conditions are imposed on the hypothesis test. Available relationships are: “greater\_than”, “less\_than”, “not\_equal”, and “equal”. For example, `group1 greater_than group2` specifies an alternative hypothesis that the mean of group1 is greater than group 2 relative to a null hypothesis that they are equal.
- **alpha** – (Default value = 0.01) The significance level; the probability of rejecting the null hypothesis when it is true. For example, a significance level of 0.01 indicates a 1% risk of concluding that a difference exists when there is no actual difference.
- **equal\_var** – (Default value = True) If True (default), perform a standard independent 2 sample test that assumes equal population variances. If False, perform Welch’s t-test, which does not assume equal population variance
- **nan\_policy** – Defines how to handle when input returns nan, one of { ‘propagate’, ‘raise’, ‘omit’ }, (Default value = ‘propagate’). For more details see: [https://docs.scipy.org/doc/scipy/reference/generated/scipy.stats.ttest\\_ind.html](https://docs.scipy.org/doc/scipy/reference/generated/scipy.stats.ttest_ind.html)
- **raise\_warning** – if True, check raises `UserWarning` instead of `SchemaError` on validation.

#### Example

The the built-in class method to do a two-sample t-test.

```
>>> import pandera as pa
>>>
>>>
>>> schema = pa.DataFrameSchema({
...     "height_in_feet": pa.Column(
```

(continues on next page)

(continued from previous page)

```

...     float, [
...         pa.Hypothesis.two_sample_ttest(
...             sample1="A",
...             sample2="B",
...             groupby="group",
...             relationship="greater_than",
...             alpha=0.05,
...             equal_var=True),
...     ]),
...     "group": pa.Column(str)
... })
>>> df = (
...     pd.DataFrame({
...         "height_in_feet": [8.1, 7, 5.2, 5.1, 4],
...         "group": ["A", "A", "B", "B", "B"]
...     })
... )
>>> schema.validate(df)[["height_in_feet", "group"]]
  height_in_feet  group
0             8.1     A
1             7.0     A
2             5.2     B
3             5.1     B
4             4.0     B

```

#### 6.13.1.3.2.4 pandera.hypotheses.Hypothesis.\_\_call\_\_

`Hypothesis.__call__(df_or_series, column=None)`

Validate pandas DataFrame or Series.

##### Parameters

- **df\_or\_series** (`Union[DataFrame, Series]`) – pandas DataFrame or Series to validate.
- **column** (`Optional[str]`) – for dataframe checks, apply the check function to this column.

**Return type** `CheckResult`

##### Returns

CheckResult tuple containing:

`check_output`: boolean scalar, Series or DataFrame indicating which elements passed the check.

`check_passed`: boolean scalar that indicating whether the check passed overall.

`checked_object`: the checked object itself. Depending on the options provided to the Check, this will be a pandas Series, DataFrame, or if the `groupby` option is specified, a `Dict[str, Series]` or `Dict[str, DataFrame]` where the keys are distinct groups.

`failure_cases`: subset of the `check_object` that failed.

## 6.13.2 Data Types

### 6.13.2.1 Library-agnostic dtypes

<code>pandera.dtypes.DataType</code>	Base class of all Pandera data types.
<code>pandera.dtypes.Bool</code>	Semantic representation of a boolean data type.
<code>pandera.dtypes.Timestamp</code>	Semantic representation of a timestamp data type.
<code>pandera.dtypes.DateTime</code>	alias of <code>pandera.dtypes.Timestamp</code>
<code>pandera.dtypes.Timedelta</code>	Semantic representation of a delta time data type.
<code>pandera.dtypes.Category</code>	Semantic representation of a categorical data type.
<code>pandera.dtypes.Float</code>	Semantic representation of a floating data type.
<code>pandera.dtypes.Float16</code>	Semantic representation of a floating data type stored in 16 bits.
<code>pandera.dtypes.Float32</code>	Semantic representation of a floating data type stored in 32 bits.
<code>pandera.dtypes.Float64</code>	Semantic representation of a floating data type stored in 64 bits.
<code>pandera.dtypes.Float128</code>	Semantic representation of a floating data type stored in 128 bits.
<code>pandera.dtypes.Int</code>	Semantic representation of an integer data type.
<code>pandera.dtypes.Int8</code>	Semantic representation of an integer data type stored in 8 bits.
<code>pandera.dtypes.Int16</code>	Semantic representation of an integer data type stored in 16 bits.
<code>pandera.dtypes.Int32</code>	Semantic representation of an integer data type stored in 32 bits.
<code>pandera.dtypes.Int64</code>	Semantic representation of an integer data type stored in 64 bits.
<code>pandera.dtypes.UInt</code>	Semantic representation of an unsigned integer data type.
<code>pandera.dtypes.UInt8</code>	Semantic representation of an unsigned integer data type stored in 8 bits.
<code>pandera.dtypes.UInt16</code>	Semantic representation of an unsigned integer data type stored in 16 bits.
<code>pandera.dtypes.UInt32</code>	Semantic representation of an unsigned integer data type stored in 32 bits.
<code>pandera.dtypes.UInt64</code>	Semantic representation of an unsigned integer data type stored in 64 bits.
<code>pandera.dtypes.Complex</code>	Semantic representation of a complex number data type.
<code>pandera.dtypes.Complex64</code>	Semantic representation of a complex number data type stored in 64 bits.
<code>pandera.dtypes.Complex128</code>	Semantic representation of a complex number data type stored in 128 bits.
<code>pandera.dtypes.Complex256</code>	Semantic representation of a complex number data type stored in 256 bits.
<code>pandera.dtypes.String</code>	Semantic representation of a string data type.

### 6.13.2.1.1 pandera.dtypes.DataType

**class** pandera.dtypes.DataType

Base class of all Pandera data types.

#### Attributes

continuous	Whether the number data type is continuous.
------------	---

#### Methods

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

#### 6.13.2.1.1.1 pandera.dtypes.DataType.\_\_init\_\_

DataType.**\_\_init\_\_**()

#### 6.13.2.1.1.2 pandera.dtypes.DataType.check

DataType.**check**(*pandera\_dtype*)

Check that pandera *DataType* are equivalent.

**Return type** bool

#### 6.13.2.1.1.3 pandera.dtypes.DataType.coerce

DataType.**coerce**(*data\_container*)

Coerce data container to the data type.

#### 6.13.2.1.1.4 pandera.dtypes.DataType.\_\_call\_\_

DataType.**\_\_call\_\_**(*data\_container*)

Coerce data container to the data type.

### 6.13.2.1.2 pandera.dtypes.Bool

**class** pandera.dtypes.Bool

Semantic representation of a boolean data type.

#### Attributes

continuous	Whether the number data type is continuous.
exact	Whether the data type is an exact representation of a number.

#### Methods

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

#### 6.13.2.1.2.1 pandera.dtypes.Bool.\_\_init\_\_

Bool.**\_\_init\_\_**()

#### 6.13.2.1.2.2 pandera.dtypes.Bool.check

Bool.**check**(*pandera\_dtype*)

Check that pandera *DataType* are equivalent.

**Return type** bool

#### 6.13.2.1.2.3 pandera.dtypes.Bool.coerce

Bool.**coerce**(*data\_container*)

Coerce data container to the data type.

#### 6.13.2.1.2.4 pandera.dtypes.Bool.\_\_call\_\_

Bool.**\_\_call\_\_**(*data\_container*)

Coerce data container to the data type.



### 6.13.2.1.3 pandera.dtypes.Timestamp

**class** `pandera.dtypes.Timestamp`

Semantic representation of a timestamp data type.

#### Attributes

<code>continuous</code>	Whether the number data type is continuous.
-------------------------	---

#### Methods

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

#### 6.13.2.1.3.1 pandera.dtypes.Timestamp.\_\_init\_\_

`Timestamp.__init__()`

#### 6.13.2.1.3.2 pandera.dtypes.Timestamp.check

`Timestamp.check(pandera_dtype)`

Check that pandera *DataType* are equivalent.

**Return type** `bool`

#### 6.13.2.1.3.3 pandera.dtypes.Timestamp.coerce

`Timestamp.coerce(data_container)`

Coerce data container to the data type.

#### 6.13.2.1.3.4 pandera.dtypes.Timestamp.\_\_call\_\_

`Timestamp.__call__(data_container)`

Coerce data container to the data type.

#### 6.13.2.1.4 pandera.dtypes.DateTime

`pandera.dtypes.DateTime`

alias of `pandera.dtypes.Timestamp`

#### 6.13.2.1.5 pandera.dtypes.Timedelta

**class** `pandera.dtypes.Timedelta`

Semantic representation of a delta time data type.

##### Attributes

---

<code>continuous</code>	Whether the number data type is continuous.
-------------------------	---

---

##### Methods

---

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

---

##### 6.13.2.1.5.1 pandera.dtypes.Timedelta.\_\_init\_\_

`Timedelta.__init__()`

##### 6.13.2.1.5.2 pandera.dtypes.Timedelta.check

`Timedelta.check(pandera_dtype)`

Check that pandera *DataType* are equivalent.

**Return type** `bool`

##### 6.13.2.1.5.3 pandera.dtypes.Timedelta.coerce

`Timedelta.coerce(data_container)`

Coerce data container to the data type.

#### 6.13.2.1.5.4 `pandera.dtypes.Timedelta.__call__`

`Timedelta.__call__(data_container)`  
Coerce data container to the data type.

#### 6.13.2.1.6 `pandera.dtypes.Category`

**class** `pandera.dtypes.Category`(*categories=None, ordered=False*)  
Semantic representation of a categorical data type.

##### Attributes

<code>categories</code>	
<code>continuous</code>	Whether the number data type is continuous.
<code>ordered</code>	

##### Methods

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

##### 6.13.2.1.6.1 `pandera.dtypes.Category.__init__`

`Category.__init__(categories=None, ordered=False)`

##### 6.13.2.1.6.2 `pandera.dtypes.Category.check`

`Category.check(pandera_dtype)`  
Check that pandera *DataType* are equivalent.

**Return type** `bool`

#### 6.13.2.1.6.3 pandera.dtypes.Category.coerce

`Category.coerce(data_container)`  
Coerce data container to the data type.

#### 6.13.2.1.6.4 pandera.dtypes.Category.\_\_call\_\_

`Category.__call__(data_container)`  
Coerce data container to the data type.

#### 6.13.2.1.7 pandera.dtypes.Float

**class** `pandera.dtypes.Float`  
Semantic representation of a floating data type.

##### Attributes

<code>bit_width</code>	Number of bits used by the machine representation.
<code>continuous</code>	Whether the number data type is continuous.
<code>exact</code>	Whether the data type is an exact representation of a number.

##### Methods

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

#### 6.13.2.1.7.1 pandera.dtypes.Float.\_\_init\_\_

`Float.__init__()`

#### 6.13.2.1.7.2 pandera.dtypes.Float.check

`Float.check(pandera_dtype)`  
Check that pandera *DataType* are equivalent.

**Return type** `bool`

### 6.13.2.1.7.3 `pandera.dtypes.Float.coerce`

`Float.coerce(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.7.4 `pandera.dtypes.Float.__call__`

`Float.__call__(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.8 `pandera.dtypes.Float16`

**class** `pandera.dtypes.Float16`  
Semantic representation of a floating data type stored in 16 bits.

#### Attributes

<code>bit_width</code>	Number of bits used by the machine representation.
<code>continuous</code>	Whether the number data type is continuous.
<code>exact</code>	Whether the data type is an exact representation of a number.

#### Methods

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

#### 6.13.2.1.8.1 `pandera.dtypes.Float16.__init__`

`Float16.__init__()`

#### 6.13.2.1.8.2 `pandera.dtypes.Float16.check`

`Float16.check(pandera_dtype)`  
Check that pandera *DataType* are equivalent.

**Return type** `bool`

### 6.13.2.1.8.3 `pandera.dtypes.Float16.coerce`

`Float16.coerce(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.8.4 `pandera.dtypes.Float16.__call__`

`Float16.__call__(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.9 `pandera.dtypes.Float32`

**class** `pandera.dtypes.Float32`  
Semantic representation of a floating data type stored in 32 bits.

#### Attributes

<code>bit_width</code>	Number of bits used by the machine representation.
<code>continuous</code>	Whether the number data type is continuous.
<code>exact</code>	Whether the data type is an exact representation of a number.

#### Methods

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

### 6.13.2.1.9.1 `pandera.dtypes.Float32.__init__`

`Float32.__init__()`

### 6.13.2.1.9.2 `pandera.dtypes.Float32.check`

`Float32.check(pandera_dtype)`  
Check that pandera *DataType* are equivalent.

**Return type** `bool`

### 6.13.2.1.9.3 pandera.dtypes.Float32.coerce

`Float32.coerce(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.9.4 pandera.dtypes.Float32.\_\_call\_\_

`Float32.__call__(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.10 pandera.dtypes.Float64

**class** `pandera.dtypes.Float64`  
Semantic representation of a floating data type stored in 64 bits.

#### Attributes

<code>bit_width</code>	Number of bits used by the machine representation.
<code>continuous</code>	Whether the number data type is continuous.
<code>exact</code>	Whether the data type is an exact representation of a number.

#### Methods

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

#### 6.13.2.1.10.1 pandera.dtypes.Float64.\_\_init\_\_

`Float64.__init__()`

#### 6.13.2.1.10.2 pandera.dtypes.Float64.check

`Float64.check(pandera_dtype)`  
Check that pandera *DataType* are equivalent.

**Return type** `bool`

### 6.13.2.1.10.3 pandera.dtypes.Float64.coerce

`Float64.coerce(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.10.4 pandera.dtypes.Float64.\_\_call\_\_

`Float64.__call__(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.11 pandera.dtypes.Float128

**class** `pandera.dtypes.Float128`  
Semantic representation of a floating data type stored in 128 bits.

#### Attributes

<code>bit_width</code>	Number of bits used by the machine representation.
<code>continuous</code>	Whether the number data type is continuous.
<code>exact</code>	Whether the data type is an exact representation of a number.

#### Methods

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

### 6.13.2.1.11.1 pandera.dtypes.Float128.\_\_init\_\_

`Float128.__init__()`

### 6.13.2.1.11.2 pandera.dtypes.Float128.check

`Float128.check(pandera_dtype)`  
Check that pandera *DataType* are equivalent.

**Return type** `bool`



### 6.13.2.1.11.3 pandera.dtypes.Float128.coerce

`Float128.coerce(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.11.4 pandera.dtypes.Float128.\_\_call\_\_

`Float128.__call__(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.12 pandera.dtypes.Int

**class** `pandera.dtypes.Int`  
Semantic representation of an integer data type.

#### Attributes

<code>bit_width</code>	Number of bits used by the machine representation.
<code>continuous</code>	Whether the number data type is continuous.
<code>exact</code>	Whether the data type is an exact representation of a number.
<code>signed</code>	Whether the integer data type is signed.

#### Methods

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

#### 6.13.2.1.12.1 pandera.dtypes.Int.\_\_init\_\_

`Int.__init__()`

#### 6.13.2.1.12.2 pandera.dtypes.Int.check

`Int.check(pandera_dtype)`  
Check that pandera *DataType* are equivalent.

**Return type** `bool`

### 6.13.2.1.12.3 pandera.dtypes.Int.coerce

`Int.coerce(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.12.4 pandera.dtypes.Int.\_\_call\_\_

`Int.__call__(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.13 pandera.dtypes.Int8

**class** `pandera.dtypes.Int8`  
Semantic representation of an integer data type stored in 8 bits.

#### Attributes

<code>bit_width</code>	Number of bits used by the machine representation.
<code>continuous</code>	Whether the number data type is continuous.
<code>exact</code>	Whether the data type is an exact representation of a number.
<code>signed</code>	Whether the integer data type is signed.

#### Methods

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

### 6.13.2.1.13.1 pandera.dtypes.Int8.\_\_init\_\_

`Int8.__init__()`

### 6.13.2.1.13.2 pandera.dtypes.Int8.check

`Int8.check(pandera_dtype)`  
Check that pandera *DataType* are equivalent.

**Return type** `bool`

### 6.13.2.1.13.3 pandera.dtypes.Int8.coerce

`Int8.coerce(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.13.4 pandera.dtypes.Int8.\_\_call\_\_

`Int8.__call__(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.14 pandera.dtypes.Int16

**class** `pandera.dtypes.Int16`  
Semantic representation of an integer data type stored in 16 bits.

#### Attributes

<code>bit_width</code>	Number of bits used by the machine representation.
<code>continuous</code>	Whether the number data type is continuous.
<code>exact</code>	Whether the data type is an exact representation of a number.
<code>signed</code>	Whether the integer data type is signed.

#### Methods

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

#### 6.13.2.1.14.1 pandera.dtypes.Int16.\_\_init\_\_

`Int16.__init__()`

#### 6.13.2.1.14.2 pandera.dtypes.Int16.check

`Int16.check(pandera_dtype)`  
Check that pandera *DataType* are equivalent.

**Return type** `bool`

### 6.13.2.1.14.3 pandera.dtypes.Int16.coerce

`Int16.coerce(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.14.4 pandera.dtypes.Int16.\_\_call\_\_

`Int16.__call__(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.15 pandera.dtypes.Int32

**class** `pandera.dtypes.Int32`  
Semantic representation of an integer data type stored in 32 bits.

#### Attributes

<code>bit_width</code>	Number of bits used by the machine representation.
<code>continuous</code>	Whether the number data type is continuous.
<code>exact</code>	Whether the data type is an exact representation of a number.
<code>signed</code>	Whether the integer data type is signed.

#### Methods

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

### 6.13.2.1.15.1 pandera.dtypes.Int32.\_\_init\_\_

`Int32.__init__()`

### 6.13.2.1.15.2 pandera.dtypes.Int32.check

`Int32.check(pandera_dtype)`  
Check that pandera *DataType* are equivalent.

**Return type** `bool`

### 6.13.2.1.15.3 `pandera.dtypes.Int32.coerce`

`Int32.coerce(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.15.4 `pandera.dtypes.Int32.__call__`

`Int32.__call__(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.16 `pandera.dtypes.Int64`

**class** `pandera.dtypes.Int64`

Semantic representation of an integer data type stored in 64 bits.

#### Attributes

<code>bit_width</code>	Number of bits used by the machine representation.
<code>continuous</code>	Whether the number data type is continuous.
<code>exact</code>	Whether the data type is an exact representation of a number.
<code>signed</code>	Whether the integer data type is signed.

#### Methods

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

#### 6.13.2.1.16.1 `pandera.dtypes.Int64.__init__`

`Int64.__init__()`

#### 6.13.2.1.16.2 `pandera.dtypes.Int64.check`

`Int64.check(pandera_dtype)`  
Check that pandera *DataType* are equivalent.

**Return type** `bool`

### 6.13.2.1.16.3 pandera.dtypes.Int64.coerce

`Int64.coerce(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.16.4 pandera.dtypes.Int64.\_\_call\_\_

`Int64.__call__(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.17 pandera.dtypes.UInt

**class** `pandera.dtypes.UInt`  
Semantic representation of an unsigned integer data type.

#### Attributes

<code>bit_width</code>	Number of bits used by the machine representation.
<code>continuous</code>	Whether the number data type is continuous.
<code>exact</code>	Whether the data type is an exact representation of a number.
<code>signed</code>	Whether the integer data type is signed.

#### Methods

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

### 6.13.2.1.17.1 pandera.dtypes.UInt.\_\_init\_\_

`UInt.__init__()`

### 6.13.2.1.17.2 pandera.dtypes.UInt.check

`UInt.check(pandera_dtype)`  
Check that pandera *DataType* are equivalent.

**Return type** `bool`

### 6.13.2.1.17.3 pandera.dtypes.UInt.coerce

`UInt.coerce(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.17.4 pandera.dtypes.UInt.\_\_call\_\_

`UInt.__call__(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.18 pandera.dtypes.UInt8

**class** `pandera.dtypes.UInt8`

Semantic representation of an unsigned integer data type stored in 8 bits.

#### Attributes

<code>bit_width</code>	Number of bits used by the machine representation.
<code>continuous</code>	Whether the number data type is continuous.
<code>exact</code>	Whether the data type is an exact representation of a number.
<code>signed</code>	Whether the integer data type is signed.

#### Methods

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

#### 6.13.2.1.18.1 pandera.dtypes.UInt8.\_\_init\_\_

`UInt8.__init__()`

#### 6.13.2.1.18.2 pandera.dtypes.UInt8.check

`UInt8.check(pandera_dtype)`  
Check that pandera *DataType* are equivalent.

**Return type** `bool`

### 6.13.2.1.18.3 pandera.dtypes.UInt8.coerce

`UInt8.coerce(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.18.4 pandera.dtypes.UInt8.\_\_call\_\_

`UInt8.__call__(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.19 pandera.dtypes.UInt16

**class** `pandera.dtypes.UInt16`

Semantic representation of an unsigned integer data type stored in 16 bits.

#### Attributes

<code>bit_width</code>	Number of bits used by the machine representation.
<code>continuous</code>	Whether the number data type is continuous.
<code>exact</code>	Whether the data type is an exact representation of a number.
<code>signed</code>	Whether the integer data type is signed.

#### Methods

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

### 6.13.2.1.19.1 pandera.dtypes.UInt16.\_\_init\_\_

`UInt16.__init__()`

### 6.13.2.1.19.2 pandera.dtypes.UInt16.check

`UInt16.check(pandera_dtype)`  
Check that pandera *DataType* are equivalent.

**Return type** `bool`



### 6.13.2.1.19.3 pandera.dtypes.UInt16.coerce

`UInt16.coerce(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.19.4 pandera.dtypes.UInt16.\_\_call\_\_

`UInt16.__call__(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.20 pandera.dtypes.UInt32

**class** `pandera.dtypes.UInt32`

Semantic representation of an unsigned integer data type stored in 32 bits.

#### Attributes

<code>bit_width</code>	Number of bits used by the machine representation.
<code>continuous</code>	Whether the number data type is continuous.
<code>exact</code>	Whether the data type is an exact representation of a number.
<code>signed</code>	Whether the integer data type is signed.

#### Methods

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

#### 6.13.2.1.20.1 pandera.dtypes.UInt32.\_\_init\_\_

`UInt32.__init__()`

#### 6.13.2.1.20.2 pandera.dtypes.UInt32.check

`UInt32.check(pandera_dtype)`  
Check that pandera *DataType* are equivalent.

**Return type** `bool`

### 6.13.2.1.20.3 pandera.dtypes.UInt32.coerce

`UInt32.coerce(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.20.4 pandera.dtypes.UInt32.\_\_call\_\_

`UInt32.__call__(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.21 pandera.dtypes.UInt64

**class** `pandera.dtypes.UInt64`

Semantic representation of an unsigned integer data type stored in 64 bits.

#### Attributes

<code>bit_width</code>	Number of bits used by the machine representation.
<code>continuous</code>	Whether the number data type is continuous.
<code>exact</code>	Whether the data type is an exact representation of a number.
<code>signed</code>	Whether the integer data type is signed.

#### Methods

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

### 6.13.2.1.21.1 pandera.dtypes.UInt64.\_\_init\_\_

`UInt64.__init__()`

### 6.13.2.1.21.2 pandera.dtypes.UInt64.check

`UInt64.check(pandera_dtype)`  
Check that pandera *DataType* are equivalent.

**Return type** `bool`

### 6.13.2.1.21.3 pandera.dtypes.UInt64.coerce

`UInt64.coerce(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.21.4 pandera.dtypes.UInt64.\_\_call\_\_

`UInt64.__call__(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.22 pandera.dtypes.Complex

**class** `pandera.dtypes.Complex`  
Semantic representation of a complex number data type.

#### Attributes

<code>bit_width</code>	Number of bits used by the machine representation.
<code>continuous</code>	Whether the number data type is continuous.
<code>exact</code>	Whether the data type is an exact representation of a number.

#### Methods

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

#### 6.13.2.1.22.1 pandera.dtypes.Complex.\_\_init\_\_

`Complex.__init__()`

#### 6.13.2.1.22.2 pandera.dtypes.Complex.check

`Complex.check(pandera_dtype)`  
Check that pandera *DataType* are equivalent.

**Return type** `bool`

### 6.13.2.1.22.3 pandera.dtypes.Complex.coerce

`Complex.coerce(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.22.4 pandera.dtypes.Complex.\_\_call\_\_

`Complex.__call__(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.23 pandera.dtypes.Complex64

**class** `pandera.dtypes.Complex64`

Semantic representation of a complex number data type stored in 64 bits.

#### Attributes

<code>bit_width</code>	Number of bits used by the machine representation.
<code>continuous</code>	Whether the number data type is continuous.
<code>exact</code>	Whether the data type is an exact representation of a number.

#### Methods

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

### 6.13.2.1.23.1 pandera.dtypes.Complex64.\_\_init\_\_

`Complex64.__init__()`

### 6.13.2.1.23.2 pandera.dtypes.Complex64.check

`Complex64.check(pandera_dtype)`  
Check that pandera *DataType* are equivalent.

**Return type** `bool`

### 6.13.2.1.23.3 pandera.dtypes.Complex64.coerce

`Complex64.coerce(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.23.4 pandera.dtypes.Complex64.\_\_call\_\_

`Complex64.__call__(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.24 pandera.dtypes.Complex128

**class** `pandera.dtypes.Complex128`

Semantic representation of a complex number data type stored in 128 bits.

#### Attributes

<code>bit_width</code>	Number of bits used by the machine representation.
<code>continuous</code>	Whether the number data type is continuous.
<code>exact</code>	Whether the data type is an exact representation of a number.

#### Methods

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

#### 6.13.2.1.24.1 pandera.dtypes.Complex128.\_\_init\_\_

`Complex128.__init__()`

#### 6.13.2.1.24.2 pandera.dtypes.Complex128.check

`Complex128.check(pandera_dtype)`  
Check that pandera *DataType* are equivalent.

**Return type** `bool`

**6.13.2.1.24.3 pandera.dtypes.Complex128.coerce**

`Complex128.coerce(data_container)`  
Coerce data container to the data type.

**6.13.2.1.24.4 pandera.dtypes.Complex128.\_\_call\_\_**

`Complex128.__call__(data_container)`  
Coerce data container to the data type.

**6.13.2.1.25 pandera.dtypes.Complex256**

**class** `pandera.dtypes.Complex256`

Semantic representation of a complex number data type stored in 256 bits.

**Attributes**

<code>bit_width</code>	Number of bits used by the machine representation.
<code>continuous</code>	Whether the number data type is continuous.
<code>exact</code>	Whether the data type is an exact representation of a number.

**Methods**

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

**6.13.2.1.25.1 pandera.dtypes.Complex256.\_\_init\_\_**

`Complex256.__init__()`

**6.13.2.1.25.2 pandera.dtypes.Complex256.check**

`Complex256.check(pandera_dtype)`  
Check that pandera *DataType* are equivalent.

**Return type** `bool`

### 6.13.2.1.25.3 `pandera.dtypes.Complex256.coerce`

`Complex256.coerce(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.25.4 `pandera.dtypes.Complex256.__call__`

`Complex256.__call__(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.26 `pandera.dtypes.String`

**class** `pandera.dtypes.String`  
Semantic representation of a string data type.

#### Attributes

<code>continuous</code>	Whether the number data type is continuous.
-------------------------	---

#### Methods

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

#### 6.13.2.1.26.1 `pandera.dtypes.String.__init__`

`String.__init__()`

#### 6.13.2.1.26.2 `pandera.dtypes.String.check`

`String.check(pandera_dtype)`  
Check that pandera *DataType* are equivalent.

**Return type** `bool`

### 6.13.2.1.26.3 `pandera.dtypes.String.coerce`

`String.coerce(data_container)`  
Coerce data container to the data type.

### 6.13.2.1.26.4 `pandera.dtypes.String.__call__`

`String.__call__(data_container)`  
Coerce data container to the data type.

## 6.13.2.2 Pandas-specific Dtypes

Listed here for compatibility with pandera versions < 0.7. Passing native pandas dtypes to pandera components is preferred.

<code>pandera.engines.pandas_engine.BOOL</code>	Semantic representation of a <code>pandas.BooleanDtype</code> .
<code>pandera.engines.pandas_engine.INT8</code>	Semantic representation of a <code>pandas.Int8Dtype</code> .
<code>pandera.engines.pandas_engine.INT16</code>	Semantic representation of a <code>pandas.Int16Dtype</code> .
<code>pandera.engines.pandas_engine.INT32</code>	Semantic representation of a <code>pandas.Int32Dtype</code> .
<code>pandera.engines.pandas_engine.INT64</code>	Semantic representation of a <code>pandas.Int64Dtype</code> .
<code>pandera.engines.pandas_engine.UINT8</code>	Semantic representation of a <code>pandas.UInt8Dtype</code> .
<code>pandera.engines.pandas_engine.UINT16</code>	Semantic representation of a <code>pandas.UInt16Dtype</code> .
<code>pandera.engines.pandas_engine.UINT32</code>	Semantic representation of a <code>pandas.UInt32Dtype</code> .
<code>pandera.engines.pandas_engine.UINT64</code>	Semantic representation of a <code>pandas.UInt64Dtype</code> .
<code>pandera.engines.pandas_engine.STRING</code>	Semantic representation of a <code>pandas.StringDtype</code> .
<code>pandera.engines.numpy_engine.Object</code>	Semantic representation of a <code>numpy.object_</code> .

### 6.13.2.2.1 `pandera.engines.pandas_engine.BOOL`

`class pandera.engines.pandas_engine.BOOL`  
Semantic representation of a `pandas.BooleanDtype`.

#### Attributes

<code>continuous</code>	Whether the number data type is continuous.
<code>exact</code>	Whether the data type is an exact representation of a number.
<code>type</code>	Native pandas dtype boxed by the data type.



## Methods

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

### 6.13.2.2.1.1 pandera.engines.pandas\_engine.BOOL.\_\_init\_\_

`BOOL.__init__()`

### 6.13.2.2.1.2 pandera.engines.pandas\_engine.BOOL.check

`BOOL.check(pandera_dtype)`  
Check that pandera *DataType* are equivalent.

**Return type** `bool`

### 6.13.2.2.1.3 pandera.engines.pandas\_engine.BOOL.coerce

`BOOL.coerce(data_container)`  
Coerce data container to the data type.

**Return type** `Union[Series, Index, DataFrame]`

### 6.13.2.2.1.4 pandera.engines.pandas\_engine.BOOL.\_\_call\_\_

`BOOL.__call__(data_container)`  
Coerce data container to the data type.

### 6.13.2.2.2 pandera.engines.pandas\_engine.INT8

**class** `pandera.engines.pandas_engine.INT8`  
Semantic representation of a `pandas.Int8Dtype`.

## Attributes

<code>bit_width</code>	Number of bits used by the machine representation.
<code>continuous</code>	Whether the number data type is continuous.
<code>exact</code>	Whether the data type is an exact representation of a number.
<code>signed</code>	Whether the integer data type is signed.
<code>type</code>	Native pandas dtype boxed by the data type.

## Methods

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

### 6.13.2.2.2.1 pandera.engines.pandas\_engine.INT8.\_\_init\_\_

`INT8.__init__()`

### 6.13.2.2.2.2 pandera.engines.pandas\_engine.INT8.check

`INT8.check(pandera_dtype)`  
Check that pandera *DataType* are equivalent.

**Return type** `bool`

### 6.13.2.2.2.3 pandera.engines.pandas\_engine.INT8.coerce

`INT8.coerce(data_container)`  
Coerce data container to the data type.

**Return type** `Union[Series, Index, DataFrame]`

### 6.13.2.2.2.4 pandera.engines.pandas\_engine.INT8.\_\_call\_\_

`INT8.__call__(data_container)`  
Coerce data container to the data type.

### 6.13.2.2.3 pandera.engines.pandas\_engine.INT16

**class** `pandera.engines.pandas_engine.INT16`  
Semantic representation of a `pandas.Int16Dtype`.

## Attributes

<code>bit_width</code>	Number of bits used by the machine representation.
<code>continuous</code>	Whether the number data type is continuous.
<code>exact</code>	Whether the data type is an exact representation of a number.
<code>signed</code>	Whether the integer data type is signed.
<code>type</code>	Native pandas dtype boxed by the data type.

## Methods

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

### 6.13.2.2.3.1 pandera.engines.pandas\_engine.INT16.\_\_init\_\_

`INT16.__init__()`

### 6.13.2.2.3.2 pandera.engines.pandas\_engine.INT16.check

`INT16.check(pandera_dtype)`

Check that pandera *DataType* are equivalent.

**Return type** `bool`

### 6.13.2.2.3.3 pandera.engines.pandas\_engine.INT16.coerce

`INT16.coerce(data_container)`

Coerce data container to the data type.

**Return type** `Union[Series, Index, DataFrame]`

### 6.13.2.2.3.4 pandera.engines.pandas\_engine.INT16.\_\_call\_\_

`INT16.__call__(data_container)`

Coerce data container to the data type.

### 6.13.2.2.4 pandera.engines.pandas\_engine.INT32

**class** `pandera.engines.pandas_engine.INT32`

Semantic representation of a `pandas.Int32Dtype`.

## Attributes

<code>bit_width</code>	Number of bits used by the machine representation.
<code>continuous</code>	Whether the number data type is continuous.
<code>exact</code>	Whether the data type is an exact representation of a number.
<code>signed</code>	Whether the integer data type is signed.
<code>type</code>	Native pandas dtype boxed by the data type.

## Methods

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

### 6.13.2.2.4.1 pandera.engines.pandas\_engine.INT32.\_\_init\_\_

`INT32.__init__()`

### 6.13.2.2.4.2 pandera.engines.pandas\_engine.INT32.check

`INT32.check(pandera_dtype)`

Check that pandera *DataType* are equivalent.

**Return type** `bool`

### 6.13.2.2.4.3 pandera.engines.pandas\_engine.INT32.coerce

`INT32.coerce(data_container)`

Coerce data container to the data type.

**Return type** `Union[Series, Index, DataFrame]`

### 6.13.2.2.4.4 pandera.engines.pandas\_engine.INT32.\_\_call\_\_

`INT32.__call__(data_container)`

Coerce data container to the data type.

### 6.13.2.2.5 pandera.engines.pandas\_engine.INT64

**class** `pandera.engines.pandas_engine.INT64`

Semantic representation of a `pandas.Int64Dtype`.

## Attributes

<code>bit_width</code>	Number of bits used by the machine representation.
<code>continuous</code>	Whether the number data type is continuous.
<code>exact</code>	Whether the data type is an exact representation of a number.
<code>signed</code>	Whether the integer data type is signed.
<code>type</code>	Native pandas dtype boxed by the data type.

## Methods

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

### 6.13.2.2.5.1 pandera.engines.pandas\_engine.INT64.\_\_init\_\_

INT64.`__init__`()

### 6.13.2.2.5.2 pandera.engines.pandas\_engine.INT64.check

INT64.`check`(*pandera\_dtype*)

Check that pandera *DataType* are equivalent.

**Return type** `bool`

### 6.13.2.2.5.3 pandera.engines.pandas\_engine.INT64.coerce

INT64.`coerce`(*data\_container*)

Coerce data container to the data type.

**Return type** `Union[Series, Index, DataFrame]`

### 6.13.2.2.5.4 pandera.engines.pandas\_engine.INT64.\_\_call\_\_

INT64.`__call__`(*data\_container*)

Coerce data container to the data type.

### 6.13.2.2.6 pandera.engines.pandas\_engine.UINT8

**class** `pandera.engines.pandas_engine.UINT8`

Semantic representation of a `pandas.UInt8Dtype`.

## Attributes

<code>bit_width</code>	Number of bits used by the machine representation.
<code>continuous</code>	Whether the number data type is continuous.
<code>exact</code>	Whether the data type is an exact representation of a number.
<code>signed</code>	Whether the integer data type is signed.
<code>type</code>	Native pandas dtype boxed by the data type.

## Methods

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

### 6.13.2.2.6.1 pandera.engines.pandas\_engine.UINT8.\_\_init\_\_

`UINT8.__init__()`

### 6.13.2.2.6.2 pandera.engines.pandas\_engine.UINT8.check

`UINT8.check(pandera_dtype)`

Check that pandera *DataType* are equivalent.

**Return type** `bool`

### 6.13.2.2.6.3 pandera.engines.pandas\_engine.UINT8.coerce

`UINT8.coerce(data_container)`

Coerce data container to the data type.

**Return type** `Union[Series, Index, DataFrame]`

### 6.13.2.2.6.4 pandera.engines.pandas\_engine.UINT8.\_\_call\_\_

`UINT8.__call__(data_container)`

Coerce data container to the data type.

### 6.13.2.2.7 pandera.engines.pandas\_engine.UINT16

**class** `pandera.engines.pandas_engine.UINT16`

Semantic representation of a `pandas.UInt16Dtype`.

## Attributes

<code>bit_width</code>	Number of bits used by the machine representation.
<code>continuous</code>	Whether the number data type is continuous.
<code>exact</code>	Whether the data type is an exact representation of a number.
<code>signed</code>	Whether the integer data type is signed.
<code>type</code>	Native pandas dtype boxed by the data type.

## Methods

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

### 6.13.2.2.7.1 pandera.engines.pandas\_engine.UINT16.\_\_init\_\_

`UINT16.__init__()`

### 6.13.2.2.7.2 pandera.engines.pandas\_engine.UINT16.check

`UINT16.check(pandera_dtype)`  
Check that pandera *DataType* are equivalent.

**Return type** `bool`

### 6.13.2.2.7.3 pandera.engines.pandas\_engine.UINT16.coerce

`UINT16.coerce(data_container)`  
Coerce data container to the data type.

**Return type** `Union[Series, Index, DataFrame]`

### 6.13.2.2.7.4 pandera.engines.pandas\_engine.UINT16.\_\_call\_\_

`UINT16.__call__(data_container)`  
Coerce data container to the data type.

### 6.13.2.2.8 pandera.engines.pandas\_engine.UINT32

**class** `pandera.engines.pandas_engine.UINT32`  
Semantic representation of a `pandas.UInt32Dtype`.

## Attributes

<code>bit_width</code>	Number of bits used by the machine representation.
<code>continuous</code>	Whether the number data type is continuous.
<code>exact</code>	Whether the data type is an exact representation of a number.
<code>signed</code>	Whether the integer data type is signed.
<code>type</code>	Native pandas dtype boxed by the data type.

## Methods

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

### 6.13.2.2.8.1 pandera.engines.pandas\_engine.UINT32.\_\_init\_\_

`UINT32.__init__()`

### 6.13.2.2.8.2 pandera.engines.pandas\_engine.UINT32.check

`UINT32.check(pandera_dtype)`  
Check that pandera *DataType* are equivalent.

**Return type** `bool`

### 6.13.2.2.8.3 pandera.engines.pandas\_engine.UINT32.coerce

`UINT32.coerce(data_container)`  
Coerce data container to the data type.

**Return type** `Union[Series, Index, DataFrame]`

### 6.13.2.2.8.4 pandera.engines.pandas\_engine.UINT32.\_\_call\_\_

`UINT32.__call__(data_container)`  
Coerce data container to the data type.

### 6.13.2.2.9 pandera.engines.pandas\_engine.UINT64

**class** `pandera.engines.pandas_engine.UINT64`  
Semantic representation of a `pandas.UInt64Dtype`.

## Attributes

<code>bit_width</code>	Number of bits used by the machine representation.
<code>continuous</code>	Whether the number data type is continuous.
<code>exact</code>	Whether the data type is an exact representation of a number.
<code>signed</code>	Whether the integer data type is signed.
<code>type</code>	Native pandas dtype boxed by the data type.



## Methods

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

### 6.13.2.2.9.1 pandera.engines.pandas\_engine.UINT64.\_\_init\_\_

`UINT64.__init__()`

### 6.13.2.2.9.2 pandera.engines.pandas\_engine.UINT64.check

`UINT64.check(pandera_dtype)`  
Check that pandera *DataType* are equivalent.

**Return type** `bool`

### 6.13.2.2.9.3 pandera.engines.pandas\_engine.UINT64.coerce

`UINT64.coerce(data_container)`  
Coerce data container to the data type.

**Return type** `Union[Series, Index, DataFrame]`

### 6.13.2.2.9.4 pandera.engines.pandas\_engine.UINT64.\_\_call\_\_

`UINT64.__call__(data_container)`  
Coerce data container to the data type.

### 6.13.2.2.10 pandera.engines.pandas\_engine.STRING

`class pandera.engines.pandas_engine.STRING(storage='python')`  
Semantic representation of a `pandas.StringDtype`.

## Attributes

<code>continuous</code>	Whether the number data type is continuous.
<code>storage</code>	
<code>type</code>	Native pandas dtype boxed by the data type.

---

**Methods**

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>from_parametrized_dtype</code>	Convert a <code>pandas.StringDtype</code> to a Pandera <code>pandera.engines.pandas_engine.STRING</code> .
<code>__call__</code>	Coerce data container to the data type.

**6.13.2.2.10.1 pandera.engines.pandas\_engine.STRING.\_\_init\_\_**

`STRING.__init__(storage='python')`

**6.13.2.2.10.2 pandera.engines.pandas\_engine.STRING.check**

`STRING.check(pandera_dtype)`  
Check that pandera *DataType* are equivalent.

**Return type** `bool`

**6.13.2.2.10.3 pandera.engines.pandas\_engine.STRING.coerce**

`STRING.coerce(data_container)`  
Coerce data container to the data type.

**Return type** `Union[Series, Index, DataFrame]`

**6.13.2.2.10.4 pandera.engines.pandas\_engine.STRING.from\_parametrized\_dtype**

`classmethod STRING.from_parametrized_dtype(pd_dtype)`  
Convert a `pandas.StringDtype` to a Pandera `pandera.engines.pandas_engine.STRING`.

**6.13.2.2.10.5 pandera.engines.pandas\_engine.STRING.\_\_call\_\_**

`STRING.__call__(data_container)`  
Coerce data container to the data type.

**6.13.2.2.11 pandera.engines.numpy\_engine.Object**

`class pandera.engines.numpy_engine.Object`  
Semantic representation of a `numpy.object_`.

**Attributes**

<code>continuous</code>	Whether the number data type is continuous.
<code>type</code>	Native numpy dtype boxed by the data type.

**Methods**

<code>__init__</code>	
<code>check</code>	Check that pandera <i>DataType</i> are equivalent.
<code>coerce</code>	Coerce data container to the data type.
<code>__call__</code>	Coerce data container to the data type.

**6.13.2.2.11.1 pandera.engines.numpy\_engine.Object.\_\_init\_\_**

`Object.__init__()`

**6.13.2.2.11.2 pandera.engines.numpy\_engine.Object.check**

`Object.check(pandera_dtype)`  
Check that pandera *DataType* are equivalent.

**Return type** `bool`

**6.13.2.2.11.3 pandera.engines.numpy\_engine.Object.coerce**

`Object.coerce(data_container)`  
Coerce data container to the data type.

**Return type** `Union[Series, Index, DataFrame, ndarray]`

**6.13.2.2.11.4 pandera.engines.numpy\_engine.Object.\_\_call\_\_**

`Object.__call__(data_container)`  
Coerce data container to the data type.

**6.13.2.3 Utility functions**

<code>pandera.dtypes.is_subdtype</code>	Returns True if first argument is lower/equal in <i>DataType</i> hierarchy.
<code>pandera.dtypes.is_float</code>	Return True if <code>pandera.dtypes.DataType</code> is a float.
<code>pandera.dtypes.is_int</code>	Return True if <code>pandera.dtypes.DataType</code> is an integer.
<code>pandera.dtypes.is_uint</code>	Return True if <code>pandera.dtypes.DataType</code> is an unsigned integer.

continues on next page

Table 92 – continued from previous page

<code>pandera.dtypes.is_complex</code>	Return True if <code>pandera.dtypes.DataType</code> is a complex number.
<code>pandera.dtypes.is_numeric</code>	Return True if <code>pandera.dtypes.DataType</code> is a complex number.
<code>pandera.dtypes.is_bool</code>	Return True if <code>pandera.dtypes.DataType</code> is a boolean.
<code>pandera.dtypes.is_string</code>	Return True if <code>pandera.dtypes.DataType</code> is a string.
<code>pandera.dtypes.is_datetime</code>	Return True if <code>pandera.dtypes.DataType</code> is a date-time.
<code>pandera.dtypes.is_timedelta</code>	Return True if <code>pandera.dtypes.DataType</code> is a timedelta.
<code>pandera.dtypes.immutable</code>	<code>dataclasses.dataclass()</code> decorator with different default values: <code>frozen=True</code> , <code>init=False</code> , <code>repr=False</code> .

### 6.13.2.3.1 `pandera.dtypes.is_subdtype`

`pandera.dtypes.is_subdtype`(*arg1*, *arg2*)

Returns True if first argument is lower/equal in `DataType` hierarchy.

**Return type** `bool`

### 6.13.2.3.2 `pandera.dtypes.is_float`

`pandera.dtypes.is_float`(*pandera\_dtype*)

Return True if `pandera.dtypes.DataType` is a float.

**Return type** `bool`

### 6.13.2.3.3 `pandera.dtypes.is_int`

`pandera.dtypes.is_int`(*pandera\_dtype*)

Return True if `pandera.dtypes.DataType` is an integer.

**Return type** `bool`

### 6.13.2.3.4 `pandera.dtypes.is_uint`

`pandera.dtypes.is_uint`(*pandera\_dtype*)

Return True if `pandera.dtypes.DataType` is an unsigned integer.

**Return type** `bool`

### 6.13.2.3.5 `pandera.dtypes.is_complex`

`pandera.dtypes.is_complex(pandera_dtype)`

Return True if `pandera.dtypes.DataType` is a complex number.

**Return type** `bool`

### 6.13.2.3.6 `pandera.dtypes.is_numeric`

`pandera.dtypes.is_numeric(pandera_dtype)`

Return True if `pandera.dtypes.DataType` is a complex number.

**Return type** `bool`

### 6.13.2.3.7 `pandera.dtypes.is_bool`

`pandera.dtypes.is_bool(pandera_dtype)`

Return True if `pandera.dtypes.DataType` is a boolean.

**Return type** `bool`

### 6.13.2.3.8 `pandera.dtypes.is_string`

`pandera.dtypes.is_string(pandera_dtype)`

Return True if `pandera.dtypes.DataType` is a string.

**Return type** `bool`

### 6.13.2.3.9 `pandera.dtypes.is_datetime`

`pandera.dtypes.is_datetime(pandera_dtype)`

Return True if `pandera.dtypes.DataType` is a datetime.

**Return type** `bool`

### 6.13.2.3.10 `pandera.dtypes.is_timedelta`

`pandera.dtypes.is_timedelta(pandera_dtype)`

Return True if `pandera.dtypes.DataType` is a timedelta.

**Return type** `bool`

### 6.13.2.3.11 pandera.dtypes.immutable

`pandera.dtypes.immutable`(*pandera\_dtype\_cls=None*, *\*\*dataclass\_kwargs*)  
`dataclasses.dataclass()` decorator with different default values: *frozen=True*, *init=False*, *repr=False*.

In addition, *init=False* disables inherited `__init__` method to ensure the `DataType`'s default attributes are not altered during initialization.

#### Parameters

- **dtype** – `DataType` to decorate.
- **dataclass\_kwargs** (*Any*) – Keywords arguments forwarded to `dataclasses.dataclass()`.

**Return type** `Union[Type[~_Dtype], Callable[[Type[~_Dtype]], Type[~_Dtype]]]`

**Returns** Immutable `DataType`

### 6.13.2.4 Engines

<code>pandera.engines.engine.Engine</code>	Base Engine metaclass.
<code>pandera.engines.numpy_engine.Engine</code>	Numpy data type engine.
<code>pandera.engines.pandas_engine.Engine</code>	Pandas data type engine.

#### 6.13.2.4.1 pandera.engines.engine.Engine

**class** `pandera.engines.engine.Engine`(*name*, *bases*, *namespace*, *\*\*kwargs*)  
 Base Engine metaclass.

Keep a registry of concrete Engines.

#### Methods

<code>dtype</code>	Convert input into a Pandera <code>DataType</code> object.
<code>get_registered_dtypes</code>	Return the <code>pandera.dtypes.DataTypes</code> registered with this engine.
<code>register_dtype</code>	Register a Pandera <code>DataType</code> with the engine, as class decorator.
<code>__call__</code>	Call self as a function.

### 6.13.2.4.1.1 `pandera.engines.engine.Engine.dtype`

`Engine.dtype(data_type)`

Convert input into a Pandera `DataType` object.

**Return type** `~_DataType`

### 6.13.2.4.1.2 `pandera.engines.engine.Engine.get_registered_dtypes`

`Engine.get_registered_dtypes()`

Return the `pandera.dtypes.DataTypes` registered with this engine.

**Return type** `List[Type[DataType]]`

### 6.13.2.4.1.3 `pandera.engines.engine.Engine.register_dtype`

`Engine.register_dtype(pandera_dtype_cls=None, *, equivalents=None)`

Register a Pandera `DataType` with the engine, as class decorator.

**Parameters**

- **`pandera_dtype`** – The `DataType` to register.
- **`equivalents`** (`Optional[List[Any]]`) – Equivalent scalar data type classes or non-parametrized data type instances.

---

**Note:** The classmethod `from_parametrized_dtype` will also be registered. See [here](#) for more usage details.

---

**Example**

```
>>> import pandera as pa
>>>
>>> class MyDataType(pa.DataType):
...     pass
>>>
>>> class MyEngine(
...     metaclass=pa.engines.engine.Engine,
...     base_pandera_dtypes=MyDataType,
... ):
...     pass
>>>
>>> @MyEngine.register_dtype(equivalents=[bool])
... class MyBool(MyDataType):
...     pass
```

**Return type** `Callable`

#### 6.13.2.4.1.4 pandera.engines.engine.Engine.\_\_call\_\_

`Engine.__call__(*args, **kwargs)`  
Call self as a function.

#### 6.13.2.4.2 pandera.engines.numpy\_engine.Engine

**class** `pandera.engines.numpy_engine.Engine`  
Numpy data type engine.

##### Methods

---

<i>dtype</i>	Convert input into a numpy-compatible Pandera <i>DataType</i> object.
--------------	---

---

#### 6.13.2.4.2.1 pandera.engines.numpy\_engine.Engine.dtype

**classmethod** `Engine.dtype(data_type)`  
Convert input into a numpy-compatible Pandera *DataType* object.  
**Return type** *DataType*

#### 6.13.2.4.3 pandera.engines.pandas\_engine.Engine

**class** `pandera.engines.pandas_engine.Engine`  
Pandas data type engine.

##### Methods

---

<i>dtype</i>	Convert input into a pandas-compatible Pandera <i>DataType</i> object.
<i>numpy_dtype</i>	Convert a Pandera dtype.

---

#### 6.13.2.4.3.1 pandera.engines.pandas\_engine.Engine.dtype

**classmethod** `Engine.dtype(data_type)`  
Convert input into a pandas-compatible Pandera *DataType* object.  
**Return type** *DataType*



### 6.13.2.4.3.2 pandera.engines.pandas\_engine.Engine.numpy\_dtype

**classmethod** `Engine.numpy_dtype(pandera_dtype)`

Convert a Pandera dtype.

**Return type** `dtype`

### 6.13.2.5 PandasDtype Enum

**Warning:** This class deprecated and will be removed from the pandera API in 0.9.0

---

`pandera.engines.pandas_engine.PandasDtype` Enumerate all valid pandas data types.

---

#### 6.13.2.5.1 pandera.engines.pandas\_engine.PandasDtype

**class** `pandera.engines.pandas_engine.PandasDtype(value)`

Enumerate all valid pandas data types.

This class simply enumerates the valid numpy dtypes for pandas arrays. For convenience `PandasDtype` enums can all be accessed in the top-level `pandera` name space via the same enum name.

**Warning:** This class is deprecated and will be removed in pandera v0.9.0. Use python types, pandas type string aliases, numpy dtypes, or pandas dtypes instead. See [Pandera Data Types \(new\)](#) for details.

#### Examples

```
>>> import pandas as pd
>>> import pandera as pa
>>>
>>> pa.SeriesSchema(pa.PandasDtype.Int).validate(pd.Series([1, 2, 3]))
0    1
1    2
2    3
dtype: int64
>>> pa.SeriesSchema(pa.PandasDtype.Float).validate(pd.Series([1.1, 2.3, 3.4]))
0    1.1
1    2.3
2    3.4
dtype: float64
>>> pa.SeriesSchema(pa.PandasDtype.String).validate(pd.Series(["a", "b", "c"]))
0    a
1    b
2    c
dtype: object
```

## Attributes

Bool	"bool" numpy dtype
DateTime	"datetime64[ns]" numpy dtype
Timedelta	"timedelta64[ns]" numpy dtype
Float	"float" numpy dtype
Float16	"float16" numpy dtype
Float32	"float32" numpy dtype
Float64	"float64" numpy dtype
Int	"int" numpy dtype
Int8	"int8" numpy dtype
Int16	"int16" numpy dtype
Int32	"int32" numpy dtype
Int64	"int64" numpy dtype
UInt8	"uint8" numpy dtype
UInt16	"uint16" numpy dtype
UInt32	"uint32" numpy dtype
UInt64	"uint64" numpy dtype
Object	"object" numpy dtype
Complex	"complex" numpy dtype
Complex64	"complex" numpy dtype
Complex128	"complex" numpy dtype
Complex256	"complex" numpy dtype
Category	pandas "categorical" datatype
INT8	"Int8" pandas dtype: pandas 0.24.0+
INT16	"Int16" pandas dtype: pandas 0.24.0+
INT32	"Int32" pandas dtype: pandas 0.24.0+
INT64	"Int64" pandas dtype: pandas 0.24.0+
UINT8	"UInt8" pandas dtype: pandas 0.24.0+
UINT16	"UInt16" pandas dtype: pandas 0.24.0+
UINT32	"UInt32" pandas dtype: pandas 0.24.0+
UINT64	"UInt64" pandas dtype: pandas 0.24.0+
String	"str" numpy dtype
STRING	"string" pandas dtypes: pandas 1.0.0+

## 6.13.3 Schema Models

### 6.13.3.1 Schema Model

---

<code>pandera.model.SchemaModel(*args, **kwargs)</code>	Definition of a DataFrameSchema.
---	----------------------------------

---

### 6.13.3.1.1 pandera.model.SchemaModel

**class** `pandera.model.SchemaModel(*args, **kwargs)`

Definition of a DataFrameSchema.

*new in 0.5.0*

See the *User Guide* for more.

#### Methods

<i>example</i>	Create a hypothesis strategy for generating a DataFrame.
<i>strategy</i>	Create a hypothesis strategy for generating a DataFrame.
<i>to_schema</i>	Create DataFrameSchema from the <i>SchemaModel</i> .
<i>to_yaml</i>	Convert <i>Schema</i> to yaml using <i>io.to_yaml</i> .
<i>validate</i>	Check if all columns in a dataframe have a column in the Schema.

#### 6.13.3.1.1.1 pandera.model.SchemaModel.example

**classmethod** `SchemaModel.example(cls, *, size=None)`

Create a hypothesis strategy for generating a DataFrame.

##### Parameters

- **size** (`Optional[int]`) – number of elements to generate
- **n\_regex\_columns** – number of regex columns to generate.

**Return type** `DataFrame[~TSchemaModel]`

**Returns** a strategy that generates pandas DataFrame objects.

#### 6.13.3.1.1.2 pandera.model.SchemaModel.strategy

**classmethod** `SchemaModel.strategy(cls, *, size=None)`

Create a hypothesis strategy for generating a DataFrame.

##### Parameters

- **size** (`Optional[int]`) – number of elements to generate
- **n\_regex\_columns** – number of regex columns to generate.

**Return type** `DataFrame[~TSchemaModel]`

**Returns** a strategy that generates pandas DataFrame objects.

### 6.13.3.1.1.3 pandera.model.SchemaModel.to\_schema

**classmethod** `SchemaModel.to_schema()`

Create `DataFrameSchema` from the `SchemaModel`.

**Return type** `DataFrameSchema`

### 6.13.3.1.1.4 pandera.model.SchemaModel.to\_yaml

**classmethod** `SchemaModel.to_yaml(stream=None)`

Convert `Schema` to yaml using `io.to_yaml`.

### 6.13.3.1.1.5 pandera.model.SchemaModel.validate

**classmethod** `SchemaModel.validate(check_obj, head=None, tail=None, sample=None, random_state=None, lazy=False, inplace=False)`

Check if all columns in a dataframe have a column in the Schema.

#### Parameters

- **check\_obj** (`pd.DataFrame`) – the dataframe to be validated.
- **head** (`Optional[int]`) – validate the first n rows. Rows overlapping with `tail` or `sample` are de-duplicated.
- **tail** (`Optional[int]`) – validate the last n rows. Rows overlapping with `head` or `sample` are de-duplicated.
- **sample** (`Optional[int]`) – validate a random sample of n rows. Rows overlapping with `head` or `tail` are de-duplicated.
- **random\_state** (`Optional[int]`) – random seed for the `sample` argument.
- **lazy** (`bool`) – if True, lazily evaluates dataframe against all validation checks and raises a `SchemaErrors`. Otherwise, raise `SchemaError` as soon as one occurs.
- **inplace** (`bool`) – if True, applies coercion to the object of validation, otherwise creates a copy of the data.

**Return type** `DataFrame[~TSchemaModel]`

**Returns** validated `DataFrame`

**Raises** `SchemaError` – when `DataFrame` violates built-in or custom checks.

#### Example

Calling `schema.validate` returns the dataframe.

```
>>> import pandas as pd
>>> import pandera as pa
>>>
>>> df = pd.DataFrame({
...     "probability": [0.1, 0.4, 0.52, 0.23, 0.8, 0.76],
...     "category": ["dog", "dog", "cat", "duck", "dog", "dog"]
... })
>>>
>>> schema_withchecks = pa.DataFrameSchema({
```

(continues on next page)

(continued from previous page)

```

...     "probability": pa.Column(
...         float, pa.Check(lambda s: (s >= 0) & (s <= 1))),
...
...     # check that the "category" column contains a few discrete
...     # values, and the majority of the entries are dogs.
...     "category": pa.Column(
...         str, [
...             pa.Check(lambda s: s.isin(["dog", "cat", "duck"])),
...             pa.Check(lambda s: (s == "dog").mean() > 0.5),
...         ]),
...     })
>>>
>>> schema_withchecks.validate(df)[["probability", "category"]]
  probability category
0          0.10     dog
1          0.40     dog
2          0.52     cat
3          0.23    duck
4          0.80     dog
5          0.76     dog

```

### 6.13.3.2 Model Components

<code>pandera.model_components.Field(*[, eq, ne, ...])</code>	Used to provide extra information about a field of a SchemaModel.
<code>pandera.model_components.check(*fields[, regex])</code>	Decorator to make SchemaModel method a column/index check function.
<code>pandera.model_components.dataframe_check([_fn])</code>	Decorator to make SchemaModel method a dataframe-wide check function.

#### 6.13.3.2.1 pandera.model\_components.Field

`pandera.model_components.Field(*, eq=None, ne=None, gt=None, ge=None, lt=None, le=None, in_range=None, isin=None, notin=None, str_contains=None, str_endswith=None, str_length=None, str_matches=None, str_startswith=None, nullable=False, allow_duplicates=True, coerce=False, regex=False, ignore_na=True, raise_warning=False, n_failure_cases=10, alias=None, check_name=None, dtype_kwargs=None, **kwargs)`

Used to provide extra information about a field of a SchemaModel.

*new in 0.5.0*

Some arguments apply only to numeric dtypes and some apply only to `str`. See the *User Guide* for more information.

The keyword-only arguments from `eq` to `str_startswith` are dispatched to the built-in `~pandera.checks.Check` methods.

#### Parameters

- **nullable** (`bool`) – whether or not the column/index is nullable.

- **allow\_duplicates** (*bool*) – whether or not to accept duplicate values.
- **coerce** (*bool*) – coerces the data type if *True*.
- **regex** (*bool*) – whether or not the field name or alias is a regex pattern.
- **ignore\_na** (*bool*) – whether or not to ignore null values in the checks.
- **raise\_warning** (*bool*) – raise a warning instead of an Exception.
- **n\_failure\_cases** (*int*) – report the first *n* unique failure cases. If *None*, report all failure cases.
- **alias** (*Optional[Any]*) – The public name of the column/index.
- **check\_name** (*Optional[bool]*) – Whether to check the name of the column/index during validation. *None* is the default behavior, which translates to *True* for columns and multi-index, and to *False* for a single index.
- **dtype\_kwargs** (*Optional[Dict[str, Any]]*) – The parameters to be forwarded to the type of the field.
- **kwargs** – Specify custom checks that have been registered with the `register_check_method` decorator.

**Return type** *Any*

### 6.13.3.2.2 pandera.model\_components.check

`pandera.model_components.check(*fields, regex=False, **check_kwargs)`

Decorator to make SchemaModel method a column/index check function.

*new in 0.5.0*

This indicates that the decorated method should be used to validate a field (column or index). The method will be converted to a classmethod. Therefore its signature must start with *cls* followed by regular check arguments. See the *User Guide* for more.

#### Parameters

- **\_fn** – Method to decorate.
- **check\_kwargs** – Keywords arguments forwarded to Check.

**Return type** `Callable[[Union[classmethod, Callable[... Any]], classmethod]`

### 6.13.3.2.3 pandera.model\_components.dataframe\_check

`pandera.model_components.dataframe_check(_fn=None, **check_kwargs)`

Decorator to make SchemaModel method a dataframe-wide check function.

*new in 0.5.0*

Decorate a method on the SchemaModel indicating that it should be used to validate the DataFrame. The method will be converted to a classmethod. Therefore its signature must start with *cls* followed by regular check arguments. See the *User Guide* for more.

**Parameters** **check\_kwargs** – Keywords arguments forwarded to Check.

**Return type** `Callable[[Union[classmethod, Callable[... Any]], classmethod]`

### 6.13.3.3 Typing

---

*pandera.typing*

Typing definitions and helpers.

---

#### 6.13.3.3.1 pandera.typing

Typing definitions and helpers.

#### Pandas object annotations

<code>DataFrame([data, index, columns, dtype, copy])</code>	Representation of <code>pandas.DataFrame</code> , only used for type annotation.
<code>Index([data, dtype, copy, name, tupleize_cols])</code>	Representation of <code>pandas.Index</code> , only used for type annotation.
<code>Series([data, index, dtype, name, copy, ...])</code>	Representation of <code>pandas.Series</code> , only used for type annotation.

#### Dtype annotations

<code>Bool()</code>	Semantic representation of a boolean data type.
<code>DateTime</code>	alias of <code>pandera.dtypes.Timestamp</code>
<code>Timedelta()</code>	Semantic representation of a delta time data type.
<code>Category([categories, ordered])</code>	Semantic representation of a categorical data type.
<code>Float()</code>	Semantic representation of a floating data type.
<code>Float16()</code>	Semantic representation of a floating data type stored in 16 bits.
<code>Float32()</code>	Semantic representation of a floating data type stored in 32 bits.
<code>Float64()</code>	Semantic representation of a floating data type stored in 64 bits.
<code>Int()</code>	Semantic representation of an integer data type.
<code>Int8()</code>	Semantic representation of an integer data type stored in 8 bits.
<code>Int16()</code>	Semantic representation of an integer data type stored in 16 bits.
<code>Int32()</code>	Semantic representation of an integer data type stored in 32 bits.
<code>Int64()</code>	Semantic representation of an integer data type stored in 64 bits.
<code>UInt8()</code>	Semantic representation of an unsigned integer data type stored in 8 bits.
<code>UInt16()</code>	Semantic representation of an unsigned integer data type stored in 16 bits.
<code>UInt32()</code>	Semantic representation of an unsigned integer data type stored in 32 bits.
<code>UInt64()</code>	Semantic representation of an unsigned integer data type stored in 64 bits.

continues on next page

Table 104 – continued from previous page

INT8()	Semantic representation of a <code>pandas.Int8Dtype</code> .
INT16()	Semantic representation of a <code>pandas.Int16Dtype</code> .
INT32()	Semantic representation of a <code>pandas.Int32Dtype</code> .
INT64()	Semantic representation of a <code>pandas.Int64Dtype</code> .
UINT8()	Semantic representation of a <code>pandas.UInt8Dtype</code> .
UINT16()	Semantic representation of a <code>pandas.UInt16Dtype</code> .
UINT32()	Semantic representation of a <code>pandas.UInt32Dtype</code> .
UINT64()	Semantic representation of a <code>pandas.UInt64Dtype</code> .
Object()	Semantic representation of a <code>numpy.object_</code> .
String()	Semantic representation of a string data type.
STRING([storage])	Semantic representation of a <code>pandas.StringDtype</code> .

### 6.13.3.4 Config

<code>pandera.model.BaseConfig</code>	Define DataFrameSchema-wide options.
---------------------------------------	--------------------------------------

#### 6.13.3.4.1 `pandera.model.BaseConfig`

**class** `pandera.model.BaseConfig`

Bases: `object`

Define DataFrameSchema-wide options.

*new in 0.5.0*

#### Attributes

<code>coerce</code>	coerce types of all schema components
<code>multiindex_coerce</code>	coerce types of all MultiIndex components
<code>multiindex_name</code>	name of multiindex
<code>multiindex_ordered</code>	validate MultiIndex in order
<code>multiindex_strict</code>	make sure all specified columns are in validated MultiIndex - if "filter", removes indexes not specified in the schema
<code>name</code>	name of schema
<code>ordered</code>	validate columns order
<code>strict</code>	make sure all specified columns are in the validated dataframe - if "filter", removes columns not specified in the schema



## 6.13.4 Decorators

<code>pandera.decorators.check_input</code>	Validate function argument when function is called.
<code>pandera.decorators.check_output</code>	Validate function output.
<code>pandera.decorators.check_io</code>	Check schema for multiple inputs and outputs.
<code>pandera.decorators.check_types</code>	Validate function inputs and output based on type annotations.

### 6.13.4.1 `pandera.decorators.check_input`

`pandera.decorators.check_input` (*schema*, *obj\_getter=None*, *head=None*, *tail=None*, *sample=None*, *random\_state=None*, *lazy=False*, *inplace=False*)

Validate function argument when function is called.

This is a decorator function that validates the schema of a dataframe argument in a function.

#### Parameters

- **schema** (`Union[DataFrameSchema, SeriesSchema]`) – dataframe/series schema object
- **obj\_getter** (`Union[str, int, None]`) – (Default value = None) if int, `obj_getter` refers to the the index of the pandas dataframe/series to be validated in the args part of the function signature. If str, `obj_getter` refers to the argument name of the pandas dataframe/series in the function signature. This works even if the series/dataframe is passed in as a positional argument when the function is called. If None, assumes that the dataframe/series is the first argument of the decorated function
- **head** (`Optional[int]`) – validate the first n rows. Rows overlapping with *tail* or *sample* are de-duplicated.
- **tail** (`Optional[int]`) – validate the last n rows. Rows overlapping with *head* or *sample* are de-duplicated.
- **sample** (`Optional[int]`) – validate a random sample of n rows. Rows overlapping with *head* or *tail* are de-duplicated.
- **random\_state** (`Optional[int]`) – random seed for the *sample* argument.
- **lazy** (`bool`) – if True, lazily evaluates dataframe against all validation checks and raises a `SchemaErrors`. Otherwise, raise `SchemaError` as soon as one occurs.
- **inplace** (`bool`) – if True, applies coercion to the object of validation, otherwise creates a copy of the data.

**Return type** `Callable[[~F], ~F]`

**Returns** wrapped function

#### Example

Check the input of a decorated function.

```
>>> import pandas as pd
>>> import pandera as pa
>>>
>>>
>>> schema = pa.DataFrameSchema({"column": pa.Column(int)})
>>>
```

(continues on next page)

```

>>> @pa.check_input(schema)
... def transform_data(df: pd.DataFrame) -> pd.DataFrame:
...     df["doubled_column"] = df["column"] * 2
...     return df
>>>
>>> df = pd.DataFrame({
...     "column": range(5),
... })
>>>
>>> transform_data(df)
   column  doubled_column
0         0                0
1         1                2
2         2                4
3         3                6
4         4                8

```

See [here](#) for more usage details.

### 6.13.4.2 `pandera.decorators.check_output`

`pandera.decorators.check_output`(*schema, obj\_getter=None, head=None, tail=None, sample=None, random\_state=None, lazy=False, inplace=False*)

Validate function output.

Similar to input validator, but validates the output of the decorated function.

#### Parameters

- **schema** (`Union[DataFrameSchema, SeriesSchema]`) – dataframe/series schema object
- **obj\_getter** (`Union[str, int, Callable, None]`) – (Default value = None) if int, assumes that the output of the decorated function is a list-like object, where `obj_getter` is the index of the pandas data dataframe/series to be validated. If str, expects that the output is a dict-like object, and `obj_getter` is the key pointing to the dataframe/series to be validated. If a callable is supplied, it expects the output of decorated function and should return the dataframe/series to be validated.
- **head** (`Optional[int]`) – validate the first n rows. Rows overlapping with `tail` or `sample` are de-duplicated.
- **tail** (`Optional[int]`) – validate the last n rows. Rows overlapping with `head` or `sample` are de-duplicated.
- **sample** (`Optional[int]`) – validate a random sample of n rows. Rows overlapping with `head` or `tail` are de-duplicated.
- **random\_state** (`Optional[int]`) – random seed for the `sample` argument.
- **lazy** (`bool`) – if True, lazily evaluates dataframe against all validation checks and raises a `SchemaErrors`. Otherwise, raise `SchemaError` as soon as one occurs.
- **inplace** (`bool`) – if True, applies coercion to the object of validation, otherwise creates a copy of the data.

**Return type** `Callable[[~F], ~F]`

**Returns** wrapped function

### Example

Check the output a decorated function.

```

>>> import pandas as pd
>>> import pandera as pa
>>>
>>>
>>> schema = pa.DataFrameSchema(
...     columns={"doubled_column": pa.Column(int)},
...     checks=pa.Check(
...         lambda df: df["doubled_column"] == df["column"] * 2
...     )
... )
>>>
>>> @pa.check_output(schema)
... def transform_data(df: pd.DataFrame) -> pd.DataFrame:
...     df["doubled_column"] = df["column"] * 2
...     return df
>>>
>>> df = pd.DataFrame({"column": range(5)})
>>>
>>> transform_data(df)
   column  doubled_column
0        0                0
1        1                2
2        2                4
3        3                6
4        4                8

```

See [here](#) for more usage details.

#### 6.13.4.3 pandera.decorators.check\_io

`pandera.decorators.check_io`(*head=None, tail=None, sample=None, random\_state=None, lazy=False, inplace=False, out=None, \*\*inputs*)

Check schema for multiple inputs and outputs.

See [here](#) for more usage details.

##### Parameters

- **head** (`Optional[int]`) – validate the first *n* rows. Rows overlapping with *tail* or *sample* are de-duplicated.
- **tail** (`Optional[int]`) – validate the last *n* rows. Rows overlapping with *head* or *sample* are de-duplicated.
- **sample** (`Optional[int]`) – validate a random sample of *n* rows. Rows overlapping with *head* or *tail* are de-duplicated.
- **random\_state** (`Optional[int]`) – random seed for the *sample* argument.
- **lazy** (`bool`) – if True, lazily evaluates dataframe against all validation checks and raises a `SchemaErrors`. Otherwise, raise `SchemaError` as soon as one occurs.
- **inplace** (`bool`) – if True, applies coercion to the object of validation, otherwise creates a copy of the data.

- **out** (`Union[DataFrameSchema, SeriesSchema, Tuple[Union[str, int, Callable], Union[DataFrameSchema, SeriesSchema]]]`, `List[Tuple[Union[str, int, Callable], Union[DataFrameSchema, SeriesSchema]]]`, `None`) – this should be a schema object if the function outputs a single dataframe/series. It can be a two-tuple, where the first element is a string, integer, or callable that fetches the pandas data structure in the output, and the second element is the schema to validate against. For multiple outputs, specify a list of two-tuples following the above structure.
- **inputs** (`Union[DataFrameSchema, SeriesSchema]`) – kwargs keys should be the argument name in the decorated function and values should be the schema used to validate the pandas data structure referenced by the argument name.

**Return type** `Callable[[~F], ~F]`

**Returns** wrapped function

#### 6.13.4.4 `pandera.decorators.check_types`

`pandera.decorators.check_types`(*wrapped: pandera.decorators.F*, \*, *head: Optional[int] = 'None'*, *tail: Optional[int] = 'None'*, *sample: Optional[int] = 'None'*, *random\_state: Optional[int] = 'None'*, *lazy: bool = 'False'*, *inplace: bool = 'False'*) → `pandera.decorators.F`

`pandera.decorators.check_types`(*wrapped: None = None*, \*, *head: Optional[int] = 'None'*, *tail: Optional[int] = 'None'*, *sample: Optional[int] = 'None'*, *random\_state: Optional[int] = 'None'*, *lazy: bool = 'False'*, *inplace: bool = 'False'*) → `Callable[[pandera.decorators.F], pandera.decorators.F]`

Validate function inputs and output based on type annotations.

See the *User Guide* for more.

##### Parameters

- **head** (`Optional[int]`) – validate the first n rows. Rows overlapping with *tail* or *sample* are de-duplicated.
- **tail** (`Optional[int]`) – validate the last n rows. Rows overlapping with *head* or *sample* are de-duplicated.
- **sample** (`Optional[int]`) – validate a random sample of n rows. Rows overlapping with *head* or *tail* are de-duplicated.
- **random\_state** (`Optional[int]`) – random seed for the *sample* argument.
- **lazy** (`bool`) – if True, lazily evaluates dataframe against all validation checks and raises a `SchemaErrors`. Otherwise, raise `SchemaError` as soon as one occurs.
- **inplace** (`bool`) – if True, applies coercion to the object of validation, otherwise creates a copy of the data.

**Return type** `Callable`

## 6.13.5 Schema Inference

---

<code>pandera.schema_inference.infer_schema</code>	Infer schema for pandas DataFrame or Series object.
--	---

---

### 6.13.5.1 pandera.schema\_inference.infer\_schema

`pandera.schema_inference.infer_schema(pandas_obj)`

Infer schema for pandas DataFrame or Series object.

**Parameters** `pandas_obj` (`Union[DataFrame, Series]`) – DataFrame or Series object to infer.

**Return type** `Union[DataFrameSchema, SeriesSchema]`

**Returns** DataFrameSchema or SeriesSchema

**Raises** TypeError if pandas\_obj is not expected type.

## 6.13.6 IO Utilities

The `io` module and built-in Hypothesis checks require a pandera installation with the corresponding extension, see the *installation* instructions for more details.

---

<code>pandera.io.from_yaml</code>	Create <code>DataFrameSchema</code> from yaml file.
<code>pandera.io.to_yaml</code>	Write <code>DataFrameSchema</code> to yaml file.
<code>pandera.io.to_script</code>	Write <code>DataFrameSchema</code> to a python script.

---

### 6.13.6.1 pandera.io.from\_yaml

`pandera.io.from_yaml(yaml_schema)`

Create `DataFrameSchema` from yaml file.

**Parameters** `yaml_schema` – str or Path to yaml schema, or serialized yaml string.

**Returns** dataframe schema.

### 6.13.6.2 pandera.io.to\_yaml

`pandera.io.to_yaml(dataframe_schema, stream=None)`

Write `DataFrameSchema` to yaml file.

**Parameters**

- `dataframe_schema` – schema to write to file or dump to string.
- `stream` – file stream to write to. If None, dumps to string.

**Returns** yaml string if stream is None, otherwise returns None.

### 6.13.6.3 pandera.io.to\_script

`pandera.io.to_script(dataframe_schema, path_or_buf=None)`

Write `DataFrameSchema` to a python script.

#### Parameters

- **dataframe\_schema** – schema to write to file or dump to string.
- **path\_or\_buf** – filepath or buf stream to write to. If None, outputs string representation of the script.

**Returns** yaml string if stream is None, otherwise returns None.

## 6.13.7 Data Synthesis Strategies

---

*pandera.strategies*

Generate synthetic data from a schema definition.

---

### 6.13.7.1 pandera.strategies

Generate synthetic data from a schema definition.

*new in 0.6.0*

This module is responsible for generating data based on the type and check constraints specified in a `pandera` schema. It's built on top of the `hypothesis` package to compose strategies given multiple checks specified in a schema.

See the *user guide* for more details.

`pandera.strategies.column_strategy(pandera_dtype, strategy=None, *, checks=None, allow_duplicates=True, name=None)`

Create a data object describing a column in a DataFrame.

#### Parameters

- **pandera\_dtype** (`Union[DataType, DataType]`) – `pandera.dtypes.DataType` instance.
- **strategy** (`Optional[SearchStrategy]`) – an optional hypothesis strategy. If specified, the pandas dtype strategy will be chained onto this strategy.
- **checks** (`Optional[Sequence]`) – sequence of `Check` s to constrain the values of the data in the column/index.
- **allow\_duplicates** (`Optional[bool]`) – whether or not generated Series contains duplicates.
- **name** (`Optional[str]`) – name of the Series.

**Returns** a `column` object.

`pandera.strategies.dataframe_strategy(pandera_dtype=None, strategy=None, *, columns=None, checks=None, index=None, size=None, n_regex_columns=1)`

Strategy to generate a pandas DataFrame.

#### Parameters

- **pandera\_dtype** (`Optional[DataType]`) – `pandera.dtypes.DataType` instance.
- **strategy** (`Optional[SearchStrategy]`) – if specified, this will raise a `BaseStrategyOnlyError`, since it cannot be chained to a prior strategy.

- **columns** (*Optional*[Dict]) – a dictionary where keys are column names and values are *Column* objects.
- **checks** (*Optional*[Sequence]) – sequence of *Check* s to constrain the values of the data at the dataframe level.
- **index** (*Optional*[Any]) – Index or MultiIndex schema component.
- **size** (*Optional*[int]) – number of elements in the Series.
- **n\_regex\_columns** (int) – number of regex columns to generate.

**Returns** hypothesis strategy.

`pandera.strategies.eq_strategy(pandera_dtype, strategy=None, *, value)`

Strategy to generate a single value.

#### Parameters

- **pandera\_dtype** (*Union*[DataType, DataType]) – *pandera.dtypes.DataType* instance.
- **strategy** (*Optional*[SearchStrategy]) – an optional hypothesis strategy. If specified, the pandas dtype strategy will be chained onto this strategy.
- **value** (*Any*) – value to generate.

**Return type** SearchStrategy

**Returns** hypothesis strategy

`pandera.strategies.field_element_strategy(pandera_dtype, strategy=None, *, checks=None)`

Strategy to generate elements of a column or index.

#### Parameters

- **pandera\_dtype** (*Union*[DataType, DataType]) – *pandera.dtypes.DataType* instance.
- **strategy** (*Optional*[SearchStrategy]) – an optional hypothesis strategy. If specified, the pandas dtype strategy will be chained onto this strategy.
- **checks** (*Optional*[Sequence]) – sequence of *Check* s to constrain the values of the data in the column/index.

**Return type** SearchStrategy

**Returns** hypothesis strategy

`pandera.strategies.ge_strategy(pandera_dtype, strategy=None, *, min_value)`

Strategy to generate values greater than or equal to a minimum value.

#### Parameters

- **pandera\_dtype** (*Union*[DataType, DataType]) – *pandera.dtypes.DataType* instance.
- **strategy** (*Optional*[SearchStrategy]) – an optional hypothesis strategy. If specified, the pandas dtype strategy will be chained onto this strategy.
- **min\_value** (*Union*[int, float]) – generate values greater than or equal to this.

**Return type** SearchStrategy

**Returns** hypothesis strategy

`pandera.strategies.gt_strategy(pandera_dtype, strategy=None, *, min_value)`

Strategy to generate values greater than a minimum value.

#### Parameters

- **pandera\_dtype** (`Union[DataType, DataType]`) – `pandera.dtypes.DataType` instance.
- **strategy** (`Optional[SearchStrategy]`) – an optional hypothesis strategy. If specified, the pandas dtype strategy will be chained onto this strategy.
- **min\_value** (`Union[int, float]`) – generate values larger than this.

**Return type** SearchStrategy

**Returns** hypothesis strategy

`pandera.strategies.in_range_strategy(pandera_dtype, strategy=None, *, min_value, max_value, include_min=True, include_max=True)`

Strategy to generate values within a particular range.

**Parameters**

- **pandera\_dtype** (`Union[DataType, DataType]`) – `pandera.dtypes.DataType` instance.
- **strategy** (`Optional[SearchStrategy]`) – an optional hypothesis strategy. If specified, the pandas dtype strategy will be chained onto this strategy.
- **min\_value** (`Union[int, float]`) – generate values greater than this.
- **max\_value** (`Union[int, float]`) – generate values less than this.
- **include\_min** (`bool`) – include `min_value` in generated data.
- **include\_max** (`bool`) – include `max_value` in generated data.

**Return type** SearchStrategy

**Returns** hypothesis strategy

`pandera.strategies.index_strategy(pandera_dtype, strategy=None, *, checks=None, nullable=False, allow_duplicates=True, name=None, size=None)`

Strategy to generate a pandas Index.

**Parameters**

- **pandera\_dtype** (`Union[DataType, DataType]`) – `pandera.dtypes.DataType` instance.
- **strategy** (`Optional[SearchStrategy]`) – an optional hypothesis strategy. If specified, the pandas dtype strategy will be chained onto this strategy.
- **checks** (`Optional[Sequence]`) – sequence of `Check` s to constrain the values of the data in the column/index.
- **nullable** (`Optional[bool]`) – whether or not generated Series contains null values.
- **allow\_duplicates** (`Optional[bool]`) – whether or not generated Series contains duplicates.
- **name** (`Optional[str]`) – name of the Series.
- **size** (`Optional[int]`) – number of elements in the Series.

**Returns** hypothesis strategy.

`pandera.strategies.isin_strategy(pandera_dtype, strategy=None, *, allowed_values)`

Strategy to generate values within a finite set.

**Parameters**

- **pandera\_dtype** (`Union[DataType, DataType]`) – `pandera.dtypes.DataType` instance.
- **strategy** (`Optional[SearchStrategy]`) – an optional hypothesis strategy. If specified, the pandas dtype strategy will be chained onto this strategy.



- **allowed\_values** (`Sequence[Any]`) – set of allowable values.

**Return type** SearchStrategy

**Returns** hypothesis strategy

`pandera.strategies.le_strategy(pandera_dtype, strategy=None, *, max_value)`

Strategy to generate values less than or equal to a maximum value.

**Parameters**

- **pandera\_dtype** (`Union[DataType, DataType]`) – `pandera.dtypes.DataType` instance.
- **strategy** (`Optional[SearchStrategy]`) – an optional hypothesis strategy. If specified, the pandas dtype strategy will be chained onto this strategy.
- **max\_value** (`Union[int, float]`) – generate values less than or equal to this.

**Return type** SearchStrategy

**Returns** hypothesis strategy

`pandera.strategies.lt_strategy(pandera_dtype, strategy=None, *, max_value)`

Strategy to generate values less than a maximum value.

**Parameters**

- **pandera\_dtype** (`Union[DataType, DataType]`) – `pandera.dtypes.DataType` instance.
- **strategy** (`Optional[SearchStrategy]`) – an optional hypothesis strategy. If specified, the pandas dtype strategy will be chained onto this strategy.
- **max\_value** (`Union[int, float]`) – generate values less than this.

**Return type** SearchStrategy

**Returns** hypothesis strategy

`pandera.strategies.multiindex_strategy(pandera_dtype=None, strategy=None, *, indexes=None, size=None)`

Strategy to generate a pandas MultiIndex object.

**Parameters**

- **pandera\_dtype** (`Optional[DataType]`) – `pandera.dtypes.DataType` instance.
- **strategy** (`Optional[SearchStrategy]`) – an optional hypothesis strategy. If specified, the pandas dtype strategy will be chained onto this strategy.
- **indexes** (`Optional[List]`) – a list of Index objects.
- **size** (`Optional[int]`) – number of elements in the Series.

**Returns** hypothesis strategy.

`pandera.strategies.ne_strategy(pandera_dtype, strategy=None, *, value)`

Strategy to generate anything except for a particular value.

**Parameters**

- **pandera\_dtype** (`Union[DataType, DataType]`) – `pandera.dtypes.DataType` instance.
- **strategy** (`Optional[SearchStrategy]`) – an optional hypothesis strategy. If specified, the pandas dtype strategy will be chained onto this strategy.
- **value** (`Any`) – value to avoid.

**Return type** SearchStrategy

**Returns** hypothesis strategy

`pandera.strategies.notin_strategy(pandera_dtype, strategy=None, *, forbidden_values)`  
Strategy to generate values excluding a set of forbidden values

**Parameters**

- **pandera\_dtype** (`Union[DataType, DataType]`) – `pandera.dtypes.DataType` instance.
- **strategy** (`Optional[SearchStrategy]`) – an optional hypothesis strategy. If specified, the pandas dtype strategy will be chained onto this strategy.
- **forbidden\_values** (`Sequence[Any]`) – set of forbidden values.

**Return type** SearchStrategy

**Returns** hypothesis strategy

`pandera.strategies.numpy_complex_dtypes(dtype, min_value=0j, max_value=None, allow_infinity=None, allow_nan=None)`

Create numpy strategy for complex numbers.

**Parameters**

- **dtype** – numpy complex number datatype
- **min\_value** (`complex`) – minimum value, must be complex number
- **max\_value** (`Optional[complex]`) – maximum value, must be complex number

**Returns** hypothesis strategy

`pandera.strategies.numpy_time_dtypes(dtype, min_value=None, max_value=None)`  
Create numpy strategy for datetime and timedelta data types.

**Parameters**

- **dtype** (`dtype`) – numpy datetime or timedelta datatype
- **min\_value** – minimum value of the datatype to create
- **max\_value** – maximum value of the datatype to create

**Returns** hypothesis strategy

`pandera.strategies.pandas_dtype_strategy(pandera_dtype, strategy=None, **kwargs)`  
Strategy to generate data from a `pandera.dtypes.DataType`.

**Parameters**

- **pandera\_dtype** (`DataType`) – `pandera.dtypes.DataType` instance.
- **strategy** (`Optional[SearchStrategy]`) – an optional hypothesis strategy. If specified, the pandas dtype strategy will be chained onto this strategy.

**Kwargs** key-word arguments passed into `hypothesis.extra.numpy.from_dtype`. For date-time, timedelta, and complex number datatypes, these arguments are passed into `numpy_time_dtypes()` and `numpy_complex_dtypes()`.

**Return type** SearchStrategy

**Returns** hypothesis strategy

`pandera.strategies.register_check_strategy(strategy_fn)`  
Decorate a Check method with a strategy.

This should be applied to a built-in `Check` method.

**Parameters** `strategy_fn` (`Callable[...]`, `SearchStrategy`) – add strategy to a check, using check statistics to generate a hypothesis strategy.

`pandera.strategies.series_strategy`(`pandera_dtype`, `strategy=None`, \*, `checks=None`, `nullable=False`, `allow_duplicates=True`, `name=None`, `size=None`)

Strategy to generate a pandas Series.

#### Parameters

- **`pandera_dtype`** (`Union`[`DataType`, `DataType`]) – `pandera.dtypes.DataType` instance.
- **`strategy`** (`Optional`[`SearchStrategy`]) – an optional hypothesis strategy. If specified, the pandas dtype strategy will be chained onto this strategy.
- **`checks`** (`Optional`[`Sequence`]) – sequence of `Check`s to constrain the values of the data in the column/index.
- **`nullable`** (`Optional`[`bool`]) – whether or not generated Series contains null values.
- **`allow_duplicates`** (`Optional`[`bool`]) – whether or not generated Series contains duplicates.
- **`name`** (`Optional`[`str`]) – name of the Series.
- **`size`** (`Optional`[`int`]) – number of elements in the Series.

**Returns** hypothesis strategy.

`pandera.strategies.str_contains_strategy`(`pandera_dtype`, `strategy=None`, \*, `pattern`)

Strategy to generate strings that contain a particular pattern.

#### Parameters

- **`pandera_dtype`** (`Union`[`DataType`, `DataType`]) – `pandera.dtypes.DataType` instance.
- **`strategy`** (`Optional`[`SearchStrategy`]) – an optional hypothesis strategy. If specified, the pandas dtype strategy will be chained onto this strategy.
- **`pattern`** (`str`) – regex pattern.

**Return type** `SearchStrategy`

**Returns** hypothesis strategy

`pandera.strategies.str_endswith_strategy`(`pandera_dtype`, `strategy=None`, \*, `string`)

Strategy to generate strings that end with a specific string pattern.

#### Parameters

- **`pandera_dtype`** (`Union`[`DataType`, `DataType`]) – `pandera.dtypes.DataType` instance.
- **`strategy`** (`Optional`[`SearchStrategy`]) – an optional hypothesis strategy. If specified, the pandas dtype strategy will be chained onto this strategy.
- **`string`** (`str`) – string pattern.

**Return type** `SearchStrategy`

**Returns** hypothesis strategy

`pandera.strategies.str_length_strategy`(`pandera_dtype`, `strategy=None`, \*, `min_value`, `max_value`)

Strategy to generate strings of a particular length

#### Parameters

- **`pandera_dtype`** (`Union`[`DataType`, `DataType`]) – `pandera.dtypes.DataType` instance.

- **strategy** (`Optional[SearchStrategy]`) – an optional hypothesis strategy. If specified, the pandas dtype strategy will be chained onto this strategy.
- **min\_value** (`int`) – minimum string length.
- **max\_value** (`int`) – maximum string length.

**Return type** SearchStrategy

**Returns** hypothesis strategy

`pandera.strategies.str_matches_strategy(pandera_dtype, strategy=None, *, pattern)`

Strategy to generate strings that patch a regex pattern.

**Parameters**

- **pandera\_dtype** (`Union[DataType, DataType]`) – `pandera.dtypes.DataType` instance.
- **strategy** (`Optional[SearchStrategy]`) – an optional hypothesis strategy. If specified, the pandas dtype strategy will be chained onto this strategy.
- **pattern** (`str`) – regex pattern.

**Return type** SearchStrategy

**Returns** hypothesis strategy

`pandera.strategies.str_startswith_strategy(pandera_dtype, strategy=None, *, string)`

Strategy to generate strings that start with a specific string pattern.

**Parameters**

- **pandera\_dtype** (`Union[DataType, DataType]`) – `pandera.dtypes.DataType` instance.
- **strategy** (`Optional[SearchStrategy]`) – an optional hypothesis strategy. If specified, the pandas dtype strategy will be chained onto this strategy.
- **string** (`str`) – string pattern.

**Return type** SearchStrategy

**Returns** hypothesis strategy

`pandera.strategies.to_numpy_dtype(pandera_dtype)`

Convert a `DataType` to numpy dtype compatible with hypothesis.

`pandera.strategies.verify_dtype(pandera_dtype, schema_type, name)`

Verify that `pandera_dtype` argument is not None.

## 6.13.8 Extensions

### 6.13.8.1 pandera.extensions

pandera API extensions

*new in 0.6.0*

This module provides utilities for extending the pandera API.

**class** `pandera.extensions.CheckType`(*value*)

Bases: `enum.Enum`

Check types for registered check methods.

**VECTORIZED = 1**

Check applied to a Series or DataFrame

**ELEMENT\_WISE = 2**

Check applied to an element of a Series or DataFrame

**GROUPBY = 3**

Check applied to dictionary of Series or DataFrames.

`pandera.extensions.register_check_method`(*check\_fn=None*, \*, *statistics=None*, *supported\_types=(`<class 'pandas.core.frame.DataFrame'>`, `<class 'pandas.core.series.Series'>`)*, *check\_type='vectorized'*, *strategy=None*)

Registers a function as a *Check* method.

See the *user guide* for more details.

#### Parameters

- **check\_fn** – check function to register. The function should take one positional argument for the object to validate and additional keyword-only arguments for the check statistics.
- **statistics** (`Optional[List[str]]`) – list of keyword-only arguments in the `check_fn`, which serve as the statistics needed to serialize/de-serialize the check and generate data if a `strategy` function is provided.
- **supported\_types** (`Union[type, Tuple, List]`) – the pandas type(s) supported by the check function. Valid values are `pd.DataFrame`, `pd.Series`, or a list/tuple of (`pa.DataFrame`, `pa.Series`) if both types are supported.
- **check\_type** (`Union[CheckType, str]`) – the expected input of the check function. Valid values are `CheckType` enums or `{"vectorized", "element_wise", "groupby"}`. The input signature of `check_fn` is determined by this argument:
  - if `vectorized`, the first positional argument of `check_fn` should be one of the `supported_types`.
  - if `element_wise`, the first positional argument of `check_fn` should be a single scalar element in the pandas Series or DataFrame.
  - if `groupby`, the first positional argument of `check_fn` should be a dictionary mapping group names to subsets of the Series or DataFrame.
- **strategy** – data-generation strategy associated with the check function.

**Returns** register check function wrapper.

## 6.13.9 Errors

<code>pandera.errors.SchemaError</code>	Raised when object does not pass schema validation constraints.
<code>pandera.errors.SchemaErrors</code>	Raised when multiple schema are lazily collected into one error.
<code>pandera.errors.SchemaInitError</code>	Raised when schema initialization fails.
<code>pandera.errors.SchemaDefinitionError</code>	Raised when schema definition is invalid on object validation.

### 6.13.9.1 `pandera.errors.SchemaError`

```
class pandera.errors.SchemaError(schema, data, message, failure_cases=None, check=None,
                                check_index=None, check_output=None)
```

Raised when object does not pass schema validation constraints.

### 6.13.9.2 `pandera.errors.SchemaErrors`

```
class pandera.errors.SchemaErrors(schema_errors, data)
```

Raised when multiple schema are lazily collected into one error.

### 6.13.9.3 `pandera.errors.SchemaInitError`

```
class pandera.errors.SchemaInitError
```

Raised when schema initialization fails.

### 6.13.9.4 `pandera.errors.SchemaDefinitionError`

```
class pandera.errors.SchemaDefinitionError
```

Raised when schema definition is invalid on object validation.

## 6.14 Contributing

Whether you are a novice or experienced software developer, all contributions and suggestions are welcome!

### 6.14.1 Getting Started

If you are looking to contribute to the *pandera* codebase, the best place to start is the [GitHub “issues” tab](#). This is also a great place for filing bug reports and making suggestions for ways in which we can improve the code and documentation.

## 6.14.2 Contributing to the Codebase

The code is hosted on [GitHub](#), so you will need to use [Git](#) to clone the project and make changes to the codebase.

First create your own fork of pandera, then clone it:

```
# replace <my-username> with your github username
git clone https://github.com/<my-username>/pandera.git
```

Once you've obtained a copy of the code, create a development environment that's separate from your existing Python environment so that you can make and test changes without compromising your own work environment.

An excellent guide on setting up python environments can be found [here](#). Pandera offers a `environment.yml` to set up a conda-based environment and `requirements-dev.txt` for a virtualenv.

### 6.14.2.1 Environment Setup

#### 6.14.2.1.1 Option 1: miniconda Setup

Install [miniconda](#), then run:

```
conda create -n pandera-dev python=3.8 # or any python version 3.7+
conda env update -n pandera-dev -f environment.yml
conda activate pandera-dev
pip install -e .
```

#### 6.14.2.1.2 Option 2: virtualenv Setup

```
pip install virtualenv
virtualenv .venv/pandera-dev
source .venv/pandera-dev/bin/activate
pip install -r requirements-dev.txt
pip install -e .
```

#### 6.14.2.1.3 Run Tests

```
pytest tests
```

#### 6.14.2.1.4 Build Documentation Locally

```
make docs
```

#### 6.14.2.1.5 Set up pre-commit

This project uses `pre-commit` to ensure that code standard checks pass locally before pushing to the remote project repo. Follow the [installation instructions](#), then set up hooks with `pre-commit install`. After, `black`, `pylint` and `mypy` checks should be run with every commit.

Make sure everything is working correctly by running

```
pre-commit run --all
```

#### 6.14.2.2 Making Changes

Before making changes to the codebase or documentation, create a new branch with:

```
git checkout -b <my-branch>
```

We recommend following the branch-naming convention described in [Making Pull Requests](#).

#### 6.14.2.3 Run the Full Test Suite Locally

Before submitting your changes for review, make sure to check that your changes do not break any tests by running:

```
# option 1: if you're working with conda (recommended)
$ make nox-conda

# option 2: if you're working with virtualenv
$ make nox
```

Option 2 assumes that you have python environments for all of the versions that pandera supports.

##### 6.14.2.3.1 Using mamba (optional)

You can also use `mamba`, which is a faster implementation of `miniconda`, to run the `nox` test suite. Simply install it via `conda-forge`, and `make nox-conda` should use it under the hood.

```
$ conda install -c conda-forge mamba
$ make nox-conda
```

#### 6.14.2.4 Project Releases

Releases are organized under `milestones`, which are be associated with a corresponding branch. This project uses [semantic versioning](#), and we recommend prioritizing issues associated with the next release.



### 6.14.2.5 Contributing Documentation

Maybe the easiest, fastest, and most useful way to contribute to this project (and any other project) is to contribute documentation. If you find an API within the project that doesn't have an example or description, or could be clearer in its explanation, contribute yours!

You can also find issues for improving documentation under the [docs](#) label. If you have ideas for documentation improvements, you can create a new issue [here](#)

This project uses Sphinx for auto-documentation and RST syntax for docstrings. Once you have the code downloaded and you find something that is in need of some TLD, take a look at the [Sphinx](#) documentation or well-documented [examples](#) within the codebase for guidance on contributing.

You can build the html documentation by running `nox -s docs`. The built documentation can be found in `docs/_build`.

### 6.14.2.6 Contributing Bugfixes

Bugs are reported under the [bug](#) label, so if you find a bug create a new issue [here](#).

### 6.14.2.7 Contributing Enhancements

New feature issues can be found under the [enhancements](#) label. You can request a feature by creating a new issue [here](#).

### 6.14.2.8 Making Pull Requests

Once your changes are ready to be submitted, make sure to push your changes to your fork of the GitHub repo before creating a pull request. Depending on the type of issue the pull request is resolving, your pull request should merge onto the appropriate branch:

#### 6.14.2.8.1 Bugfixes

- branch naming convention: `bugfix/<issue number>` or `bugfix/<bugfix-name>`
- pull request to: `dev`

#### 6.14.2.8.2 Documentation

- branch naming convention: `docs/<issue number>` or `docs/<doc-name>`
- pull request to: `release/x.x.x` branch if specified in the issue milestone, otherwise `dev`

### 6.14.2.8.3 Enhancements

- branch naming convention: `feature/<issue number>` or `feature/<bugfix-name>`
- pull request to: `release/x.x.x` branch if specified in the issue milestone, otherwise `dev`

We will review your changes, and might ask you to make additional changes before it is finally ready to merge. However, once it's ready, we will merge it, and you will have successfully contributed to the codebase!

### 6.14.2.9 Questions, Ideas, General Discussion

Head on over to the [discussion](#) section if you have questions or ideas, want to show off something that you did with pandera, or want to discuss a topic related to the project.

### 6.14.2.10 Dataframe Schema Style Guides

We have guidelines regarding dataframe and schema styles that are encouraged for each pull request:

- If specifying a single column DataFrame, this can be expressed as a one-liner:

```
DataFrameSchema({"col1": Column(...)})
```

- If specifying one column with multiple lines, or multiple columns:

```
DataFrameSchema(
    {
        "col1": Column(
            int,
            checks=[
                Check(...),
                Check(...),
            ]
        ),
    }
)
```

- If specifying columns with additional arguments that fit in one line:

```
DataFrameSchema(
    {"a": Column(int, nullable=True)},
    strict=True
)
```

- If specifying columns with additional arguments that don't fit in one line:

```
DataFrameSchema(
    {
        "a": Column(
            int,
            nullable=True,
            coerce=True,
            ...
        ),
        "b": Column(
```

(continues on next page)

---

(continued from previous page)

```
        ...,  
    )  
},  
strict=True)
```



## HOW TO CITE

If you use `pandera` in the context of academic or industry research, please consider citing the paper and/or software package.

### 7.1 Paper

```
@InProceedings{ niels_bantilan-proc-scipy-2020,  
  author    = { {N}iels {B}antilan },  
  title     = { pandera: {S}tatistical {D}ata {V}alidation of {P}andas {D}ataframes },  
  booktitle = { {P}roceedings of the 19th {P}ython in {S}cience {C}onference },  
  pages     = { 116 - 124 },  
  year      = { 2020 },  
  editor    = { {M}eghann {A}garwal and {C}hris {C}alloway and {D}illon {N}iederhut and  
↪{D}avid {S}hupe },  
  doi       = { 10.25080/Majora-342d178e-010 }  
}
```

### 7.2 Software Package



## LICENSE AND CREDITS

pandera is licensed under the [MIT license](#). and is written and maintained by Niels Bantilan ([niels@pandera.ci](mailto:niels@pandera.ci))





## INDICES AND TABLES

- `genindex`



## PYTHON MODULE INDEX

### p

`pandera.extensions`, 177  
`pandera.strategies`, 170  
`pandera.typing`, 163



## Symbols

- `__call__` () (*pandera.checks.Check* method), 106
- `__call__` () (*pandera.dtypes.Bool* method), 116
- `__call__` () (*pandera.dtypes.Category* method), 120
- `__call__` () (*pandera.dtypes.Complex* method), 136
- `__call__` () (*pandera.dtypes.Complex128* method), 138
- `__call__` () (*pandera.dtypes.Complex256* method), 139
- `__call__` () (*pandera.dtypes.Complex64* method), 137
- `__call__` () (*pandera.dtypes.DataType* method), 115
- `__call__` () (*pandera.dtypes.Float* method), 121
- `__call__` () (*pandera.dtypes.Float128* method), 125
- `__call__` () (*pandera.dtypes.Float16* method), 122
- `__call__` () (*pandera.dtypes.Float32* method), 123
- `__call__` () (*pandera.dtypes.Float64* method), 124
- `__call__` () (*pandera.dtypes.Int* method), 126
- `__call__` () (*pandera.dtypes.Int16* method), 128
- `__call__` () (*pandera.dtypes.Int32* method), 129
- `__call__` () (*pandera.dtypes.Int64* method), 130
- `__call__` () (*pandera.dtypes.Int8* method), 127
- `__call__` () (*pandera.dtypes.String* method), 140
- `__call__` () (*pandera.dtypes.Timedelta* method), 119
- `__call__` () (*pandera.dtypes.Timestamp* method), 117
- `__call__` () (*pandera.dtypes.UInt* method), 131
- `__call__` () (*pandera.dtypes.UInt16* method), 133
- `__call__` () (*pandera.dtypes.UInt32* method), 134
- `__call__` () (*pandera.dtypes.UInt64* method), 135
- `__call__` () (*pandera.dtypes.UInt8* method), 132
- `__call__` () (*pandera.engines.engine.Engine* method), 156
- `__call__` () (*pandera.engines.numpy\_engine.Object* method), 151
- `__call__` () (*pandera.engines.pandas\_engine.BOOL* method), 141
- `__call__` () (*pandera.engines.pandas\_engine.INT16* method), 143
- `__call__` () (*pandera.engines.pandas\_engine.INT32* method), 144
- `__call__` () (*pandera.engines.pandas\_engine.INT64* method), 145
- `__call__` () (*pandera.engines.pandas\_engine.INT8* method), 142
- `__call__` () (*pandera.engines.pandas\_engine.STRING* method), 150
- `__call__` () (*pandera.engines.pandas\_engine.UINT16* method), 147
- `__call__` () (*pandera.engines.pandas\_engine.UINT32* method), 148
- `__call__` () (*pandera.engines.pandas\_engine.UINT64* method), 149
- `__call__` () (*pandera.engines.pandas\_engine.UINT8* method), 146
- `__call__` () (*pandera.hypotheses.Hypothesis* method), 113
- `__call__` () (*pandera.schema\_components.Column* method), 90
- `__call__` () (*pandera.schema\_components.Index* method), 92
- `__call__` () (*pandera.schema\_components.MultiIndex* method), 96
- `__call__` () (*pandera.schemas.DataFrameSchema* method), 83
- `__call__` () (*pandera.schemas.SeriesSchema* method), 86
- `__init__` () (*pandera.dtypes.Bool* method), 116
- `__init__` () (*pandera.dtypes.Category* method), 119
- `__init__` () (*pandera.dtypes.Complex* method), 135
- `__init__` () (*pandera.dtypes.Complex128* method), 137
- `__init__` () (*pandera.dtypes.Complex256* method), 138
- `__init__` () (*pandera.dtypes.Complex64* method), 136
- `__init__` () (*pandera.dtypes.DataType* method), 115
- `__init__` () (*pandera.dtypes.Float* method), 120
- `__init__` () (*pandera.dtypes.Float128* method), 124
- `__init__` () (*pandera.dtypes.Float16* method), 121
- `__init__` () (*pandera.dtypes.Float32* method), 122
- `__init__` () (*pandera.dtypes.Float64* method), 123
- `__init__` () (*pandera.dtypes.Int* method), 125
- `__init__` () (*pandera.dtypes.Int16* method), 127
- `__init__` () (*pandera.dtypes.Int32* method), 128
- `__init__` () (*pandera.dtypes.Int64* method), 129
- `__init__` () (*pandera.dtypes.Int8* method), 126
- `__init__` () (*pandera.dtypes.String* method), 139
- `__init__` () (*pandera.dtypes.Timedelta* method), 118
- `__init__` () (*pandera.dtypes.Timestamp* method), 117
- `__init__` () (*pandera.dtypes.UInt* method), 130

- `__init__()` (*pandera.dtypes.UInt16 method*), 132
  - `__init__()` (*pandera.dtypes.UInt32 method*), 133
  - `__init__()` (*pandera.dtypes.UInt64 method*), 134
  - `__init__()` (*pandera.dtypes.UInt8 method*), 131
  - `__init__()` (*pandera.engines.numpy\_engine.Object method*), 151
  - `__init__()` (*pandera.engines.pandas\_engine.BOOL method*), 141
  - `__init__()` (*pandera.engines.pandas\_engine.INT16 method*), 143
  - `__init__()` (*pandera.engines.pandas\_engine.INT32 method*), 144
  - `__init__()` (*pandera.engines.pandas\_engine.INT64 method*), 145
  - `__init__()` (*pandera.engines.pandas\_engine.INT8 method*), 142
  - `__init__()` (*pandera.engines.pandas\_engine.STRING method*), 150
  - `__init__()` (*pandera.engines.pandas\_engine.UINT16 method*), 147
  - `__init__()` (*pandera.engines.pandas\_engine.UINT32 method*), 148
  - `__init__()` (*pandera.engines.pandas\_engine.UINT64 method*), 149
  - `__init__()` (*pandera.engines.pandas\_engine.UINT8 method*), 146
  - `__init__()` (*pandera.hypotheses.Hypothesis method*), 109
  - `__init__()` (*pandera.schema\_components.Column method*), 88
  - `__init__()` (*pandera.schema\_components.MultiIndex method*), 94
  - `__init__()` (*pandera.schemas.DataFrameSchema method*), 71
  - `__init__()` (*pandera.schemas.SeriesSchema method*), 84
- ## A
- `add_columns()` (*pandera.schemas.DataFrameSchema method*), 72
  - `allow_duplicates` (*pandera.io.FrictionlessFieldParser property*), 67
- ## B
- `BaseConfig` (*class in pandera.model*), 164
  - `Bool` (*class in pandera.dtypes*), 116
  - `BOOL` (*class in pandera.engines.pandas\_engine*), 140
- ## C
- `Category` (*class in pandera.dtypes*), 119
  - `Check` (*class in pandera.checks*), 97
  - `check()` (*in module pandera.model\_components*), 162
  - `check()` (*pandera.dtypes.Bool method*), 116
  - `check()` (*pandera.dtypes.Category method*), 119
  - `check()` (*pandera.dtypes.Complex method*), 135
  - `check()` (*pandera.dtypes.Complex128 method*), 137
  - `check()` (*pandera.dtypes.Complex256 method*), 138
  - `check()` (*pandera.dtypes.Complex64 method*), 136
  - `check()` (*pandera.dtypes.DataType method*), 115
  - `check()` (*pandera.dtypes.Float method*), 120
  - `check()` (*pandera.dtypes.Float128 method*), 124
  - `check()` (*pandera.dtypes.Float16 method*), 121
  - `check()` (*pandera.dtypes.Float32 method*), 122
  - `check()` (*pandera.dtypes.Float64 method*), 123
  - `check()` (*pandera.dtypes.Int method*), 125
  - `check()` (*pandera.dtypes.Int16 method*), 127
  - `check()` (*pandera.dtypes.Int32 method*), 128
  - `check()` (*pandera.dtypes.Int64 method*), 129
  - `check()` (*pandera.dtypes.Int8 method*), 126
  - `check()` (*pandera.dtypes.String method*), 139
  - `check()` (*pandera.dtypes.Timedelta method*), 118
  - `check()` (*pandera.dtypes.Timestamp method*), 117
  - `check()` (*pandera.dtypes.UInt method*), 130
  - `check()` (*pandera.dtypes.UInt16 method*), 132
  - `check()` (*pandera.dtypes.UInt32 method*), 133
  - `check()` (*pandera.dtypes.UInt64 method*), 134
  - `check()` (*pandera.dtypes.UInt8 method*), 131
  - `check()` (*pandera.engines.numpy\_engine.Object method*), 151
  - `check()` (*pandera.engines.pandas\_engine.BOOL method*), 141
  - `check()` (*pandera.engines.pandas\_engine.INT16 method*), 143
  - `check()` (*pandera.engines.pandas\_engine.INT32 method*), 144
  - `check()` (*pandera.engines.pandas\_engine.INT64 method*), 145
  - `check()` (*pandera.engines.pandas\_engine.INT8 method*), 142
  - `check()` (*pandera.engines.pandas\_engine.STRING method*), 150
  - `check()` (*pandera.engines.pandas\_engine.UINT16 method*), 147
  - `check()` (*pandera.engines.pandas\_engine.UINT32 method*), 148
  - `check()` (*pandera.engines.pandas\_engine.UINT64 method*), 149
  - `check()` (*pandera.engines.pandas\_engine.UINT8 method*), 146
  - `check_input()` (*in module pandera.decorators*), 165
  - `check_io()` (*in module pandera.decorators*), 167
  - `check_output()` (*in module pandera.decorators*), 166
  - `check_types()` (*in module pandera.decorators*), 168
  - `checks` (*pandera.io.FrictionlessFieldParser property*), 67
  - `CheckType` (*class in pandera.extensions*), 177
  - `coerce` (*pandera.io.FrictionlessFieldParser property*), 67

- `coerce()` (*pandera.dtypes.Bool* method), 116  
`coerce()` (*pandera.dtypes.Category* method), 120  
`coerce()` (*pandera.dtypes.Complex* method), 136  
`coerce()` (*pandera.dtypes.Complex128* method), 138  
`coerce()` (*pandera.dtypes.Complex256* method), 139  
`coerce()` (*pandera.dtypes.Complex64* method), 137  
`coerce()` (*pandera.dtypes.DataType* method), 115  
`coerce()` (*pandera.dtypes.Float* method), 121  
`coerce()` (*pandera.dtypes.Float128* method), 125  
`coerce()` (*pandera.dtypes.Float16* method), 122  
`coerce()` (*pandera.dtypes.Float32* method), 123  
`coerce()` (*pandera.dtypes.Float64* method), 124  
`coerce()` (*pandera.dtypes.Int* method), 126  
`coerce()` (*pandera.dtypes.Int16* method), 128  
`coerce()` (*pandera.dtypes.Int32* method), 129  
`coerce()` (*pandera.dtypes.Int64* method), 130  
`coerce()` (*pandera.dtypes.Int8* method), 127  
`coerce()` (*pandera.dtypes.String* method), 140  
`coerce()` (*pandera.dtypes.Timedelta* method), 118  
`coerce()` (*pandera.dtypes.Timestamp* method), 117  
`coerce()` (*pandera.dtypes.UInt* method), 131  
`coerce()` (*pandera.dtypes.UInt16* method), 133  
`coerce()` (*pandera.dtypes.UInt32* method), 134  
`coerce()` (*pandera.dtypes.UInt64* method), 135  
`coerce()` (*pandera.dtypes.UInt8* method), 132  
`coerce()` (*pandera.engines.numpy\_engine.Object* method), 151  
`coerce()` (*pandera.engines.pandas\_engine.BOOL* method), 141  
`coerce()` (*pandera.engines.pandas\_engine.INT16* method), 143  
`coerce()` (*pandera.engines.pandas\_engine.INT32* method), 144  
`coerce()` (*pandera.engines.pandas\_engine.INT64* method), 145  
`coerce()` (*pandera.engines.pandas\_engine.INT8* method), 142  
`coerce()` (*pandera.engines.pandas\_engine.STRING* method), 150  
`coerce()` (*pandera.engines.pandas\_engine.UINT16* method), 147  
`coerce()` (*pandera.engines.pandas\_engine.UINT32* method), 148  
`coerce()` (*pandera.engines.pandas\_engine.UINT64* method), 149  
`coerce()` (*pandera.engines.pandas\_engine.UINT8* method), 146  
`coerce_dtype()` (*pandera.schema\_components.Column* method), 89  
`coerce_dtype()` (*pandera.schema\_components.MultiIndex* method), 95  
`coerce_dtype()` (*pandera.schemas.DataFrameSchema* method), 73  
`Column` (*class in pandera.schema\_components*), 86  
`column_strategy()` (*in module pandera.strategies*), 170  
`Complex` (*class in pandera.dtypes*), 135  
`Complex128` (*class in pandera.dtypes*), 137  
`Complex256` (*class in pandera.dtypes*), 138  
`Complex64` (*class in pandera.dtypes*), 136  
**D**  
`dataframe_check()` (*in module pandera.model\_components*), 162  
`dataframe_strategy()` (*in module pandera.strategies*), 170  
`DataFrameSchema` (*class in pandera.schemas*), 68  
`DataType` (*class in pandera.dtypes*), 115  
`DateTime` (*in module pandera.dtypes*), 118  
`dtype` (*pandera.io.FrictionlessFieldParser* property), 67  
`dtype()` (*pandera.engines.engine.Engine* method), 155  
`dtype()` (*pandera.engines.numpy\_engine.Engine* class method), 156  
`dtype()` (*pandera.engines.pandas\_engine.Engine* class method), 156  
**E**  
`ELEMENT_WISE` (*pandera.extensions.CheckType* attribute), 177  
`Engine` (*class in pandera.engines.engine*), 154  
`Engine` (*class in pandera.engines.numpy\_engine*), 156  
`Engine` (*class in pandera.engines.pandas\_engine*), 156  
`eq()` (*pandera.checks.Check* class method), 100  
`eq_strategy()` (*in module pandera.strategies*), 171  
`equal_to()` (*pandera.checks.Check* class method), 100  
`example()` (*pandera.model.SchemaModel* class method), 159  
`example()` (*pandera.schema\_components.Column* method), 89  
`example()` (*pandera.schema\_components.Index* method), 91  
`example()` (*pandera.schema\_components.MultiIndex* method), 95  
`example()` (*pandera.schemas.DataFrameSchema* method), 73  
**F**  
`Field()` (*in module pandera.model\_components*), 161  
`field_element_strategy()` (*in module pandera.strategies*), 171  
`Float` (*class in pandera.dtypes*), 120  
`Float128` (*class in pandera.dtypes*), 124  
`Float16` (*class in pandera.dtypes*), 121  
`Float32` (*class in pandera.dtypes*), 122  
`Float64` (*class in pandera.dtypes*), 123  
`FrictionlessFieldParser` (*class in pandera.io*), 67

- from\_frictionless\_schema() (in module *pandera.io*), 66  
 from\_parametrized\_dtype() (pandera.engines.pandas\_engine.STRING class method), 150  
 from\_yaml() (in module *pandera.io*), 169  
 from\_yaml() (pandera.schemas.DataFrameSchema class method), 73
- ## G
- ge() (pandera.checks.Check class method), 100  
 ge\_strategy() (in module *pandera.strategies*), 171  
 get\_dtypes() (pandera.schemas.DataFrameSchema method), 74  
 get\_regex\_columns() (pandera.schema\_components.Column method), 89  
 get\_registered\_dtypes() (pandera.engines.engine.Engine method), 155  
 greater\_than() (pandera.checks.Check class method), 101  
 greater\_than\_or\_equal\_to() (pandera.checks.Check class method), 101  
 GROUPBY (pandera.extensions.CheckType attribute), 177  
 gt() (pandera.checks.Check class method), 101  
 gt\_strategy() (in module *pandera.strategies*), 171
- ## H
- Hypothesis (class in *pandera.hypotheses*), 106
- ## I
- immutable() (in module *pandera.dtypes*), 154  
 in\_range() (pandera.checks.Check class method), 102  
 in\_range\_strategy() (in module *pandera.strategies*), 172  
 Index (class in *pandera.schema\_components*), 90  
 index\_strategy() (in module *pandera.strategies*), 172  
 infer\_schema() (in module *pandera.schema\_inference*), 169  
 Int (class in *pandera.dtypes*), 125  
 Int16 (class in *pandera.dtypes*), 127  
 INT16 (class in *pandera.engines.pandas\_engine*), 142  
 Int32 (class in *pandera.dtypes*), 128  
 INT32 (class in *pandera.engines.pandas\_engine*), 143  
 Int64 (class in *pandera.dtypes*), 129  
 INT64 (class in *pandera.engines.pandas\_engine*), 144  
 Int8 (class in *pandera.dtypes*), 126  
 INT8 (class in *pandera.engines.pandas\_engine*), 141  
 is\_bool() (in module *pandera.dtypes*), 153  
 is\_complex() (in module *pandera.dtypes*), 153  
 is\_datetime() (in module *pandera.dtypes*), 153  
 is\_float() (in module *pandera.dtypes*), 152  
 is\_int() (in module *pandera.dtypes*), 152  
 is\_numeric() (in module *pandera.dtypes*), 153  
 is\_string() (in module *pandera.dtypes*), 153  
 is\_subdtype() (in module *pandera.dtypes*), 152  
 is\_timedelta() (in module *pandera.dtypes*), 153  
 is\_uint() (in module *pandera.dtypes*), 152  
 isin() (pandera.checks.Check class method), 102  
 isin\_strategy() (in module *pandera.strategies*), 172
- ## L
- le() (pandera.checks.Check class method), 102  
 le\_strategy() (in module *pandera.strategies*), 173  
 less\_than() (pandera.checks.Check class method), 103  
 less\_than\_or\_equal\_to() (pandera.checks.Check class method), 103  
 lt() (pandera.checks.Check class method), 103  
 lt\_strategy() (in module *pandera.strategies*), 173
- ## M
- module  
     pandera.extensions, 177  
     pandera.strategies, 170  
     pandera.typing, 163  
 MultiIndex (class in *pandera.schema\_components*), 93  
 multiindex\_strategy() (in module *pandera.strategies*), 173
- ## N
- ne() (pandera.checks.Check class method), 104  
 ne\_strategy() (in module *pandera.strategies*), 173  
 not\_equal\_to() (pandera.checks.Check class method), 104  
 notin() (pandera.checks.Check class method), 104  
 notin\_strategy() (in module *pandera.strategies*), 174  
 nullable (pandera.io.FrictionlessFieldParser property), 67  
 numpy\_complex\_dtypes() (in module *pandera.strategies*), 174  
 numpy\_dtype() (pandera.engines.pandas\_engine.Engine class method), 157  
 numpy\_time\_dtypes() (in module *pandera.strategies*), 174
- ## O
- Object (class in *pandera.engines.numpy\_engine*), 150  
 one\_sample\_ttest() (pandera.hypotheses.Hypothesis class method), 110
- ## P
- pandas\_dtype\_strategy() (in module *pandera.strategies*), 174  
 PandasDtype (class in *pandera.engines.pandas\_engine*), 157  
 pandera.extensions  
     module, 177



pandera.strategies  
module, 170

pandera.typing  
module, 163

## R

regex (*pandera.io.FrictionlessFieldParser* property), 67

register\_check\_method() (in module *pandera.extensions*), 177

register\_check\_strategy() (in module *pandera.strategies*), 174

register\_dtype() (*pandera.engines.engine.Engine* method), 155

remove\_columns() (*pandera.schemas.DataFrameSchema* method), 74

rename\_columns() (*pandera.schemas.DataFrameSchema* method), 75

required (*pandera.io.FrictionlessFieldParser* property), 68

reset\_index() (*pandera.schemas.DataFrameSchema* method), 76

## S

SchemaDefinitionError (class in *pandera.errors*), 178

SchemaError (class in *pandera.errors*), 178

SchemaErrors (class in *pandera.errors*), 178

SchemaInitError (class in *pandera.errors*), 178

SchemaModel (class in *pandera.model*), 159

select\_columns() (*pandera.schemas.DataFrameSchema* method), 77

series\_strategy() (in module *pandera.strategies*), 175

SeriesSchema (class in *pandera.schemas*), 83

set\_index() (*pandera.schemas.DataFrameSchema* method), 78

set\_name() (*pandera.schema\_components.Column* method), 89

str\_contains() (*pandera.checks.Check* class method), 105

str\_contains\_strategy() (in module *pandera.strategies*), 175

str\_endswith() (*pandera.checks.Check* class method), 105

str\_endswith\_strategy() (in module *pandera.strategies*), 175

str\_length() (*pandera.checks.Check* class method), 105

str\_length\_strategy() (in module *pandera.strategies*), 175

str\_matches() (*pandera.checks.Check* class method), 105

str\_matches\_strategy() (in module *pandera.strategies*), 176

str\_startswith() (*pandera.checks.Check* class method), 106

str\_startswith\_strategy() (in module *pandera.strategies*), 176

strategy() (*pandera.model.SchemaModel* class method), 159

strategy() (*pandera.schema\_components.Column* method), 89

strategy() (*pandera.schema\_components.Index* method), 92

strategy() (*pandera.schema\_components.MultiIndex* method), 95

strategy() (*pandera.schemas.DataFrameSchema* method), 79

strategy\_component() (*pandera.schema\_components.Column* method), 90

strategy\_component() (*pandera.schema\_components.Index* method), 92

String (class in *pandera.dtypes*), 139

STRING (class in *pandera.engines.pandas\_engine*), 149

## T

Timedelta (class in *pandera.dtypes*), 118

Timestamp (class in *pandera.dtypes*), 117

to\_numpy\_dtype() (in module *pandera.strategies*), 176

to\_pandera\_column() (*pandera.io.FrictionlessFieldParser* method), 68

to\_schema() (*pandera.model.SchemaModel* class method), 160

to\_script() (in module *pandera.io*), 170

to\_script() (*pandera.schemas.DataFrameSchema* method), 80

to\_yaml() (in module *pandera.io*), 169

to\_yaml() (*pandera.model.SchemaModel* class method), 160

to\_yaml() (*pandera.schemas.DataFrameSchema* method), 80

two\_sample\_ttest() (*pandera.hypotheses.Hypothesis* class method), 112

## U

UInt (class in *pandera.dtypes*), 130

UInt16 (class in *pandera.dtypes*), 132

UINT16 (class in *pandera.engines.pandas\_engine*), 146

UInt32 (class in *pandera.dtypes*), 133

UINT32 (class in *pandera.engines.pandas\_engine*), 147

UInt64 (class in *pandera.dtypes*), 134

UINT64 (class in *pandera.engines.pandas\_engine*), 148

UInt8 (class in *pandera.dtypes*), 131

UINT8 (*class in pandera.engines.pandas\_engine*), 145  
update\_column() (*pandera.schemas.DataFrameSchema method*),  
80  
update\_columns() (*pandera.schemas.DataFrameSchema method*),  
81

## V

validate() (*pandera.model.SchemaModel class method*), 160  
validate() (*pandera.schema\_components.Column method*), 90  
validate() (*pandera.schema\_components.Index method*), 92  
validate() (*pandera.schema\_components.MultiIndex method*), 96  
validate() (*pandera.schemas.DataFrameSchema method*), 82  
validate() (*pandera.schemas.SeriesSchema method*),  
85  
VECTORIZED (*pandera.extensions.CheckType attribute*),  
177  
verify\_dtype() (*in module pandera.strategies*), 176